



debian

Leitfaden für Debian-Betreuer

Osamu Aoki, Helge Kreutzmann und Mechtilde
Stehmann

3. Februar 2026

Leitfaden für Debian-Betreuer

by Osamu Aoki, Helge Kreutzmann und Mechtilde Stehmann

Copyright © 2014-2026 Osamu Aoki

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Diese Anleitung wurde mit den nachfolgenden Dokumenten als Referenz erstellt:

- »Making a Debian Package (AKA the Debmake Manual)«, Copyright © 1997 Jaldhar Vyas.
- »The New-Maintainer's Debian Packaging Howto«, Copyright © 1997 Will Lowe.
- »Debian-Leitfaden für Neue Paketbetreuer«, Copyright © 1998-2002 Josip Rodin, 2005-2017 Osamu Aoki, 2010 Craig Small und 2010 Raphaël Hertzog.

Die neuste Version dieser Anleitung sollte

- im Paket „[debmake-doc](#)“ und
- auf der „[Debian-Dokumentations-Website](#)“ verfügbar sein.

Inhaltsverzeichnis

1	Vorwort	1
2	Überblick	3
3	Voraussetzungen	5
3.1	Leute bei Debian	5
3.2	Wie Sie beitragen können	5
3.3	Soziale Dynamik von Debian	6
3.4	Technische Erinnerungen	6
3.5	Debian-Dokumentation	7
3.6	Hilfequellen	8
3.7	Archivsituation	8
3.8	Wege, beizutragen	9
3.9	Neue Beitragende und Betreuer	10
4	Werkzeugeinrichtung	12
4.1	Email setup	12
4.2	mc setup	13
4.3	git setup	13
4.4	quilt setup	13
4.5	devscripts setup	14
4.6	sbuild setup	14
4.7	Persistent chroot setup	16
4.8	gbp setup	17
4.9	HTTP-Proxy	17
4.10	Privates Debian-Depot	17
4.11	Virtuelle Maschinen	17
4.12	Local network with virtual machines	17
5	Simple packaging	18
5.1	Packaging tarball	18
5.2	Gesamtbild	18
5.3	Was ist Debmake?	19
5.4	Was ist Debuild?	20
5.5	Schritt 1: Holen der Quellen der Originalautoren	20
5.6	Step 2: Generate template files with debmake	21
5.7	Schritt 3: Anpassung der Vorlagendateien	26
5.8	Step 4: Building package with debuild	28
5.9	Step 3 (alternatives): Modification to the upstream source	30
5.10	Patch by „diff -u“ approach	31
5.11	Patch by dquilt approach	32
5.12	Patch by „ dpkg-source --auto-commit “ approach	34
6	Basics for packaging	37
6.1	Arbeitsablauf des Paketierens	37
6.2	debhelper package	39
6.3	Paketname und -version	40
6.4	Natives Debian-Paket	41
6.5	debian/rules file	41
6.6	debian/control file	42
6.7	debian/changelog file	43
6.8	debian/copyright file	44
6.9	debian/patches/* files	44
6.10	debian/source/include-binaries file	45

6.11	debian/watch file	45
6.12	debian/upstream/signing-key.asc file	45
6.13	debian/salsa-ci.yml file	46
6.14	Other debian/* files	46
7	Quality of packaging	51
7.1	Reformat debian/* files with wrap-and-sort	51
7.2	Validate debian/* files with deputy	51
8	Sanitization of the source	52
8.1	Fix with Files-Excluded	52
8.2	Fix with „ debian/rules clean “	53
8.3	Fix with extend-diff-ignore	53
8.4	Fix with tar-ignore	53
8.5	Fix with „ git clean -dfx “	54
9	More on packaging	55
9.1	Package customization	55
9.2	Customized debian/rules	55
9.3	Variables for debian/rules	56
9.4	New upstream release	56
9.5	Manage patch queue with dquilt	57
9.6	Build commands	57
9.7	Note on sbuild	57
9.8	Special build cases	58
9.9	Upload orig.tar.xz	58
9.10	Skipped uploads	59
9.11	Bug reports	59
10	Advanced packaging	61
10.1	Historical perspective	61
10.2	Current trends	61
10.3	Note on build system	62
10.4	Continuous integration	62
10.5	Bootstrapping	62
10.6	Compiler hardening	63
10.7	Reproduzierbares Bauen	63
10.8	Substvar	63
10.9	Bibliothekspaket	64
10.10	Multiarch	65
10.11	Aufteilung eines Debian-Binärpakets	65
10.12	Paketentrennungsszenarien und -beispiele	66
10.13	Multiarch library path	66
10.14	Multiarch header file path	67
10.15	Multiarch *.pc file path	67
10.16	Bibliothekssymbole	67
10.17	Library package name	68
10.18	Bibliotheksubergänge	69
10.19	binNMU-sicher	69
10.20	Fehlersuchinformationen	70
10.21	dbgsym package	70
10.22	debconf	70
11	Packaging with git	72
11.1	Salsa repository	73
11.2	Salsa account setup	73
11.3	Salsa CI service	73
11.4	Branch names	73
11.5	Patch unapplied Git repository	74

11.6 Patch by „ gbp-pq “ approach	74
11.7 Manage patch queue with gbp-pq	74
11.8 gbp import-dscs --debsnap	75
11.9 Note on gbp	75
11.10The Git repository browser	76
11.11Git commit history organization	76
11.12 Quasi-native Debian packaging	76
11.13Patch applied Git repository	77
11.14Note on dgit	77
12 Tipps	79
12.1 Build under UTF-8	79
12.2 UTF-8 conversion	79
12.3 Hints for Debugging	79
13 Tool usages	82
13.1 debdiff	82
13.2 dget	82
13.3 mk-origtargz	83
13.4 origtargz	83
13.5 git deborig	83
13.6 dpkg-source -b	83
13.7 dpkg-source -x	83
13.8 debc	83
13.9 piuparts	84
13.10 ts	84
13.11 dpkg-depcheck	84
14 Weitere Beispiele	85
14.1 Cherry-pick templates	85
14.2 Kein Makefile (Shell, CLI)	87
14.3 Makefile (Shell, CLI)	94
14.4 pyproject.toml (Python3, CLI)	97
14.5 Makefile (Shell, GUI)	103
14.6 pyproject.toml (Python3, GUI)	106
14.7 Makefile (Paket mit einem Programm)	109
14.8 Makefile.in + configure (Paket mit einem Programm)	112
14.9 Autotools (Paket mit einem Programm)	116
14.10CMake (Paket mit einem Programm)	120
14.11Autotools (Paket mit mehreren Programmen)	124
14.12CMake (multi-binary package)	131
14.13Internationalization	136
14.14Details	142
15 debmake(1)-Handbuchseite	143
15.1 BEZEICHNUNG	143
15.2 ÜBERSICHT	143
15.3 BESCHREIBUNG	143
15.4 Positional arguments	144
15.5 Options	144
15.6 BEISPIELE	145
15.7 HELFERPAKETE	146
15.8 CAVEAT	146
15.9 DEBUG	147
15.10AUTOR	147
15.11LIZENZ	147
15.12SIEHE AUCH	147

16 debmake options	148
16.1 Shortcut option (-i)	148
16.2 debmake -b	148
16.3 debmake -B	149
16.4 debmake -x	149

Zusammenfassung

Dieser Anleitung »Leitfaden für Debian-Betreuer« (2026-02-03) beschreibt gewöhnlichen Debian-Benutzern und angehenden Entwicklern den Bau des Debian-Pakets mittels des Befehls **debmake**.

Diese Anleitung konzentriert sich auf die moderne Paketierart und enthält viele einfache Beispiele.

- POSIX-Shell-Skript-Paketierung
- Python3-Skript-Paketierung
- C mit Makefile/Autotools/CMake
- mehrere Binärpakete mit Laufzeitbibliotheken usw.

Diese »Anleitung für Debian-Betreuer« kann als Nachfolger des »Debian-Leitfaden für Neue Paketbetreuer« angesehen werden.

Kapitel 1

Vorwort

Falls Sie ein etwas erfahrener Debian-Benutzer [1](#) sind, könnten Ihnen die folgende Situationen bekannt vorkommen:

- Sie möchten ein bestimmtes, noch nicht im Debian-Archiv verfügbares Softwarepaket installieren.
- Sie möchten ein Debian-Paket mit einer neueren Version der Originalautoren aktualisieren.
- Sie möchten Fehler in einem Debian-Paket mit Patches korrigieren.

If you want to create a Debian package to fulfill these needs and share your work with the community, you are the target audience of this guide as a prospective Debian maintainer. [2](#) Welcome to the Debian community.

Debian has many social and technical rules and conventions to follow, as it is a large volunteer organization with a rich history. Debian has also developed an extensive array of packaging and archive maintenance tools to build consistent sets of binary packages that address many technical objectives:

- packages have clearly specified package dependencies and patches and build correctly from scratch in a clean build environment („Abschnitt [6.6](#)“, „Abschnitt [6.9](#)“, „Abschnitt [4.6](#)“)
- Paketbau unter vielen Architekturen („Abschnitt [9.3](#)“)
- builds are reproducible („Abschnitt [10.7](#)“)
- multiarch is supported („Abschnitt [10.10](#)“)
- bootstrapping new architectures is possible („Abschnitt [10.5](#)“)
- builds use specific compiler flags to harden security („Abschnitt [10.6](#)“)
- packages are split optimally into multiple binary packages („Abschnitt [10.11](#)“)
- library names and contents are managed to ensure smooth transitions on upgrades („Abschnitt [10.18](#)“)
- installations use interactive prompts correctly (if at all) („Abschnitt [10.22](#)“)
- continuous integration is used to ensure quality („Abschnitt [10.4](#)“)
- ...

These factors can be overwhelming for many new prospective Debian maintainers. This guide aims to provide entry points to help them get started. It covers the following:

- Was Sie wissen sollten, bevor Sie als angehender Betreuer bei Debian mitmachen.
- Wie es aussieht, ein einfaches Debian-Paket zu erstellen.
- Welche Art von Regeln für das Erstellen des Debian-Pakets existieren.

¹You need to know a little about Unix programming, but you don't need to be an expert. You can learn about basic Debian system handling from the „[Debian Reference](#)“. It also contains pointers for learning about Unix programming.

²If you're not interested in sharing the Debian package, you can address your local needs by compiling and installing the fixed upstream source package into `/usr/local/`.

- Tips for making the Debian package with minimal effort.
- Examples of making Debian packages in typical scenarios.

The author recognized the limitations of updating the original „New Maintainers' Guide“ with the **dh-make** package and decided to create an alternative tool with accompanying documentation to address modern requirements such as multi-arch. This resulted in the **debmake** package, initially released as version 4.0 in 2013. The current **debmake** version is 5.1.2. It comes with this updated „[Guide for Debian Maintainers](#)“ in the **debmake-doc** package (version: 1.26-1). (In 2016, **dh-make** was ported from Perl to Python with updated features.)

Many chores and tips have been integrated into the **debmake** command allowing this guide to be terse. This guide also offers many packaging examples for you to get started.

Achtung



Es bedarf vieler Stunden, um Debian-Pakete zu erstellen und zu betreuen. Der Debian-Betreuer muss **sowohl technisch kompetent als auch sorgfältig** sein, um diese Herausforderung zu meistern.

Some important topics are explained in detail. While some may seem irrelevant to you, please be patient. Certain corner cases are omitted, and some topics are only covered through external references. These are intentional choices to keep this guide simple and maintainable.

Kapitel 2

Überblick

The Debian packaging of the *package-1.0.tar.xz*, containing a simple C source following the „[GNU Coding Standards](#)“ and „[FHS](#)“, can be done with the **debmake** command as follows.

```
[base_dir] $ tar --xz -xvf package-1.0.tar.xz
[base_dir] $ cd package-1.0
[package-1.0] $ debmake
... Make manual adjustments of generated configuration files
[package-1.0] $ debuild
```

Falls die manuellen Anpassungen der erstellten Konfigurationsdateien übersprungen werden, fehlt dem erstellten Binärpaket eine sinnvolle Paketbeschreibung. Es funktioniert aber dennoch unter dem Befehl **dpkg** gut für Ihren lokalen Einsatz.

Achtung



The **debmake** command only provides decent template files. These template files must be manually adjusted to their perfection to comply with the strict quality requirements of the Debian archive, if the generated package is intended for general consumption.

If you are new to Debian packaging, focus on understanding the overall process rather than worrying about the details.

If you are familiar with Debian packaging, you'll notice that **debmake** is similar to the **dh_make** command. This is because **debmake** is designed to replace the functionality historically provided by **dh_make**.¹

Der Befehl **debmake** wurde mit den folgenden Funktionalitäten gestaltet:

- moderner Paketierstil
 - **debian/copyright**: „[DEP-5](#)“-konform
 - **debian/control**: **substvar** support, **multiarch** support, multi binary packages, ...
 - **debian/rules**: **dh** syntax, compiler hardening options, ...
- Flexibilität
 - many options (see „Abschnitt [16.2](#)“, „Kapitel [15](#)“, and „Kapitel [16](#)“)
- vernünftige Standardaktionen
 - Ausführung ohne Unterbrechung mit sauberen Ergebnissen
 - Erstellung des Multiarch-Pakets, außer die Option **-m** wird explizit angegeben
 - generate the non-native Debian package with the Debian source format „**3.0 (quilt)**“, unless the **-n** option is explicitly specified.

¹Before **dh_make**, the **deb-make** command was popular. The current **debmake** package starts its version from **4.0** to avoid version conflicts with the obsolete **debmake** package, which provided the „**deb-make**“ command.

The **debmake** command delegates most of the heavy lifting to its back-end packages: **debhelper**, **dpkg-dev**, **devscripts**, **sbuild**, **schroot**, **licensecheck**, **licenseecon**, etc.

Tipp



Ensure that you properly quote the arguments of the **-b**, **-f**, and **-w** options to protect them from shell interference.

Tipp



Das nicht-native Debian-Paket ist das normale Debian-Paket.

Tipp



Das detaillierte Protokoll aller Paketbaubeispiele in diesem Dokument kann durch Folgen der Anweisungen in „Abschnitt [14.14](#)“ erhalten werden.

Kapitel 3

Voraussetzungen

Here are the prerequisites you need to understand before getting involved with Debian.

3.1 Leute bei Debian

Es nehmen verschiedene Arten von Leuten mit verschiedenen Rollen rund um Debian teil:

- **Originalautor**: die Person, die das ursprüngliche Programm erstellte.
- **Originalbetreuer**: Die Person, die derzeit das Programm betreut.
- **Betreuer**: Die Person, die das Debian-Paket des Programms erstellt.
- **Sponsor**: Eine Person, die den Betreuern beim Hochladen (nach Prüfen des Inhalts) des Pakets in das offizielle Debian-Paketarchiv hilft.
- **Mentor**: Eine Person, die neuen Betreuern beim Paketieren usw. hilft.
- **Debian-Entwickler** (DD): ein Mitglied des Debian-Projekts mit vollen Hochlade-Rechten in das offizielle Debian-Paketarchiv.
- **Debian-Betreuer** (DM): Eine Person, mit begrenzten Hochladerechten in das offizielle Debian-Paketarchiv.

Please note that you can't become an official **Debian Developer** (DD) overnight, as it requires more than just technical skills. Don't be discouraged by this. If your work is useful to others, you can still upload your package either as a **maintainer** through a **sponsor** or as a **Debian Maintainer**.

Please note that you don't need to create new packages to become an official Debian Developer. Contributing to existing packages can also provide a path to becoming an official Debian Developer. There are many packages waiting for good maintainers (see „`Abschnitt 3.8`“).

3.2 Wie Sie beitragen können

Bitte lesen Sie die folgenden Dokumenten, um zu verstehen, wie Sie zu Debian beitragen können:

- „[Wie können Sie Debian helfen?](#)“ (offiziell)
- „[The Debian GNU/Linux FAQ, Chapter 13 - Contributing to the Debian Project](#)“ (semi-official)
- „[Debian Wiki, HelpDebian](#)“ (ergänzend)
- „[Debian New Member site](#)“ (offiziell)
- „[Debian Mentors FAQ](#)“ (ergänzend)

3.3 Soziale Dynamik von Debian

Bitte verstehen Sie die soziale Dynamik, um sich für die Wechselwirkungen mit Debian vorzubereiten:

- We are all volunteers.
 - You can't impose tasks on others.
 - You should be self-motivated to do things.
- Freundliche Zusammenarbeit ist der Motor.
 - Ihr Beitrag sollte Andere nicht überlasten.
 - Ihr Beitrag hat nur Wert, wenn ihn andere wertschätzen.
- Debian is not a school where you get automatic attention from teachers.
 - You should be able to learn many things independently.
 - Attention from other volunteers is a scarce resource.
- Debian verbessert sich ständig.
 - Es wird erwartet, dass Sie hochqualitative Pakete erstellen.
 - Sie sollten sich Änderungen anpassen.

Da in der restlichen Anleitung nur auf die technischen Aspekte der Paketierung fokussiert wird, wird auf folgendes zum Verständnis der sozialen Dynamik von Debian verwiesen:

- „[Debian: 17 years of Free Software, "do-ocracy", and democracy](#)“ (Introductory slides by the ex-DPL)

3.4 Technische Erinnerungen

Here are some technical reminders to help other maintainers work on your package easily and effectively, maximizing the output of Debian as a whole.

- Ermöglichen Sie in Ihrem Paket eine leichte Fehlersuche.
 - Halten Sie Ihr Paket einfach.
 - Machen Sie Ihr Paket nicht zu komplex.
- Halten Sie Ihr Paket gut dokumentiert.
 - Verwenden Sie einen lesbaren Code-Stil.
 - Fügen Sie in den Code Kommentare ein.
 - Formatieren Sie Code konsistent.
 - Verwalten Sie das Git-Depot [1](#) des Pakets.

Anmerkung



Die Fehlersuche in Software kann mehr Zeit verbrauchen, als die eigentliche Erstellung.

It is unwise to run your base system under the **unstable** suite, even for development purposes.

- Creation and verification of binary **deb** packages should use a minimal **unstable** chroot as described in „Abschnitt [4.6](#)“.

¹Die überwältigende Mehrheit der Debian-Betreuer verwenden **git** statt anderer VCS-Systeme wie **hg**, **bzr**, usw.

- Basic interactive package development activities should use an **unstable** chroot as described in „Abschnitt 4.7“.

Anmerkung



Advanced package development activities, such as testing full Desktop systems, network daemons, and system installer packages, should use the **unstable** suite running under „[virtualization](#)“.

3.5 Debian-Dokumentation

Bitte lesen Sie nach Bedarf den einschlägigen Anteil der neusten Debian-Dokumentation, um perfekte Debian-Pakete zu erstellen:

- „Debian Policy Manual“
 - The official „must follow“ rules (<https://www.debian.org/doc/devel-manuals#policy>)
- „Debian Developer’s Reference“
 - The official „best practice“ document (<https://www.debian.org/doc/devel-manuals#devref>)
- „Guide for Debian Maintainers“ — this guide
 - A „tutorial reference“ document (<https://www.debian.org/doc/devel-manuals#debmake-doc>)

All these documents are published on <https://www.debian.org> using the **unstable** suite versions of corresponding Debian packages. If you wish to have local access to all these documents from your base system, please consider using techniques such as „[apt-pinning](#)“ and „[chroot](#)“.

Falls dieser Leitfaden der offiziellen Debian-Dokumentation widerspricht, dann ist die offizielle Debian-Dokumentation korrekt. Bitte reichen Sie mittels des Befehls **reportbug** (auf englisch) einen Fehlerbericht gegen das Paket **debmake-doc** ein.

Hier sind alternative Anleitungen, die Sie zusammen mit diesem Leitfaden lesen können:

- „Debian Packaging Tutorial“
 - <https://www.debian.org/doc/devel-manuals#packaging-tutorial>
 - <https://packages.qa.debian.org/p/packaging-tutorial.html>
- „Ubuntu Packaging Guide“ (Ubuntu is Debian based.)
 - <http://packaging.ubuntu.com/html/>
- „Debian New Maintainers’ Guide“ (predecessor of this tutorial, deprecated)
 - <https://www.debian.org/doc/devel-manuals#maint-guide>
 - <https://packages.qa.debian.org/m/maint-guide.html>

Tipp



When reading these, you may consider using the **debmake** command in place of the **dh_make** command.

3.6 Hilfequellen

Before deciding to ask your question in a public forum, please do your part by reading the relevant documentation:

- Paketierinformationen, die über die Befehle **aptitude**, **apt-cache** und **dpkg** verfügbar sind.
- Dateien in **/usr/share/doc/Paket** für alle einschlägigen Pakete.
- Inhalte von **man Befehl** für alle einschlägigen Befehle.
- Inhalte von **info Befehl** für alle einschlägigen Befehle.
- Inhalte von „debian-mentors@lists.debian.org-Mailinglist-Archiv“.
- Inhalte von „debian-devel@lists.debian.org-Mailinglist-Archiv“.

You can find your desired information effectively by using a well-formed search string such as "keyword site:lists.debian.org" to limit the search domain of the web search engine.

Creating a small test package is a good way to learn the details of packaging. Inspecting existing well-maintained packages is the best way to learn how other people make packages.

Falls Sie immer noch Fragen über das Paketieren haben, können Sie die Fragen direkt stellen (auf Englisch):

- debian-mentors@lists.debian.org mailing list. (This mailing list is for the novice.)
- debian-devel@lists.debian.org mailing list. (This mailing list is for the expert.)
- IRC such as #debian-mentors.
- Teams focusing on a specific set of packages. (Full list at <https://wiki.debian.org/Teams>)
- Sprachspezifische Mailinglisten
 - „debian-devel-{french,italian,portuguese,spanish}@lists.debian.org“
 - „debian-chinese-gb@lists.debian.org“ (Diese Mailingliste ist für allgemeine Diskussion auf (vereinfachtem) Chinesisch.)
 - „debian-devel@debian.or.jp“

More experienced Debian developers will gladly help you if you ask properly after making the required efforts.

Achtung



Debian development is a moving target. Some information found on the web may be outdated, incorrect, or non-applicable. Please use such information carefully.

3.7 Archivsituation

Bitte begreifen Sie die Situation des Debian-Archivs.

- Debian hat bereits Pakete für die meisten Programmarten.
- Die Anzahl an Paketen im Debian-Archiv ist mehrere zehnmal so groß wie die Anzahl der aktiven Betreuer.
- Bei einigen Paketen fehlt leider die entsprechende Aufmerksamkeit des Betreuers.

Daher werden Beiträge zu Paketen, die sich bereits im Archiv befinden, von anderen Betreuern weit-
aus mehr geschätzt (und erhalten eher Sponsoring für das Hochladen).

Tipp



The **wnpp-alert** command from the **devscripts** package can check for installed packages that are up for adoption or orphaned.

Tipp



The **how-can-i-help** package can show opportunities for contributing to Debian based on packages installed locally.

3.8 Wege, beizutragen

Hier ist Pseudo-Python-Code für Ihre Wege, zu Debian mit einem **Programm** beizutragen:

```
if exist_in_debian(program):
    if is_team_maintained(program):
        join_team(program)
    if is_orphaned(program): # maintainer: Debian QA Group
        adopt_it(program)
    elif is_RFA(program): # Request for Adoption
        adopt_it(program)
    else:
        if need_help(program):
            contact_maintainer(program)
            triaging_bugs(program)
            preparing_QA_or_NMU_uploads(program)
        else:
            leave_it(program)
else: # new packages
    if not is_good_program(program):
        give_up_packaging(program)
    elif not is_distributable(program):
        give_up_packaging(program)
    else: # worth packaging
        if is_ITPed_by_others(program):
            if need_help(program):
                contact_ITPer_for_collaboration(program)
            else:
                leave_it_to_ITPer(program)
        else: # really new
            if is_applicable_team(program):
                join_team(program)
            if is_DFSG(program) and is_DFSG(dependency(program)):
                file_ITP(program, area="main") # This is Debian
            elif is_DFSG(program):
                file_ITP(program, area="contrib") # This is not Debian
            else: # non-DFSG
                file_ITP(program, area="non-free") # This is not Debian
            package_it_and_close_ITP(program)
```

Hier:

- Für das Prüfen von `exist_in_debian()` und `is_team_maintained()`:

- der Befehl **aptitude**
- „[Debian-Pakete](#)“-Webseite
- Debian wiki „[Teams](#)“ page
- Für das Prüfen von `is_orphaned()`, `is_RFA()` und `is_ITPed_by_others()`:
 - Die Ausgabe des Befehls **wnpp-alert**.
 - „[Arbeit-bedürfende und voraussichtliche Pakete](#)“
 - „[Debian-Fehlerberichtsprotokolle: Fehler im Pseudo-Paket wnpp in Unstable](#)“
 - „[Debian-Pakete, die liebgewonnen werden müssen](#)“
 - „[Durchsuchen Sie wnpp Fehlerberichte basierend auf Debtags](#)“
- Für das Prüfen von `is_good_program()`:
 - Das Programm sollte nützlich sein.
 - Das Programm sollte keine Sicherheits- und Wartungsbedenken in das Debian-System einbringen.
 - Das Programm sollte gut dokumentiert sein und sein Code muss verständlich (d.h. nicht verschleiert) sein.
 - Die Autoren des Programms stimmen mit der Paketierung überein und sind mit Debian einvernehmlich. [2](#)
- Für die Prüfung von `is_it_DFSG()` und `is_its_dependency_DFSG()`:
 - „[Debian Richtlinien für Freie Software](#)“ (DFSG).
- Für die Prüfung von `is_it_distributable()`:
 - Die Software muss eine Lizenz haben und sie sollte ihre Verbreitung erlauben.

You either need to file an **ITP** or adopt a package to start working on it. See the „Debian Developer’s Reference“:

- „[5.1. Neue Pakete](#)“.
- „[5.9. Verschieben, Entfernen, Verwaisen, Adoptieren und Wiedereinführen von Paketen](#)“.

3.9 Neue Beitragende und Betreuer

Die neuen Beitragenden und Betreuer könnten sich fragen, was sie lernen sollten, um zu Debian beizutragen. Hier sind meine Vorschläge, abhängig von Ihrem Schwerpunkt:

- Paketierung
 - Grundlagen der **POSIX-Shell** und **Make**.
 - Etwas rudimentäres Wissen von **Perl** und **Python**.
- Übersetzungen
 - Grundlagen, wie das PO-basierte Übersetzungssystem funktioniert.
- Dokumentation
 - Basics of text markups (XML, ReST, Wiki, ...).

Der neue Beitragende und Betreuer könnte sich fragen, wo er mit Beiträgen zu Debian beginnen sollte. Hier sind meine Vorschläge, abhängig von Ihren Fertigkeiten:

²Das ist nicht die absolute Voraussetzung. Die ablehnende Einstellung der Originalautoren kann für uns alle zu einem großen Ressourcenproblem werden. Die freundlichen Originalautoren können konsultiert werden, um alle Probleme mit dem Programm zu lösen.

- **POSIX-Shell-, Perl- und Python-Fertigkeiten:**
 - Schicken Sie Patches zum Debian-Installer.
 - Schicken Sie Patches an Paketierhelferskripte von Debian wie **Devscripts**, **Sbuild**, **Schroot** usw., die in diesem Dokument erwähnt sind.
- **C- und C++-Fähigkeiten:**
 - Schicken Sie Patches an Pakete mit den Prioritäten **required** und **important**.
- Sprachfähigkeiten jenseits von Englisch:
 - Schicken Sie Patches zu den PO-Dateien des Debian-Installers.
 - Schicken Sie Patches an den PO-Dateien der Pakete mit den Prioritäten **required** und **important**.
- Dokumentations-Fähigkeiten
 - Aktualisieren Sie Inhalte auf „[Debian-Wiki](#)“.
 - Schicken Sie Patches an das existierende „[Debian-Dokumentation](#)“.

Diese Aktivitäten sollten Ihnen einen guten Kontakt zu den anderen Debian-Menschen verschaffen, um Ihre Glaubwürdigkeit zu begründen.

Der unerfahrene Betreuer sollte das Paketieren von Programmen mit einer hohen Sicherheitsexposition vermeiden:

- **Setuid-** oder **Setgid-**Programme
- **Daemon-**Programme
- Programme, die in den Verzeichnissen **/sbin/** oder **/usr/sbin/** installiert werden

Wenn Sie mehr Erfahrung beim Paketieren gesammelt haben, werden Sie in der Lage sein, solche Programme zu paketieren.

Kapitel 4

Werkzeugeinrichtung

Das Paket **build-essential** muss in Ihrer Bauumgebung installiert sein.

The **devscripts** package should be installed in the development environment of the maintainer.

It is a good idea to install and set up all of the popular set of packages mentioned in this chapter. These enable us to share the common baseline working environment, although these are not necessarily absolute requirements.

Please also consider to install the tools mentioned in the „[Overview of Debian Maintainer Tools](#)“ in the „Debian Developer's Reference“, as needed.

Achtung



Die hier vorgestellte Einrichtung der Werkzeuge ist nur als Beispiel gedacht und kann nicht mit den neuesten im System installierten Paketen übereinstimmen. Debian-Entwicklung ist ein voranschreitendes Ziel. Lesen Sie die relevante Dokumentation und aktualisieren Sie Ihre Konfiguration wo notwendig.

4.1 Email setup

Verschiedene Debian-Betreuungswerkzeuge erkennen Ihre zu verwendene E-Mail-Adresse und Ihren Namen über die Shell-Umgebungsvariablen **\$DEBEMAIL** und **\$DEBFULLNAME**.

Let's set these environment variables by adding the following lines to **~/.bashrc** [1](#).

Fügen Sie zur **~/.bashrc folgendes hinzu**

```
DEBEMAIL="osamu@debian.org"
DEBFULLNAME="Osamu Aoki"
export DEBEMAIL DEBFULLNAME
```

Anmerkung



The above is for the author of this manual. The configuration and operation examples presented in this manual use these email address and name settings. You must use your email address and name for your system.

¹Hierbei wird angenommen, dass Sie die Bash als Ihre Anmelde-Shell verwenden. Falls Sie eine andere Anmelde-Shell, wie die Z-Shell, verwenden, verwenden Sie deren entsprechenden Konfigurationsdateien statt **~/.bashrc**.

4.2 mc setup

Der Befehl **mc** bietet Ihnen einen sehr leichten Zugang zur Verwaltung von Dateien. Es kann binäre **deb**-Dateien zum Prüfen ihrer Inhalte öffnen, indem die Eingabetaste über der binären **deb**-Datei gedrückt wird. Es verwendet den Befehl **dpkg-deb** als seinen Backend. Lassen Sie es uns wie folgt einrichten, um leichtes **chdir** zu ermöglichen.

Fügen Sie zur `~/.bashrc` folgendes hinzu

```
# mc related
if [ -f /usr/lib/mc/mc.sh ]; then
    . /usr/lib/mc/mc.sh
fi
```

4.3 git setup

Heutzutage ist der Befehl **git** ein unverzichtbares Werkzeug, um den Quellbau mit Verlauf zu verwalten.

Die globale Benutzerkonfiguration für den Befehl **git**, wie Ihren Namen und Ihre E-Mail-Adresse, können in **~/.gitconfig** wie folgt gesetzt werden:

```
[~] $ git config --global user.name "Osamu Aoki"
[~] $ git config --global user.email osamu@debian.org
```

Falls Sie an die CVS- oder Subversion-Befehle gewöhnt sind, möchten Sie vielleicht eine Reihe von Aliassen wie folgt setzen:

```
[~] $ git config --global alias.ci "commit -a"
[~] $ git config --global alias.co checkout
```

Sie können Ihre globale Konfiguration wie folgt prüfen:

```
[~] $ git config --global --list
```

Tipp



Es ist essentiell, einige GUI git-Werkzeuge wie **gitk** oder **gitg** zu verwenden, um effektiv mit der Chronik des git-Depots zu arbeiten.

4.4 quilt setup

Der Befehl **quilt** bietet eine grundlegende Methode zur Aufzeichnung von Änderungen. Für die Debian-Paketierung sollte es so angepasst werden, dass Änderungen im **debian/patches**-Verzeichnis anstelle des voreingestellten **patches**-Verzeichnisses aufgezeichnet werden.

Um zu vermeiden, dass das Verhalten des Befehls **quilt** selbst geändert wird, erstellen wir einen Alias **dquilt** für das Debian-Paket, indem wir die folgenden Zeilen in die Datei **~/.bashrc** einfügen. Die zweite Zeile bietet die gleiche Shell-Vervollständigungs-Funktion des **quilt**-Befehls für den **dquilt**-Befehl.

Fügen Sie zur `~/.bashrc` folgendes hinzu

```
alias dquilt="quilt --quiltrc=${HOME}/.quiltrc-dpkg"
. /usr/share/bash-completion/completions/quilt
complete -F _quilt_completion $ _quilt_complete_opt dquilt
```

Dann erstellen wir **~/.quiltrc-dpkg** wie folgt.

```
d=.
while [ ! -d $d/debian -a `readlink -e $d` != / ];
do d=$d/..; done
```

```
if [ -d $d/debian ] && [ -z $QUILT_PATCHES ]; then
    # if in Debian packaging tree with unset $QUILT_PATCHES
    QUILT_PATCHES="debian/patches"
    QUILT_PATCH_OPTS="--reject-format=unified"
    QUILT_DIFF_ARGS="-p ab --no-timestamps --no-index --color=auto"
    QUILT_REFRESH_ARGS="-p ab --no-timestamps --no-index"
    QUILT_COLORS="diff_hdr=1;32:diff_add=1;34:diff_rem=1;31:diff_hunk=1;33:"
    QUILT_COLORS="{QUILT_COLORS}diff_ctx=35:diff_cctx=33"
    if ! [ -d $d/debian/patches ]; then mkdir $d/debian/patches; fi
fi
```

See **quilt(1)** and „[How To Survive With Many Patches or Introduction to Quilt \(quilt.html\)](#)“ on how to use the **quilt** command.

Siehe „Abschnitt 5.9“ für beispielhafte Verwendungen.

Note that „**gbp pq**“ is able to consume existing **debian/patches**, automate updating and modifying the patches, and export them back into **debian/patches**, all without using quilt nor the need to learn or configure quilt.

4.5 devscripts setup

Der Befehl **debsign**, der im Paket **devscripts** enthalten ist, wird verwendet, um das Debian-Paket mit Ihrem privaten GPG-Schlüssel zu signieren.

Der Befehl **debbuild**, der im Paket **devscripts** enthalten ist, baut das Binärpaket und überprüft es mit dem Befehl **lintian**. Es ist praktisch, ausführliche Ausgaben von dem Befehl **lintian** zu haben.

Sie können diese in **~/devscripts** wie folgt einrichten.

```
DEBUILD_DPKG_BUILDPACKAGE_OPTS="-i -I -us -uc"
DEBUILD_LINTIAN_OPTS="-i -I --show-overrides"
DEBSIGN_KEYID="Your_GPG_keyID"
```

The **-i** and **-I** options in **DEBUILD_DPKG_BUILDPACKAGE_OPTS** for the **dpkg-source** command help rebuilding of Debian packages without extraneous contents (see „Kapitel 8“).

Derzeit ist ein RSA-Schlüssel mit 4096 Bits eine gute Idee. Siehe „[Einen neuen GPG-Key erstellen](#)“.

4.6 sbuild setup

The **sbuild** package provides a clean room („**chroot**“) build environment. It offers this efficiently with the help of **schroot** using the bind-mount feature of the modern Linux kernel.

Since it is the same build environment as the Debian's **buildd** infrastructure, it is always up to date and comes full of useful features.

It can be customized to offer following features:

- Das **Schroot**-Paket, um die Geschwindigkeit der Chroot-Erstellung zu erhöhen.
- Das **lintian**-Paket, um Fehler im Paket zu finden.
- Das **Piuparts**-Paket, um Fehler im Paket zu finden.
- Das **Autopkgtest**-Paket, um Fehler im Paket zu finden.
- Das **ccache**-Paket, um die **gcc**-Geschwindigkeit zu erhöhen. (optional)
- Das **libeatmydata1**-Paket zur Erhöhung der **dpkg**-Geschwindigkeit. (optional)
- Die parallele **make**, um die Baugeschwindigkeit zu erhöhen. (optional)

Let's set up **sbuild** environment 2:

```
[~] $ sudo apt install sbuild piuparts autopkgtest lintian
[~] $ sudo apt install sbuild-debian-developer-setup
[~] $ sudo sbuild-debian-developer-setup -s unstable
```

²Be careful since some older HOWTOs may use different chroot setups.

Let's update your group membership to include **sbuid** and verify it:

```
[~] $ newgrp -
[~] $ id
uid=1000(<yourname>) gid=1000(<yourname>) groups=...,132(sbuid)
```

Here, „reboot of system“ or „**kill -TERM -1**“ can be used instead to update your group membership ³

Let's create the configuration file `~/local/sbuid/config.pl` in line with recent Debian practice of „**source-only-upload**“ as:

```
[~] $ cat >~/local/sbuid/config.pl << 'EOF'
#####
# PACKAGE BUILD RELATED (source-only-upload as default)
#####
# -d
$distribution = 'unstable';
# -A
$build_arch_all = 1;
# -s
$build_source = 1;
# --source-only-changes
$source_only_changes = 1;
# -v
$verbose = 1;

#####
# POST-BUILD RELATED (turn off functionality by setting variables to 0)
#####
$run_lintian = 1;
$lintian_opts = ['-i', '-I'];
$run_piuparts = 1;
$piuparts_opts = ['--schroot', 'unstable-amd64-sbuid'];
$run_autopkgtest = 1;
$autopkgtest_root_args = '';
$autopkgtest_opts = [ '--', 'schroot', '%r-%a-sbuid' ];

#####
# PERL MAGIC
#####
1;
EOF
```

Anmerkung



There are some exceptional cases such as NEW uploads, uploads with NEW binary packages, and security uploads where you can't do **source-only-upload** but are required to upload with binary packages. The above configuration needs to be adjusted for those exceptional cases.

Following document assumes that **sbuid** is configured this way.

Edit this to your needs. Post-build tests can be turned on and off by assigning 1 or 0 to the corresponding variables,

³Simply „logout and login under some modern GUI Desktop environment“ may not update your group membership.

Warnung

Die optionale Anpassung kann negative Auswirkungen haben. Im Zweifelsfall deaktivieren Sie sie.

Anmerkung

The parallel **make** may fail for some existing packages and may make the build log difficult to read.

Tipp

Many **sbuild** related hints are available at „Abschnitt 9.7“ and „<https://wiki.debian.org/sbuild>“.

4.7 Persistent chroot setup

Anmerkung

Use of independent copied chroot filesystem prevents contaminating the source chroot used by **sbuild**.

For building new experimental packages or for debugging buggy packages, let's setup dedicated persistent chroot „**source:unstable-amd64-desktop**“ by:

```
[~] $ sudo cp -a /srv/chroot/unstable-amd64-sbuild /srv/chroot/unstable-amd64- ↵
      desktop
[~] $ sudo tee /etc/schroot/chroot.d/unstable-amd64-desktop-XXXXXX << EOF
[unstable-amd64-desktop]
description=Debian sid/amd64 persistent chroot
groups=root,sbuild
root-groups=root,sbuild
profile=desktop
type=directory
directory=/srv/chroot/unstable-amd64-desktop
union-type=overlay
EOF
```

Here, **desktop** profile is used instead of **sbuild** profile. Please make sure to adjust **/etc/schroot/desktop/fstab** to make package source accessible from inside of the chroot.

You can log into this chroot „**source:unstable-amd64-desktop**“ by:

```
[~] $ sudo schroot -c source:unstable-amd64-desktop
```


4.8 gbp setup

The **git-buildpackage** package offers the **gbp(1)** command. Its user configuration file is **~/.gbp.conf**.

```
# Configuration file for "gbp <command>"

[DEFAULT]
# the default build command:
builder = sbuild
# use pristine-tar:
pristine-tar = True
# Use color when on a terminal, alternatives: on/true, off/false or auto
color = auto
```

4.9 HTTP-Proxy

You should set up a local HTTP caching proxy to save the bandwidth for the Debian package repository access. There are several choices:

- Specialized HTTP caching proxy using the **apt-cacher-ng** package.
- Generic HTTP caching proxy (**squid** package) configured by **squid-deb-proxy** package

In order to use this HTTP proxy without manual configuration adjustment, it's a good idea to install either **auto-apt-proxy** or **squid-deb-proxy-client** package to everywhere.

4.10 Privates Debian-Depot

Sie können ein privates Debian-Depot mit dem Paket **reprepro** einrichten.

4.11 Virtuelle Maschinen

For testing GUI application, it is a good idea to have virtual machines. Install **virt-manager** and **qemu-kvm** packages.

Use of chroot and virtual machines allows us not to update the whole host PC to the latest **unstable** suite.

4.12 Local network with virtual machines

In order to access virtual machines easily over the local network, setting up multicast DNS service discovery infrastructure by installing **avahi-utils** is a good idea.

For all running virtual machines and the host PC, we can use each host name appended with **.local** for SSH to access each other.

Kapitel 5

Simple packaging

There is an old Latin saying: „**Longum iter est per praecepta, breve et efficax per exempla**“ („It's a long way by the rules, but short and efficient with examples“).

5.1 Packaging tarball

Hier ist ein Beispiel zur Erstellung eines einfachen Debian-Pakets aus einer einfachen C-Quelle mittels einer **Makefile** als Bausystem.

Let's assume this upstream tarball to be **debhello-0.0.tar.xz**.

Diese Art der Quellen soll als Nichtsystemdatei wie folgt installiert werden:

Basics for the install from the upstream tarball

```
[base_dir] $ tar --xz -xmf debhello-0.0.tar.xz
[base_dir] $ cd debhello-0.0
[debhello-0.0] $ make
[debhello-0.0] $ make install
```

Debian packaging requires changing this „**make install**“ process to install files to the target system image location instead of the normal location under **/usr/local**.

Anmerkung



Beispiele zur Erstellung von Debian-Paketen aus anderen, komplizierteren Bausystemen werden in „Kapitel 14“ beschrieben.

5.2 Gesamtbild

The big picture for building a single non-native Debian package from the upstream tarball **debhello-0.0.tar.xz** can be summarized as:

- The maintainer obtains the upstream tarball **debhello-0.0.tar.xz** and untars its contents to the **debhello-0.0** directory.
- The **debmake** command debianizes the upstream source tree by adding template files only in the **debian** directory.
 - The **debhello_0.0.orig.tar.xz** symlink is created pointing to the **debhello-0.0.tar.xz** file.
 - The maintainer customizes template files.
- The **debbuild** command builds the binary package from the debianized source tree.
 - **debhello-0.0-1.debian.tar.xz** is created containing the **debian** directory.

Big picture of package building

```
[base_dir] $ tar --xz -xmf debhello-0.0.tar.xz
[base_dir] $ cd debhello-0.0
[debhello-0.0] $ debmake
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
...
[debhello-0.0] $ ... manual customization of debian/* files
[debhello-0.0] $ debuild
...
```

Tipp



The **debuild** command in this and following examples may be substituted by equivalent commands such as the **sbuid** command.

Tipp



If the upstream tarball in the **.tar.xz** format is available, use it instead of the one in the **.tar.xz** and **.tar.bz2** formats. The **xz** compression format offers the better compression than the **gzip** and **bzip2** compressions.

5.3 Was ist Debmake?

Anmerkung



Actual packaging activities are often performed manually without using **debmake** while referencing only existing similar packages and „[Debian Policy Manual](#)“.

The **debmake** command is the helper script for the Debian packaging. („Kapitel 15“)

- It creates good template files for the Debian packages.
- It always sets most of the obvious option states and values to reasonable defaults.
- Es erstellt den Tarball der Originalautoren und die benötigten Symlinks, falls sie fehlen.
- Es setzt die bestehenden Konfigurationsdateien im Verzeichnis **debian/** nicht außer Kraft.
- Es unterstützt die **Multiarch**-Pakete.
- It provides short extracted license texts as **debian/copyright** using **licensecheck** to help license review.

Diese Funktionalitäten ermöglichen ein einfaches und moderens Paketieren für Debian mit **debmake**. In retrospective, I created **debmake** to simplify this documentation. I consider **debmake** to be more-or-less a demonstration session generator for tutorial purpose.

The **debmake** command isn't the only helper script to make a Debian package. If you are interested alternative packaging helper tools, please see:

- Debian wiki: „[AutomaticPackagingTools](#)“ — Extensive comparison of packaging helper scripts
- Debian wiki: „[CopyrightReviewTools](#)“ — Extensive comparison of copyright review helper scripts

5.4 Was ist Debuild?

Hier ist eine Zusammenfassung von Befehlen, die dem Befehl **debuild** ähnlich sind.

- Die Datei **debian/rules** definiert, wie das binäre Debian-Paket gebaut wird.
- Der Befehl **dpkg-buildpackage** ist der offizielle Befehl, ein Debian-Binärpaket zu bauen. Bei einem normalen Binärbau führt er grob die folgenden Schritte aus:
 - „**dpkg-source --before-build**“ (apply Debian patches, unless they are already applied)
 - „**fakeroot debian/rules clean**“
 - „**dpkg-source --build**“ (build the Debian source package)
 - „**fakeroot debian/rules build**“
 - „**fakeroot debian/rules binary**“
 - „**dpkg-genbuildinfo**“ (generate a ***.buildinfo** file)
 - „**dpkg-genchanges**“ (generate a ***.changes** file)
 - „**fakeroot debian/rules clean**“
 - „**dpkg-source --after-build**“ (unapply Debian patches, if they are applied during **--before-build**)
 - „**debsign**“ (sign the ***.dsc** and ***.changes** files)
 - ✱ If you followed „Abschnitt 4.5“ to set the **-us** and **-uc** options, this step is skipped and you must run the **debsign** command manually.
- The **debuild** command is a wrapper script of the **dpkg-buildpackage** command to build the Debian binary package under the proper environment variables.
- The **sbuild** command is a wrapper script to build the Debian binary package under the proper chroot environment with the proper environment variables.

Anmerkung



Siehe **dpkg-buildpackage(1)** für die Details.

5.5 Schritt 1: Holen der Quellen der Originalautoren

Let's get the upstream source.

Download debhello-0.0.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-0.0.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-0.0.tar.xz
[base_dir] $ tree
.
+-- debhello-0.0
|   +-- Makefile
|   +-- README.md
|   +-- src
|       +-- hello.c
+-- debhello-0.0.tar.xz

3 directories, 4 files
```

Here, the C source **hello.c** is a very simple one.

hello.c

```
[base_dir] $ cat debhello-0.0/src/hello.c
#include <stdio.h>
int
main()
{
    printf("Hello, world!\n");
    return 0;
}
```

Here, the **Makefile** supports „[GNU Coding Standards](#)“ and „[FHS](#)“. Notably:

- build binaries honoring **\$(CPPFLAGS)**, **\$(CFLAGS)**, **\$(LDFLAGS)**, etc.
- install files with **\$(DESTDIR)** defined to the target system image
- install files with **\$(prefix)** defined, which can be overridden to be **/usr**

Makefile

```
[base_dir] $ cat debhello-0.0/Makefile
prefix = /usr/local

all: src/hello

src/hello: src/hello.c
    @echo "CFLAGS=$(CFLAGS)" | \
        fold -s -w 70 | \
        sed -e 's/^/# /'
    $(CC) $(CPPFLAGS) $(CFLAGS) $(LDCFLAGS) -o $@ $^

install: src/hello
    install -D src/hello \
        $(DESTDIR)$(prefix)/bin/hello

clean:
    -rm -f src/hello

distclean: clean

uninstall:
    -rm -f $(DESTDIR)$(prefix)/bin/hello

.PHONY: all install clean distclean uninstall
```

Anmerkung



The **echo** of the **\$(CFLAGS)** variable is used to verify the proper setting of the build flag in the following example.

5.6 Step 2: Generate template files with debmake

Die Ausgabe des Befehls **debmake** ist sehr ausführlich und erklärt seine Tätigkeiten wie folgt:

The output from the debmake command with -x1 option

```
[base_dir] $ cd debhello-0.0
[debhello-0.0] $ debmake -x1
```

```

I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-0.0] $ cd ..
I: Non-native Debian package pkg="debhello", ver="0.0", rev="1" method="dir_d...
I: already in the package-version form: "debhello-0.0"
I: [base_dir] $ ln -sf debhello-0.0.tar.xz debhello_0.0.orig.tar.xz
I: [base_dir] $ cd debhello-0.0
I: parsing option -b ""
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: build_type = make
I: ext_type = c                      1 files
I: ext_type = md                     1 files
I: creating debian/* files with "-x 1" option
I: [debhello-0.0] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
I: creating debian/rules from extra0_rules
I: creating debian/source/format from extra0source_format
I: creating debian/README.Debian from extra1_README.Debian
I: creating debian/README.source from extra1_README.source
I: creating debian/clean from extra1_clean
I: creating debian/dirs from extra1_dirs
I: creating debian/docs from extra1_docs
I: creating debian/examples from extra1_examples
I: creating debian/gbp.conf from extra1_gbp.conf
I: creating debian/links from extra1_links
I: creating debian/manpages from extra1_manpages
I: creating debian/salsa-ci.yml from extra1_salsa-ci.yml
I: creating debian/watch from extra1nn_watch
I: creating debian/tests/control from extra1tests_control
I: creating debian/upstream/metadata from extra1upstream_metadata
I: creating debian/patches/series from extra1patches_series
I: creating debian/install from extra1bin_install
I: [debhello-0.0] $ wrap-and-sort -ast
I: debian/* may have a blank line at the top.

```

The **debmake** command generates all these template files based on command line options. Since no options are specified, the **debmake** command chooses reasonable default values for you:

- Der Quellpaketname: **debhello**
- Die Version der Originalautoren: **0.0**
- Deb Binärpaketname: **debhello**
- Die Debian-Revision: **1**
- The package type: **bin** (the ELF binary executable package)
- The **-x** option: **-x1** (without maintainer script supports for simplicity)

Anmerkung



Here, the **debmake** command is invoked with the **-x1** option to keep this tutorial simple. Use of default **-x2** or more extensive **-x3** option is highly recommended.

Lassen Sie uns die erstellten Vorlagendateien anschauen.

Der Quellbaum, nach der grundlegenden Ausführung von debmake.

```

[debhello-0.0] $ cd ..
[base_dir] $ tree
.
+-- debhhello-0.0
|   +-- Makefile
|   +-- README.md
|   +-- debian
|       +-- README.Debian
|       +-- README.source
|       +-- changelog
|       +-- clean
|       +-- control
|       +-- copyright
|       +-- dirs
|       +-- docs
|       +-- examples
|       +-- gbp.conf
|       +-- install
|       +-- links
|       +-- manpages
|       +-- patches
|       |   +-- series
|       +-- rules
|       +-- salsa-ci.yml
|       +-- source
|       |   +-- format
|       +-- tests
|       |   +-- control
|       +-- upstream
|       |   +-- metadata
|       +-- watch
|   +-- src
|       +-- hello.c
+-- debhhello-0.0.tar.xz
+-- debhhello_0.0.orig.tar.xz -> debhhello-0.0.tar.xz

8 directories, 25 files

```

The **debian/rules** file is the build script provided by the package maintainer. Here is its template file generated by the **debmake** command.

debian/rules (Vorlagendatei):

```

[base_dir] $ cd debhhello-0.0
[debhello-0.0] $ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
# See debhelper(7) (un-comment to enable)
# This is an autogenerated template for debian/rules.
#
# Output every command that modifies files on the build system.
#export DH_VERBOSE = 1
#
# Copy some variable definitions from pkg-info.mk and vendor.mk
# under /usr/share/dpkg/ to here if they are useful.
#
# See FEATURE AREAS/ENVIRONMENT in dpkg-buildflags(1)
# Apply all hardening options
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
# Package maintainers to append CFLAGS
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
# Package maintainers to append LDFLAGS
#export DEB_LDFLAGS_MAINT_APPEND = -Wl,-O1
#
# With debhelper version 9 or newer, the dh command exports

```

```

# all buildflags. So there is no need to include the
# /usr/share/dpkg/buildflags.mk file here if compat is 9 or newer.
#
# These are rarely used code. (START)
#
# The following include for *.mk magically sets miscellaneous
# variables while honoring existing values of pertinent
# environment variables:
#
# Architecture-related variables such as DEB_TARGET_MULTIARCH:
#include /usr/share/dpkg/architecture.mk
# Vendor-related variables such as DEB_VENDOR:
#include /usr/share/dpkg/vendor.mk
# Package-related variables such as DEB_DISTRIBUTION
#include /usr/share/dpkg/pkg-info.mk
#
# You may alternatively set them using a simple script such as:
# DEB_VENDOR ?= $(shell dpkg-vendor --query Vendor)
#
# These are rarely used code. (END)
#

### main packaging script based on post dh7 syntax
%:
    dh $@

# debmake generated override targets
# Use "make prefix=/usr" (override prefix=/usr/local in Makefile)
#override_dh_auto_install:
#    dh_auto_install -- prefix=/usr

# Do not install python .pyc .pyo if they exist
#override_dh_install:
#    dh_install --list-missing -X.pyc -X.pyo

# Multiarch package requires library files to be installed to
# /usr/lib/<triplet>/ . If the build system does not support
# $(DEB_HOST_MULTIARCH), you may need to override some targets such as
# dh_auto_configure or dh_auto_install to use $(DEB_HOST_MULTIARCH) .

```

This is essentially the standard **debian/rules** file with the **dh** command. (There are some commented out contents for you to customize it.)

The **debian/control** file provides the main meta data for the Debian package. Here is its template file generated by the **debmake** command.

debian/control (Vorlagendatei):

```

[debhelloworld-0.0] $ cat debian/control
Source: debhelloworld
Section: unknown
Priority: optional
Maintainer: "Osamu Aoki" <osamu@debian.org>
Build-Depends:
    debhelper-compat (= 13),
Standards-Version: 4.7.3
Homepage: <insert the upstream URL, if relevant>
Rules-Requires-Root: no
#Vcs-Git: https://salsa.debian.org/debian/debhelloworld.git
#Vcs-Browser: https://salsa.debian.org/debian/<project_site>

Package: debhelloworld
Section: unknown
Architecture: any
Multi-Arch: foreign
Depends:

```



```

${misc:Depends},
${shlibs:Depends},
Description: auto-generated package by debmake
This Debian binary package was auto-generated by the
debmake(1) command provided by the debmake package.
.
==== This comes from the unmodified template file ====
.
Please edit this template file (debian/control) and other package files
(debian/*) to make them meet all the requirements of the Debian Policy
before uploading this package to the Debian archive.
.
See
* https://www.debian.org/doc/manuals/developers-reference/best-pkging-pract...
* https://www.debian.org/doc/manuals/debmake-doc/ch05.en.html#control
.
The synopsis description at the top should be about 60 characters and
written as a phrase. No extra capital letters or a final period. No
articles b''-b'' "a", "an", or "the".
.
The package description for general-purpose applications should be
written for a less technical user. This means that we should avoid
jargon. GNOME or KDE is fine but GTK+ is probably not.
.
Use the canonical forms of words:
* Use X Window System, X11, or X; not X Windows, X-Windows, or X Window.
* Use GTK+, not GTK or gtk.
* Use GNOME, not Gnome.
* Use PostScript, not Postscript or postscript.

```

Warnung



If you leave „**Section: unknown**“ in the template **debian/control** file unchanged, the **lintian** error may cause the build to fail.

Since this is the ELF binary executable package, the **debmake** command sets „**Architecture: any**“ and „**Multi-Arch: foreign**“. Also, it sets required **substvar** parameters as „**Depends: \${shlibs:Depends}, \${misc:Depends}**“. These are explained in „Kapitel 6“.

Anmerkung



Please note this **debian/control** file uses the RFC-822 style as documented in „[5.2 Source package control files — debian/control](#)“ of the „Debian Policy Manual“. The use of the empty line and the leading space are significant.

The **debian/copyright** file provides the copyright summary data of the Debian package using the **licensecheck** command.

debian/copyright (Vorlagendatei):

```

[debhelloworld-0.0] $ cat debian/copyright
Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: FIXME
Upstream-Contact: FIXME
Source: FIXME
Disclaimer: Autogenerated by licensecheck

Files: ./Makefile
       ./README.md

```

```
./src/hello.c
Copyright: NONE
License: UNKNOWN
FIXME
```

5.7 Schritt 3: Anpassung der Vorlagendateien

Um ein geeignetes Debian-Paket zu erstellen, sind manuelle Anpassungen durch den Betreuer notwendig.

In order to install files as a part of the system files, the **\$(prefix)** value of **/usr/local** in the **Makefile** should be overridden to be **/usr**. This can be accommodated by the following the **debian/rules** file with the **override_dh_auto_install** target setting „**prefix=/usr**“.

debian/rules (Betreuerversion):

```
[base_dir] $ cd debhello-0.0
[debhello-0.0] $ vim debian/rules
... hack, hack, hack, ...
[debhello-0.0] $ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@

override_dh_auto_install:
    dh_auto_install -- prefix=/usr
```

Exportieren der Umgebungsvariable **DH_VERBOSE** in der Datei **debian/rules** zwingt das Werkzeug **debhelper** dazu, einen feingranularen Baubericht zu erstellen.

Exporting **DEB_BUILD_MAINT_OPTION** as above sets the hardening options as described in the „FEATURE AREAS/ENVIRONMENT“ in **dpkg-buildflags(1)**. [1](#)

Durch Exportieren von **DEB_CFLAGS_MAINT_APPEND** wie oben wird der C-Compiler gezwungen, alle Warnungen auszugeben.

Durch Exportieren von **DEB_LDFLAGS_MAINT_APPEND** wie oben wird der Linker gezwungen, nur zu linken, wenn die Bibliothek tatsächlich benötigt wird. [2](#)

The **dh_auto_install** command for the Makefile based build system essentially runs „**\$(MAKE) install DESTDIR=debian/debhello**“. The creation of this **override_dh_auto_install** target changes its behavior to „**\$(MAKE) install DESTDIR=debian/debhello prefix=/usr**“.

Hier sind die Betreuerversionen der Dateien **debian/control** und **debian/copyright**.

debian/control (Betreuerversion):

```
[debhello-0.0] $ vim debian/control
... hack, hack, hack, ...
[debhello-0.0] $ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends:
    debhelper-compat (= 13),
Standards-Version: 4.7.3
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no
```

¹This is a cliché to force a read-only relocation link for the hardening and to prevent the lintian warning „**W: debhello: hardening-no-relro usr/bin/hello**“. This is not really needed for this example but should be harmless. The lintian tool seems to produce a false positive warning for this case which has no linked library.

²This is a cliché to prevent overlinking for the complex library dependency case such as Gnome programs. This is not really needed for this simple example but should be harmless.

```
Package: debhello
Architecture: any
Multi-Arch: foreign
Depends:
    ${misc:Depends},
    ${shlibs:Depends},
Description: Simple packaging example for debmake
    This Debian binary package is an example package.
    (This is an example only)
```

debian/copyright (Betreuerversion):

```
[debhello-0.0] $ vim debian/copyright
... hack, hack, hack, ...
[debhello-0.0] $ cat debian/copyright
Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: debhello
Upstream-Contact: Osamu Aoki <osamu@debian.org>
Source: https://salsa.debian.org/debian/debmake-doc

Files:      *
Copyright:  2015-2021 Osamu Aoki <osamu@debian.org>
License:     Expat
Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:
.
The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.
.
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
```

Let's remove unused template files and edit remaining template files:

- **debian/README.source**
- **debian/patches/series** (No upstream patch)
- **clean**
- **dirs**
- **install**
- **links**

Vorlagendateien unter debian/. (v=0.0):

```
[debhello-0.0] $ rm -f debian/clean debian/dirs debian/install debian/links
[debhello-0.0] $ rm -f debian/README.source debian/source/*.ex
[debhello-0.0] $ rm -rf debian/patches
[debhello-0.0] $ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
```

```

+-- copyright
+-- docs
+-- examples
+-- gbp.conf
+-- manpages
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 14 files

```

Tipp



Konfigurationsdateien, die vom Befehl **dh_*** aus dem Paket **debhelper** verwandt werden, behandeln normalerweise **#** als Beginn einer Kommentarzeile.

5.8 Step 4: Building package with debuild

You can create a non-native Debian package using the **debuild** command or its equivalents (see „Abschnitt 5.4“) in this source tree. The command output is very verbose and explains what it does as follows.

Building package with debuild

```

[base_dir] $ cd debhello-0.0
[debhello-0.0] $ debuild
dpkg-buildpackage -us -uc -ui -i
dpkg-buildpackage: info: source package debhello
dpkg-buildpackage: info: source version 0.0-1
dpkg-buildpackage: info: source distribution unstable
dpkg-buildpackage: info: source changed by Osamu Aoki <osamu@debian.org>
dpkg-source -i --before-build .
dpkg-buildpackage: info: host architecture amd64
debian/rules clean
dh clean
  dh_auto_clean
    make -j12 distclean
...
debian/rules binary
dh binary
  dh_update_autotools_config
  dh_autoreconf
  dh_auto_configure
  dh_auto_build
    make -j12 INSTALL="install --strip-program=true"
make[1]: Entering directory '/path/to/base_dir/debhello-0.0'
# CFLAGS=-g -O2 -Werror=implicit-function-declaration
...
Finished running lintian.

```

Sie können überprüfen, dass **CFLAGS** korrekt mit **-Wall** und **-pedantic** durch die Variable **DEB_CFLAGS_MAINT** aktualisiert ist.

Wie vom Paket **lintian** berichtet sollte eine Handbuchseite zum Paket hinzugefügt werden, wie dies in späteren Beispielen gezeigt wird (siehe „Kapitel 14“). Lassen Sie uns jetzt weitermachen.

Lassen Sie uns die Ergebnisse anschauen.

Die durch den Befehl `debuild` erstellten Dateien von `debhello` Version 0.0:

```
[debhello-0.0] $ cd ..
[base_dir] $ tree -FL 1
./
+-- debhello-0.0/
+-- debhello-0.0.tar.xz
+-- debhello-dbgsym_0.0-1_amd64.deb
+-- debhello_0.0-1.debian.tar.xz
+-- debhello_0.0-1.dsc
+-- debhello_0.0-1_amd64.build
+-- debhello_0.0-1_amd64.buildinfo
+-- debhello_0.0-1_amd64.changes
+-- debhello_0.0-1_amd64.deb
+-- debhello_0.0.orig.tar.xz -> debhello-0.0.tar.xz

2 directories, 9 files
```

You see all the generated files.

- The **debhello_0.0.orig.tar.xz** is a symlink to the upstream tarball.
- The **debhello_0.0-1.debian.tar.xz** contains the maintainer generated contents.
- The **debhello_0.0-1.dsc** is the meta data file for the Debian source package.
- The **debhello_0.0-1_amd64.deb** is the Debian binary package.
- The **debhello-dbgsym_0.0-1_amd64.deb** is the Debian debug symbol binary package. See „Abschnitt 10.21“.
- The **debhello_0.0-1_amd64.build** file is the build log file.
- The **debhello_0.0-1_amd64.buildinfo** file is the meta data file generated by `dpkg-genbuildinfo(1)`.
- The **debhello_0.0-1_amd64.changes** is the meta data file for the Debian binary package.

The **debhello_0.0-1.debian.tar.xz** contains the Debian changes to the upstream source as follows.

The compressed archive contents of `debhello_0.0-1.debian.tar.xz`:

```
[base_dir] $ tar --xz -tf debhello-0.0.tar.xz
debhello-0.0/
debhello-0.0/src/
debhello-0.0/src/hello.c
debhello-0.0/Makefile
debhello-0.0/README.md
[base_dir] $ tar --xz -tf debhello_0.0-1.debian.tar.xz
debian/
debian/README.Debian
debian/changelog
debian/control
debian/copyright
debian/docs
debian/examples
debian/gbp.conf
debian/manpages
debian/rules
debian/salsa-ci.yml
debian/source/
debian/source/format
debian/tests/
debian/tests/control
debian/upstream/
debian/upstream/metadata
debian/watch
```

The **debhello_0.0-1_amd64.deb** contains the binary files to be installed to the target system.

The **debhello-dbgsym_0.0-1_amd64.deb** contains the debug symbol files to be installed to the target system.

The binary package contents of all binary packages:

```
[base_dir] $ dpkg -c debhello-dbgsym_0.0-1_amd64.deb
drwxr-xr-x root/root ... ./
drwxr-xr-x root/root ... ./usr/
drwxr-xr-x root/root ... ./usr/lib/
drwxr-xr-x root/root ... ./usr/lib/debug/
drwxr-xr-x root/root ... ./usr/lib/debug/.build-id/
drwxr-xr-x root/root ... ./usr/lib/debug/.build-id/00/
-rw-r--r-- root/root ... ./usr/lib/debug/.build-id/00/d21e230186d135c41c9540...
drwxr-xr-x root/root ... ./usr/share/
drwxr-xr-x root/root ... ./usr/share/doc/
lrwxrwxrwx root/root ... ./usr/share/doc/debhello-dbgsym -> debhello
[base_dir] $ dpkg -c debhello_0.0-1_amd64.deb
drwxr-xr-x root/root ... ./
drwxr-xr-x root/root ... ./usr/
drwxr-xr-x root/root ... ./usr/bin/
-rwxr-xr-x root/root ... ./usr/bin/hello
drwxr-xr-x root/root ... ./usr/share/
drwxr-xr-x root/root ... ./usr/share/doc/
drwxr-xr-x root/root ... ./usr/share/doc/debhello/
-rw-r--r-- root/root ... ./usr/share/doc/debhello/README.Debian
-rw-r--r-- root/root ... ./usr/share/doc/debhello/changelog.Debian.gz
-rw-r--r-- root/root ... ./usr/share/doc/debhello/copyright
```

The generated dependency list of all binary packages.

The generated dependency list of all binary packages (v=0.0):

```
[debhello-0.0] $ dpkg -f debhello-dbgsym_0.0-1_amd64.deb pre-depends \
depends recommends conflicts breaks
Depends: debhello (= 0.0-1)
[debhello-0.0] $ dpkg -f debhello_0.0-1_amd64.deb pre-depends \
depends recommends conflicts breaks
Depends: libc6 (>= 2.34)
```

Achtung



Many more details need to be addressed before uploading the package to the Debian archive.

Anmerkung



If manual adjustments of auto-generated configuration files by the **debmake** command are skipped, the generated binary package may lack meaningful package description and some of the policy requirements may be missed. This sloppy package functions well under the **dpkg** command, and may be good enough for your local deployment.

5.9 Step 3 (alternatives): Modification to the upstream source

The above example did not touch the upstream source to make the proper Debian package. An alternative approach as the maintainer is to modify files in the upstream source. For example, **Makefile** may be

modified to set the **\$(prefix)** value to **/usr**.

Anmerkung



The above „Abschnitt 5.7“ using the **debian/rules** file is the better approach for packaging for this example. But let's continue on with this alternative approaches as a leaning experience.

In the following, let's consider 3 simple variants of this alternative approach to generate **debian/patches/*** files representing modifications to the upstream source in the Debian source format „3.0 (quilt)“. These substitute „Abschnitt 5.7“ in the above step-by-step example:

- „Abschnitt 5.10“
- „Abschnitt 5.11“
- „Abschnitt 5.12“

Please note the **debian/rules** file used for these examples doesn't have the **override_dh_auto_install** target as follows:

debian/rules (alternative maintainer version):

```
[base_dir] $ cd debhello-0.0
[debhello-0.0] $ vim debian/rules
... hack, hack, hack, ...
[debhello-0.0] $ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@
```

5.10 Patch by „diff -u“ approach

Here, the patch file **000-prefix-usr.patch** is created using the **diff** command.

Patch by diff -u

```
[base_dir] $ cp -a debhello-0.0 debhello-0.0.orig
[debhello-0.0] $ vim debhello-0.0/Makefile
... hack, hack, hack, ...
[base_dir] $ diff -Nru debhello-0.0.orig debhello-0.0 >000-prefix-usr.patch
[base_dir] $ cat 000-prefix-usr.patch
diff -Nru debhello-0.0.orig/Makefile debhello-0.0/Makefile
--- debhello-0.0.orig/Makefile    2026-02-03 08:55:45.275309668 +0000
+++ debhello-0.0/Makefile        2026-02-03 08:55:45.354384730 +0000
@@ -1,4 +1,4 @@
-prefix = /usr/local
+prefix = /usr

all: src/hello

[base_dir] $ rm -rf debhello-0.0
[base_dir] $ mv -f debhello-0.0.orig debhello-0.0
```

Please note that the upstream source tree is restored to the original state after generating a patch file **000-prefix-usr.patch**.

This **000-prefix-usr.patch** is edited to be **DEP-3** conforming and moved to the right location as below. **000-prefix-usr.patch (DEP-3):**

```
[debhello-0.0] $ echo '000-prefix-usr.patch' >debian/patches/series
[debhello-0.0] $ vim ../000-prefix-usr.patch
... hack, hack, hack, ...
[debhello-0.0] $ mv -f ../000-prefix-usr.patch debian/patches/000-prefix-usr....
[debhello-0.0] $ cat debian/patches/000-prefix-usr.patch
From: Osamu Aoki <osamu@debian.org>
Description: set prefix=/usr patch
diff -Nru debhhello-0.0.orig/Makefile debhhello-0.0/Makefile
--- debhhello-0.0.orig/Makefile
+++ debhhello-0.0/Makefile
@@ -1,4 +1,4 @@
-prefix = /usr/local
+prefix = /usr

all: src/hello
```

Anmerkung



When generating the Debian source package by **dpkg-source** via **dpkg-buildpackage** in the following step of „Abschnitt 5.8“, the **dpkg-source** command assumes that no patch was applied to the upstream source, since the **.pc/applied-patches** is missing.

5.11 Patch by quilt approach

Here, the patch file **000-prefix-usr.patch** is created using the **dquilt** command.

dquilt is a simple wrapper of the **quilt** program. The syntax and function of the **dquilt** command is the same as the **quilt**(1) command, except for the fact that the generated patch is stored in the **debian/patches/** directory.

Patch by quilt

```
[debhello-0.0] $ dquilt new 000-prefix-usr.patch
Patch debian/patches/000-prefix-usr.patch is now on top
[debhello-0.0] $ dquilt add Makefile
File Makefile added to patch debian/patches/000-prefix-usr.patch
... hack, hack, hack, ...
[debhello-0.0] $ head -1 Makefile
prefix = /usr
[debhello-0.0] $ dquilt refresh
Refreshed patch debian/patches/000-prefix-usr.patch
[debhello-0.0] $ dquilt header -e --dep3
... edit the DEP-3 patch header with editor
[debhello-0.0] $ tree -a
.
+-- .pc
|   +-- .quilt_patches
|   +-- .quilt_series
|   +-- .version
|   +-- 000-prefix-usr.patch
|       |   +-- .timestamp
|       |   +-- Makefile
|   +-- applied-patches
+-- Makefile
+-- README.md
+-- debian
|   +-- README.Debian
|   +-- README.source
```



```

|   +-- changelog
|   +-- clean
|   +-- control
|   +-- copyright
|   +-- dirs
|   +-- docs
|   +-- examples
|   +-- gbp.conf
|   +-- install
|   +-- links
|   +-- manpages
|   +-- patches
|       |   +-- 000-prefix-usr.patch
|       |   +-- series
|   +-- rules
|   +-- salsa-ci.yml
|   +-- source
|       |   +-- format
|   +-- tests
|       |   +-- control
|   +-- upstream
|       |   +-- metadata
|   +-- watch
+-- src
    +-- hello.c

9 directories, 30 files
[debhhello-0.0] $ cat debian/patches/series
000-prefix-usr.patch
[debhhello-0.0] $ cat debian/patches/000-prefix-usr.patch
Description: set prefix=/usr patch
Author: Osamu Aoki <osamu@debian.org>
Index: debhhello-0.0/Makefile
=====
--- debhhello-0.0.orig/Makefile
+++ debhhello-0.0/Makefile
@@ -1,4 +1,4 @@
-prefix = /usr/local
+prefix = /usr

all: src/hello

```

Here, **Makefile** in the upstream source tree doesn't need to be restored to the original state for the packaging.

Anmerkung



When generating the Debian source package by **dpkg-source** via **dpkg-buildpackage** in the following step of „Abschnitt 5.8“, the **dpkg-source** command assumes that patches were applied to the upstream source, since the **.pc/applied-patches** exists.

The upstream source tree can be restored to the original state for the packaging.

The upstream source tree (restored):

```

[debhhello-0.0] $ dquilt pop -a
Removing patch debian/patches/000-prefix-usr.patch
Restoring Makefile

No patches applied
[debhhello-0.0] $ head -1 Makefile
prefix = /usr/local

```

```
[debhello-0.0] $ tree -a .pc
.pc
+-- .quilt_patches
+-- .quilt_series
+-- .version

1 directory, 3 files
```

Here, **Makefile** is restored and the **.pc/applied-patches** is missing.

5.12 Patch by „dpkg-source --auto-commit“ approach

Here, the patch file isn't created in this step but the source files are setup to create **debian/patches/*** files in the following step of „Abschnitt 5.8“.

For this, **debmake** must be invoked without **-x1** option to generate normal template files using default **-x2** option, instead.

The output from the debmake command

```
[base_dir] $ cd debhello-0.0
[debhello-0.0] $ debmake
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
...
```

Bearbeiten Sie die Quellen der Originalautoren.

Modified Makefile

```
[debhello-0.0] $ vim Makefile
... hack, hack, hack, ...
[debhello-0.0] $ head -n1 Makefile
prefix = /usr
```

Let's edit **debian/source/options**:

debian/source/options for auto-commit

```
[debhello-0.0] $ mv debian/source/options.ex debian/source/options
[debhello-0.0] $ vim debian/source/options
... hack, hack, hack, ...
[debhello-0.0] $ cat debian/source/options
# == Patch applied strategy (merge) ==
#
# The source outside of debian/ directory is modified by maintainer and
# different from the upstream one:
# * Workflow using dpkg-source commit (commit all to VCS after dpkg-source ...
#   https://www.debian.org/doc/manuals/debmake-doc/ch04.en.html#dpkg-sour...
# * Workflow described in dgit-maint-merge(7)
#
single-debian-patch
auto-commit
```

Let's edit **debian/source/patch-header**:

debian/source/patch-header for auto-commit

```
[debhello-0.0] $ mv debian/source/patch-header.ex debian/source/patch-header
[debhello-0.0] $ vim debian/source/patch-header
... hack, hack, hack, ...
[debhello-0.0] $ cat debian/source/patch-header
Description: debian-changes
Author: Osamu Aoki <osamu@debian.org>
```

Let's remove **debian/patches/*** files and other unused template files.

Remove unused template files

```
[debhello-0.0] $ rm -f debian/clean debian/dirs debian/install debian/links
[debhello-0.0] $ rm -f debian/README.source debian/*.ex debian/source/*.ex
[debhello-0.0] $ rm -rf debian/patches
[debhello-0.0] $ tree debian
debian
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- docs
+-- examples
+-- gbp.conf
+-- manpages
+-- rules
+-- salsa-ci.yml
+-- source
|   +-- format
|   +-- options
|   +-- patch-header
+-- tests
|   +-- control
+-- upstream
|   +-- metadata
+-- watch

4 directories, 16 files
```

There are no **debian/patches/*** files at the end of this step.

Anmerkung



When generating the Debian source package by **dpkg-source** via **dpkg-buildpackage** in the following step of „Abschnitt 5.8“, the **dpkg-source** command uses options specified in **debian/source/options** to auto-commit modification applied to the upstream source as **patches/debian-changes**.

Let's inspect the Debian source package generated after the following „Abschnitt 5.8“ step and extracting files from **debhello-0.0.debian.tar.xz**.

Inspect debhello-0.0.debian.tar.xz after debuild

```
[base_dir] $ tar --xz -xvf debhello_0.0-1.debian.tar.xz
debian/
debian/README.Debian
debian/changelog
debian/control
debian/copyright
debian/docs
debian/examples
debian/gbp.conf
debian/manpages
debian/patches/
debian/patches/debian-changes
debian/patches/series
debian/rules
debian/salsa-ci.yml
debian/source/
debian/source/format
debian/source/options
debian/source/patch-header
debian/tests/
debian/tests/control
debian/upstream/
```

```
debian/upstream/metadata
debian/watch
```

Let's check generated **debian/patches/*** files.

Inspect debian/patches/* after debuild

```
[base_dir] $ cat debian/patches/series
debian-changes
[base_dir] $ cat debian/patches/debian-changes
Description: debian-changes
Author: Osamu Aoki <osamu@debian.org>

--- debhello-0.0.orig/Makefile
+++ debhello-0.0/Makefile
@@ -1,4 +1,4 @@
-prefix = /usr/local
+prefix = /usr

all: src/hello
```

The Debian source package **debhello-0.0.debian.tar.xz** is confirmed to be generated properly with **debian/patches/*** files for the Debian modification.

Kapitel 6

Basics for packaging

Here, a broad overview is presented without using VCS operations for the basic rules of Debian packaging focusing on the non-native Debian package in the „**3.0 (quilt)**“ format.

Anmerkung



Zu Gunsten der Klarheit werden einige Details bewusst übergangen. Bitte lesen Sie die Handbuchseiten von **dpkg-source(1)**, **dpkg-buildpackage(1)**, **dpkg(1)**, **dpkg-deb(1)**, **deb(5)** usw.

Das Debian-Quellpaket ist eine Gruppe von Eingabedateien (d.h. nicht eine einzelne Datei), die zum Bau des Debian-Binärpakets verwandt werden.

Das Debian-Binärpaket ist eine besondere Archivdatei, die die Gruppe der installierbaren Binärdaten mit ihren zugehörigen Informationen enthält.

Ein einzelnes Debian-Quellpaket kann mehrere Debian-Binärpakete, die in der Datei **debian/control** definiert sind, installieren.

The non-native Debian package in the Debian source format „**3.0 (quilt)**“ is the most normal Debian source package format.

Anmerkung



There are many wrapper scripts. Use them to streamline your workflow but make sure to understand the basics of their internals.

6.1 Arbeitsablauf des Paketierens

The Debian packaging workflow to create a Debian binary package involves generating several specifically named files (see „Abschnitt 6.3“) as defined in the „Debian Policy Manual“. This workflow can be summarized in 10 steps with some over simplification as follows.

1. The upstream tarball is downloaded as the *package-version.tar.xz* file.
2. The upstream tarball is untarred to create many files under the *package-version/* directory.
3. The upstream tarball is copied (or symlinked) to the particular filename *packagename_version.orig.tar.xz*.
 - the character separating *package* and *version* is changed from - (hyphen) to _ (underscore)
 - **.orig** is added in the file extension.
4. The Debian package specification files are added to the upstream source under the *package-version/debian/* directory.

- Required specification files under the **debian/** directory:
 - debian/rules** Das ausführbare Skript zum Bau des Debian-Pakets (siehe „Abschnitt 6.5“)
 - debian/control** The package configuration file containing the source package name, the source build dependencies, the binary package name, the binary dependencies, etc. (see „Abschnitt 6.6“)
 - debian/changelog** The Debian package history file defining the upstream package version and the Debian revision in its first line (see „Abschnitt 6.7“)
 - debian/copyright** The copyright and license summary (see „Abschnitt 6.8“)
 - debian/source/format** This indicates the desired format to **dpkg-source**(1) (see Debian wiki: „DebSrc3.0“)
 - Optional specification files under the **debian/*** (see „Abschnitt 6.14“):
 - These files must be manually edited to their perfection according to the „[Debian Policy Manual](#)“ and „[Debian Developer's Reference](#)“.
5. The **dpkg-buildpackage** command (usually from its wrapper **debuild** or **sbuild**) is invoked in the *package-version/* directory to make the Debian source and binary packages by invoking the **debian/rules** script.
- The current directory is set as: „**CURDIR=/path/to/package-version/**“
 - Create the Debian source package in the Debian source format „3.0 (quilt)“ using **dpkg-source**(1)
 - *package_version.orig.tar.xz* (copy or symlink of *package-version.tar.xz*)
 - *package_version-revision.debian.tar.xz* (tarball of **debian/** found in *package-version/*)
 - *package_version-revision.dsc*
 - Build the source using „**debian/rules build**“ into **\$(DESTDIR)**
 - „**DESTDIR=debian/binarypackage/**“ for single binary package 1
 - „**DESTDIR=debian/tmp/**“ for multi binary package
 - Create the Debian binary package using **dpkg-deb**(1), **dpkg-genbuildinfo**(1), and **dpkg-genchanges**(1).
 - *binarypackage_version-revision_arch.deb*
 - ... (There may be multiple Debian binary package files.)
 - *package_version-revision_arch.changes*
 - *package_version-revision_arch.buildinfo*
6. Check the quality of the Debian package with the **lintian** command. (recommended)
- Follow the rejection guidelines from [ftp-master](#).
 - „[REJECT-FAQ](#)“
 - „[NEW-Checkliste](#)“
 - „[Lintian Autorejects](#)“ („[lintian tag list](#)“)
7. Test the goodness of the generated Debian binary package manually by installing it and running its programs.
8. After confirming the goodness, prepare files for the normal source-only upload to the Debian archive.
9. Sign the Debian package file with the **debsign** command using your private GPG key.
- Use „**debsign package_version-revision_source.changes**“ (source-only upload situation)
 - Use „**debsign package_version-revision_arch.changes**“ (source+binary upload situation)
10. Upload the set of the Debian package files with the **dput** command to the Debian archive.
- Use „**dput package_version-revision_source.changes**“ (source-only upload)

¹This is the default up to **debhelper** v13. At **debhelper** v14, it warns the default change. After **debhelper** v15, it will change the default to **DESTDIR=debian/tmp/**.

- Use „**dput package_version-revision_arch.changes**“ (source+binary upload)

Test building and confirming of the binary package goodness as above is the moral obligation as a diligent Debian developer but there is no physical barrier for people to skip such operations at this moment for the source-only upload.

For the upstream tarball, the **debmake** command helps up to the step 4 in the above workflow. For the upstream working tree *package/* checked out, e.g., by „**git clone** <https://github.com/upstreamname/package.git>“ without any upstream tarball, the **debmake** command invoked in it helps up to step 4, too. The **debmake** command does not overwrite any existing configuration files.

Here, please replace each part of the filename as:

- the *package* part with the Debian source package name
- the *binarypackage* part with the Debian binary package name
- the *version* part with the upstream version
- the *revision* part with the Debian revision
- the *arch* part with the package architecture (e.g., **amd64**)

The current Debian practice for uploading the normal Debian package is:

- Use the source-only upload if all generated binary packages exist in the Debian **sid** archive. This is usual case.
- Use the source+binary upload if any one of generated packages is missing in the Debian **sid** archive. (This involves manually handled NEW process by the archive management team.)

See also „[Source-only uploads](#)“.

Tipp



Many patch management and VCS usage strategies for the Debian packaging are practiced. You don't need to use all of them.

Tipp



There is very extensive documentation in „[Chapter 6. Best Packaging Practices](#)“ in the „Debian Developer's Reference“. Please read it.

6.2 debhelper package

Although a Debian package can be made by writing a **debian/rules** script without using the **debhelper** package, it is impractical to do so. There are too many modern „[Debian Policy](#)“ required features to be addressed, such as application of the proper file permissions, use of the proper architecture dependent library installation path, insertion of the installation hook scripts, generation of the debug symbol package, generation of package dependency information, generation of the package information files, application of the proper timestamp for reproducible build, etc.

Debhelper package provides a set of useful scripts in order to simplify Debian's packaging workflow and reduce the burden of package maintainers. When properly used, they will help packagers handle and implement „[Debian Policy](#)“ required features automatically.

The modern Debian packaging workflow can be organized into a simple modular workflow by:

- using the **dh** command to invoke many utility scripts automatically from the **debhelper** package, and

- configuring their behavior with declarative configuration files in the **debian/** directory.

You should almost always use **debhelper** as your package's build dependency. This document also assumes that you are using a fairly contemporary version of **debhelper** to handle packaging works in the following contents.

Anmerkung



For **debhelper** „compat >= 9“, the **dh** command exports compiler flags (**CFLAGS**, **CXXFLAGS**, **FFLAGS**, **CPPFLAGS** and **LDFLAGS**) with values as returned by **dpkg-buildflags** if they are not set previously. (The **dh** command calls **set_buildflags** defined in the **Debian::Debhelper::Dh_Lib** module.)

Anmerkung



debhelper(1) changes its behavior with time. Please make sure to read **debhelper-compat-upgrade-checklist(7)** to understand the situation.

6.3 Paketname und -version

If the upstream source comes as **hello-0.9.12.tar.xz**, you can take **hello** as the upstream source package name and **0.9.12** as the upstream version.

There are some limitations for what characters may be used as a part of the Debian package. The most notable limitation is the prohibition of uppercase letters in the package name. Here is a summary as a set of regular expressions:

- Upstream package name (**-p**): `[-+ . a - z 0 - 9] { 2 , }`
- Binary package name (**-b**): `[-+ . a - z 0 - 9] { 2 , }`
- Upstream version (**-u**): `[0 - 9] [-+ . : ~ a - z 0 - 9 A - Z] *`
- Debian revision (**-r**): `[0 - 9] [+ . ~ a - z 0 - 9 A - Z] *`

See the exact definition in „[Chapter 5 - Control files and their fields](#)“ in the „Debian Policy Manual“.

You must adjust the package name and upstream version accordingly for the Debian packaging.

In order to manage the package name and version information effectively under popular tools such as the **aptitude** command, it is a good idea to keep the length of package name to be equal or less than 30 characters; and the total length of version and revision to be equal or less than 14 characters. [2](#)

In order to avoid name collisions, the user visible binary package name should not be chosen from any generic words.

If upstream does not use a normal versioning scheme such as **2.30.32** but uses some kind of date such as **11Apr29**, a random codename string, or a VCS hash value as part of the version, make sure to remove them from the upstream version. Such information can be recorded in the **debian/changelog** file. If you need to invent a version string, use the **YYYYMMDD** format such as **20110429** as upstream version. This ensures that the **dpkg** command interprets later versions correctly as upgrades. If you need to ensure a smooth transition to a normal version scheme such as **0.1** in the future, use the **0~YYMMDD** format such as **0~110429** as upstream version, instead.

Version strings can be compared using the **dpkg** command as follows.

```
[~] $ dpkg --compare-versions ver1 op ver2
```

The version comparison rule can be summarized as:

²For more than 90% of packages, the package name is equal or less than 24 characters; the upstream version is equal or less than 10 characters and the Debian revision is equal or less than 3 characters.

- Strings are compared from the head to the tail.
- Letters are larger than digits.
- Numbers are compared as integers.
- Letters are compared in ASCII code order.

There are special rules for period (.), plus (+), and tilde (~) characters, as follows.

```
0.0 < 0.5 < 0.10 < 0.99 < 1 < 1.0~rc1 < 1.0 < 1.0+b1 < 1.0+nm1 < 1.1 < 2.0
```

One tricky case occurs when the upstream releases **hello-0.9.12-ReleaseCandidate-99.tar.xz** as the pre-release of **hello-0.9.12.tar.xz**. You can ensure the Debian package upgrade to work properly by renaming the upstream source to **hello-0.9.12~rc99.tar.xz**.

6.4 Natives Debian-Paket

The non-native Debian package in the Debian source format „**3.0 (quilt)**“ is the most normal Debian source package format. The **debian/source/format** file should have „**3.0 (quilt)**“ in it as described in **dpkg-source(1)**. The above workflow and the following packaging examples always use this format.

A native Debian package is the rare Debian binary package format. It may be used only when the package is useful and valuable only for Debian. Thus, its use is generally discouraged.

Achtung



A native Debian package is often accidentally built when its upstream tarball is not accessible from the **dpkg-buildpackage** command with its correct name *package_version.orig.tar.xz*. This is a typical newbie mistake caused by making a symlink name with „-“ instead of the correct one with „_“.

A native Debian package has no separation between the **upstream code** and the **Debian changes** and consists only of the following:

- *package_version.tar.xz* (copy or symlink of *package-version.tar.xz* with **debian/*** files.)
- *package_version.dsc*

If you need to create a native Debian package, create it in the Debian source format „**3.0 (native)**“ using **dpkg-source(1)**.

Tipp



There is no need to create the tarball in advance if the native Debian package format is used. The **debian/source/format** file should have „**3.0 (native)**“ in it as described in **dpkg-source(1)** and The **debian/source/format** file should have the version without the Debian revision (**1.0** instead of **1.0-1**). Then, the tarball containing is generated when „**dpkg-source -b**“ is invoked in the source tree.

6.5 debian/rules file

The **debian/rules** file is the executable script which re-targets the upstream build system to install files in the **\$(DESTDIR)** and creates the archive file of the generated files as the **deb** file. The **deb** file is used for the binary distribution and installed to the system using the **dpkg** command.

The Debian policy compliant **debian/rules** file supporting all the required targets can be written as simple as 3:

Simple debian/rules:

³The **debmake** command generates a bit more complicated **debian/rules** file. But this is the core part.

```
#!/usr/bin/make -f
#export DH_VERBOSE = 1

%:
    dh $@
```

The **dh** command functions as the sequencer to call all required „**dh target**“ commands at the right moment. ⁴

- **dh clean**: bereinigt Dateien in dem Quellbaum.
- **dh build** : build the source tree
- **dh build-arch** : build the source tree for architecture dependent packages
- **dh build-indep** : build the source tree for architecture independent packages
- **dh install** : install the binary files to **\$(DESTDIR)**
- **dh install-arch** : install the binary files to **\$(DESTDIR)** for architecture dependent packages
- **dh install-indep** : install the binary files to **\$(DESTDIR)** for architecture independent packages
- **dh binary** : generate the **deb** file
- **dh binary-arch** : generate the **deb** file for architecture dependent packages
- **dh binary-indep** : generate the **deb** file for architecture independent packages

Here, **\$(DESTDIR)** path depends on the build type.

- „**DESTDIR=debian/binarypackage/**“ for single binary package ⁵
- „**DESTDIR=debian/tmp/**“ for multi binary package

See „Abschnitt 9.2“ and „Abschnitt 9.3“ for customization.

Tipp



Setting „**export DH_VERBOSE = 1**“ outputs every command that modifies files on the build system. Also it enables verbose build logs for some build systems.

6.6 debian/control file

The **debian/control** file consists of blocks of metadata separated by blank lines. Each block of metadata defines the following, in this order:

- Metadaten für das Debian-Quellpaket
- Metadaten für das Debian-Binärpaket

See „Chapter 5 - Control files and their fields“ of the "Debian Policy Manual" for the definition of each metadata field.

⁴This simplicity is available since version 7 of the **debhelper** package. This guide assumes the use of **debhelper** version 13 or newer.

⁵This is the default up to **debhelper** v13. At **debhelper** v14, it warns the default change. After **debhelper** v15, it will change the default to **DESTDIR=debian/tmp/**.

Anmerkung



The **debmake** command sets the **debian/control** file with „**Build-Depends: debhelper-compat (= 13)**“ to set the **debhelper** compatibility level.

Tipp



If an existing package has a **debhelper** compatibility level lower than 13, it's probably time to update its packaging.

6.7 debian/changelog file

The **debian/changelog** file records the Debian package history.

- Edit this file using the **debchange** command (alias **dch**).
- The first line defines the upstream package version and the Debian revision.
- Document changes in a specific, formal, and concise style.
 - If Debian maintainer modification fixes reported bugs, add „**Closes: #<bug_number>**“ to close those bugs.
- Even if you're uploading your package yourself, you must document all non-trivial user-visible changes, such as:
 - Security-related bug fixes.
 - User interface changes.
- If you're asking a sponsor to upload it, document changes more comprehensively, including all packaging-related ones, to help with package review.
 - The sponsor shouldn't have to guess your reasoning behind package changes.
 - Remember that the sponsor's time is valuable.

After finishing your packaging and verifying its quality, execute the "**dch -r**" command and save the finalized **debian/changelog** file with the suite normally set to **unstable**.⁶ If you're packaging for backports, security updates, LTS, etc., use the appropriate distribution names instead.

The **debmake** command creates the initial template file with the upstream package version and the Debian revision. The distribution is set to **UNRELEASED** to prevent accidental uploads to the Debian archive.

Tipp



The date string used in the **debian/changelog** file can be manually generated by the „**LC_ALL=C date -R**“ command.

⁶If you're using the **vim** editor, make sure to save this with the **":wq"** command.

Tipp

Use a **debian/changelog** entry with a version string like **1.0.1-1~rc1** when experimenting. Later, consolidate such **changelog** entries into a single entry for the official package.

The **debian/changelog** file is installed in the **/usr/share/doc/binarypackage** directory as **changelog.Debian.gz** by the **dh_installchangelogs** command.

Der Changelog der Originalautoren wird als **changelog.gz** in das Verzeichnis **/usr/share/doc/Binärpaket** installiert.

The upstream changelog is automatically found by the **dh_installchangelogs** using the case insensitive match of its file name to **changelog**, **changes**, **changelog.txt**, **changes.txt**, **history**, **history.txt**, or **changelog.md** and searched in the **/ doc/** or **docs/** directories.

6.8 debian/copyright file

Debian takes copyright and license matters very seriously. The "Debian Policy Manual" requires a summary of these in the **debian/copyright** file of the package.

- „12.5. Copyright information“
- „2.3. Copyright considerations“
- „License information“

The **debmake** command creates the initial **debian/copyright** template file using the **licensecheck(1)** command.

6.9 debian/patches/* files

As demonstrated in „Abschnitt 5.9“, the **debian/patches/** directory holds

- **patch-file-name.patch** files providing **-p1** patches and
- the **series** file which defines how these patches are applied.

See how these files are used in:

- „Abschnitt 13.6“ to build the Debian source package
- „Abschnitt 13.7“ to extract source files from the Debian source package

Anmerkung

Header texts of these patches should conform to „DEP-3“.

Anmerkung

If you want to use VCS tools such as **git**, **gbp** and **dgit** to create and manage these patches after learning basics here, please refer to later in „Kapitel 11“.

6.10 debian/source/include-binaries file

The „**dpkg-source --commit**“ command functions like **dquilt** but has one advantage over the **dquilt** command. The **dquilt** command can't handle modified binary files since they are not representable in a diff. Also, adding binary files under the **debian/** directory is normally rejected by **dpkg-source**. By listing these binary files in **debian/source/include-binaries**, the maintainer can include these binary files to the Debian source package generated by **dpkg-source**.

6.11 debian/watch file

Anmerkung



This file is for use by the Debian non-native package.

The **uscan(1)** command downloads the latest upstream version using the **debian/watch** file. E.g.:
Basic debian/watch file:

```
version=4
https://ftp.gnu.org/gnu/hello/ @PACKAGE@@ANY_VERSION@@ARCHIVE_EXT@
```

The **uscan** command may verify the authenticity of the upstream tarball with optional configuration (see „Abschnitt 6.12“).

See **uscan(1)**, „Abschnitt 9.4“, „Abschnitt 8.1“, and „Abschnitt 11.7“ for more.

6.12 debian/upstream/signing-key.asc file

Some packages are signed by a GPG key and their authenticity can be verified using their public GPG key.

For example, „GNU hello“ can be downloaded via HTTP from <https://ftp.gnu.org/gnu/hello/> . There are sets of files:

- **hello-version.tar.xz** (upstream source)
- **hello-version.tar.xz.sig** (detached signature)

Let's pick the latest version set.

Download the upstream tarball and its signature.

```
[base_dir] $ wget https://ftp.gnu.org/gnu/hello/hello-2.9.tar.xz
...
[base_dir] $ wget https://ftp.gnu.org/gnu/hello/hello-2.9.tar.xz.sig
...
[base_dir] $ gpg --verify hello-2.9.tar.xz.sig
gpg: Signature made Thu 10 Oct 2013 08:49:23 AM JST using DSA key ID 80EE4A00
gpg: Can't check signature: public key not found
```

If you know the public GPG key of the upstream maintainer from the mailing list, use it as the **debian/upstream/signing-key.asc** file. Otherwise, use the hkp keyserver and check it via your [web of trust](#).

Download public GPG key for the upstream

```
[base_dir] $ gpg --keyserver hkp://keys.gnupg.net --recv-key 80EE4A00
gpg: requesting key 80EE4A00 from hkp server keys.gnupg.net
gpg: key 80EE4A00: public key "Reuben Thomas <rtr@sc3d.org>" imported
gpg: no ultimately trusted keys found
gpg: Total number processed: 1
```

```
gpg:                imported: 1
[base_dir] $ gpg --verify hello-2.9.tar.xz.sig
gpg: Signature made Thu 10 Oct 2013 08:49:23 AM JST using DSA key ID 80EE4A00
gpg: Good signature from "Reuben Thomas <rtrt@sc3d.org>"
...
Primary key fingerprint: 9297 8852 A62F A5E2 85B2  A174 6808 9F73 80EE 4A00
```

Tipp

If your network environment blocks access to the HKP port **11371**, use „**hkp://keyserver.ubuntu.com:80**“ instead.

After confirming the key ID **80EE4A00** is a trustworthy one, download its public key into the **debian/upstream/signing-key.asc** file.

Set public GPG key to `debian/upstream/signing-key.asc`

```
[base_dir] $ gpg --armor --export 80EE4A00 >debian/upstream/signing-key.asc
```

With the above **debian/upstream/signing-key.asc** file and the following **debian/watch** file, the **uscan** command can verify the authenticity of the upstream tarball after its download. E.g.:

Improved `debian/watch` file with GPG support:

```
version=4
opts="pgpsigurlmangle=s/$/.sig/" \
https://ftp.gnu.org/gnu/hello/ @PACKAGE@@ANY_VERSION@@ARCHIVE_EXT@
```

6.13 **debian/salsa-ci.yml** file

Install [Salsa CI](#) configuration file. See „Abschnitt [11.3](#)“.

6.14 **Other `debian/*` files**

Optional configuration files may be added under the **debian/** directory. Most of them are to control **dh_*** commands offered by the **debhelper** package but there are some for **dpkg-source**, **lintian** and **gbp** commands.

Tipp

Even an upstream source without its build system can be packaged just by using these files. See „Abschnitt [14.2](#)“ as an example.

The alphabetical list of notable optional **debian/binarypackage.*** configuration files listed below provides very powerful means to set the installation path of files. Please note:

- The „-x^[01234]“ superscript notation that appears in the following list indicates the minimum value for the **debmake -x** option that generates the associated template file. See „Abschnitt [16.4](#)“ or **debmake(1)** for details.
- For a single binary package, the „*binarypackage*.“ part of the filename in the list may be removed.
- For a multi binary package, a configuration file missing the „*binarypackage*“ part of the filename is applied to the first binary package listed in the **debian/control**.

- When there are many binary packages, their configurations can be specified independently by prefixing their name to their configuration filenames such as „*package-1.install*“, „*package-2.install*“, etc.
- Some template configuration files may not be created by the **debmake** command. In such cases, you need to create them with an editor.
- Some configuration template files generated by the **debmake** command with an extra **.ex** suffix need to be activated by removing that suffix.
- The **debmake -B** command adds template files with an extra **.ex** suffix for all existing template files without **.ex** and they need to be activated by removing that suffix.
- Nicht verwendete Vorlagendateien, die durch den Befehl **debmake** erstellt wurden, sollten entfernt werden.
- Kopieren Sie die Konfigurationsvorlagendateien wie benötigt nach den Dateinamen, die ihren Programmpaketnamen entsprechen.

binarypackage.bug-control ^{-x2} installed as **usr/share/bug/binarypackage/control** in *binarypackage*. See „Abschnitt 9.11“.

binarypackage.bug-presubj ^{-x2} installed as **usr/share/bug/binarypackage/presubj** in *binarypackage*. See „Abschnitt 9.11“.

binarypackage.bug-script ^{-x2} installed as **usr/share/bug/binarypackage** or **usr/share/bug/binarypackage/scripts** in *binarypackage*. See „Abschnitt 9.11“.

Binärpaket.bash-completion List **bash** completion scripts to be installed.

The **bash-completion** package is required for both build and user environments.

Siehe **dh_bash-completion(1)**.

clean ^{-x1} List files that should be removed but are not cleaned by the **dh_auto_clean** command.

Siehe **dh_auto_clean(1)** und **dh_clean(1)**.

compat ^{-x4} Set the **debhelper** compatibility level. (deprecated)

Use „**Build-Depends: debhelper-compat (= 13)**“ in **debian/control** to specify the compatibility level and remove **debian/compat**.

See „**COMPATIBILITY LEVELS**“ in **debhelper(7)**.

binarypackage.conf files ^{-x3} This optional file is installed into the **DEBIAN** directory within the binary package while supplementing it with all the conf files auto-detected by **debhelper**.

This file is primarily useful for using "special" entries such as the remove-on-upgrade feature from **dpkg(1)**.

If the program you're packaging requires every user to modify the configuration files in the **/etc** directory, there are two popular ways to arrange for them not to be conf files, keeping the **dpkg** command happy and quiet.

- Create a symlink under the **/etc** directory pointing to a file under the **/var** directory generated by the maintainer scripts.
- Create a file generated by the maintainer scripts under the **/etc** directory.

Siehe **dh_installdeb(1)**.

binarypackage.config This is the **debconf config** script used for asking any questions necessary to configure the package. See „Abschnitt 10.22“.

Binärpaket.cron.hourly ^{-x3} Installed into the **etc/cron/hourly/binarypackage** file in *binarypackage*.

Siehe **dh_installcron(1)** und **cron(8)**.

Binärpaket.cron.daily ^{-x3} Installed into the **etc/cron/daily/binarypackage** file in *binarypackage*.

Siehe **dh_installcron(1)** und **cron(8)**.

Binärpaket.cron.weekly ^{-x3} Installed into the **etc/cron/weekly/binarypackage** file in *binarypackage*.

Siehe **dh_installcron(1)** und **cron(8)**.

Binärpaket.cron.monthly ^{-x3} Installed into the `*etc/cron/monthly/*binarypackage` file in *binarypackage*.

Siehe `dh_installcron(1)` und `cron(8)`.

Binärpaket.cron.d ^{-x3} Installed into the `etc/cron.d/binarypackage` file in *binarypackage*.

Siehe `dh_installcron(1)`, `cron(8)` und `crontab(5)`.

Binärpaket.default ^{-x3} If this exists, it is installed into `etc/default/binarypackage` in *binarypackage*.

Siehe `dh_installinit(1)`.

binarypackage.dirs ^{-x1} List directories to be created in *binarypackage*.

Siehe `dh_installdirs(1)`.

Usually, this is not needed since all `dh_install*` commands create required directories automatically. Use this only when you run into trouble.

binarypackage.doc-base ^{-x1} Installed as the **doc-base** control file in *binarypackage*.

See `dh_installdocs(1)` and „[Debian doc-base Manual \(doc-base.html\)](#)“ provided by the **doc-base** package.

binarypackage.docs ^{-x1} List documentation files to be installed in *binarypackage*.

Siehe `dh_installdocs(1)`.

binarypackage.emacsen-compat Installed into `usr/lib/emacsen-common/packages/compat/binarypackage` in *binarypackage*.

Siehe `dh_installemacsen(1)`.

Binärpaket.emacsen-install ^{-x3} Installed into `usr/lib/emacsen-common/packages/install/binarypackage` in *binarypackage*.

Siehe `dh_installemacsen(1)`.

Binärpaket.emacsen-remove ^{-x3} Installed into `usr/lib/emacsen-common/packages/remove/binarypackage` in *binarypackage*.

Siehe `dh_installemacsen(1)`.

Binärpaket.emacsen-startup ^{-x3} Installed into `usr/lib/emacsen-common/packages/startup/binarypackage` in *binarypackage*.

Siehe `dh_installemacsen(1)`.

binarypackage.examples ^{-x1} List example files or directories to be installed into `usr/share/doc/binarypackage` in *binarypackage*.

Siehe `dh_installexamples(1)`.

gbp.conf ^{-x1} Falls diese existiert, funktioniert sie als Konfigurationsdatei für den Befehl **gbp**.

Siehe `gbp.conf(5)`, `gbp(1)` und `git-buildpackage(1)`.

binarypackage.info ^{-x1} Führt Info-Dateien auf, die in *Binärpaket* installiert werden.

Siehe `dh_installinfo(1)`.

binarypackage.init ^{-x4} Installed into `etc/init.d/binarypackage` in *binarypackage*. (deprecated)

Siehe `dh_installinit(1)`.

binarypackage.install ^{-x1} Liste der Dateien, die installiert werden sollten, aber nicht durch den Befehl `dh_auto_install` installiert wurden.

Siehe `dh_install(1)` und `dh_auto_install(1)`.

binarypackage.links ^{-x1} List pairs of source and destination files to be symlinked. Each pair should be put on its own line, with the source and destination separated by whitespace.

Siehe `dh_link(1)`.

binarypackage.lintian-overrides ^{-x2} Installed into `usr/share/lintian/overrides/binarypackage` in the package build directory. This file is used to suppress erroneous **lintian** diagnostics.

Siehe `dh_lintian(1)`, `lintian(1)` und „[Lintian User's Manual](#)“.

binarypackage.maintscript ^{-x2} If this optional file exists, **debhelper** uses this as the template to generate **DEBIAN/binarypackage.{pre,post}{inst,rm}** files within the binary package while adding „-- \"\$@““ to the `dpkg-maintscript-helper(1)` command.

See `dh_installdeb(1)` and „[Chapter 6 - Package maintainer scripts and installation procedure](#)“ in the „*Debian Policy Manual*“.

manpage.* ^{-x2} These are manpage template files generated by the **debmake** command. Please rename these to appropriate file names and update their contents.

Debian Policy requires that each program, utility, and function should have an associated manual page included in the same package. Manual pages are written in **nroff**(1). If you are new to making a manpage, use **manpage.asciidoc** ^{-x3} or **manpage.1** ^{-x3} as the starting point.

binarypackage.manpages ^{-x1} List man pages to be installed.

Siehe **dh_installman**(1).

Binärpaket.menu (veraltet, nicht mehr installiert) [tech-ctte #741573](#) decided „Debian should use **.desktop** files as appropriate“.

Debian menu file installed into **usr/share/menu/binarypackage** in **binarypackage**.

See **menufile**(5) for its format. See **dh_installmenu**(1).

NEWS Installed into **usr/share/doc/binarypackage/NEWS.Debian**.

Siehe **dh_installchangelogs**(1).

patches/* Collection of **-p1** patch files which are applied to the upstream source before building the source.

No patch files are generated by the **debmake** command.

Siehe **dpkg-source**(1), „Abschnitt 4.4“ und „Abschnitt 5.9“.

patches/series ^{-x1} The application sequence of the **patches/*** patch files.

binarypackage.preinst ^{-x3}, **binarypackage.postinst** ^{-x3}, **binarypackage.prerm** ^{-x3}, **binarypackage.postrm** ^{-x3}

If these optional files exist, the corresponding files are installed into the **DEBIAN** directory within the binary package after enriched by **debhelper**. Otherwise, these files in the **DEBIAN** directory within the binary package is generated by **debhelper**.

Whenever possible, simpler **binarypackage.maintscript** should be used instead.

See **dh_installdeb**(1) and „Chapter 6 - Package maintainer scripts and installation procedure“ in the „Debian Policy Manual“.

See also **debconf-devel**(7) and „3.9.1 Prompting in maintainer scripts“ in the „Debian Policy Manual“.

README.Debian ^{-x1} Installed into the first binary package listed in the **debian/control** file as **usr/share/doc/binarypackage/README.Debian**.

This file provides the information specific to the Debian package.

Siehe **dh_installdocs**(1).

README.source ^{-x1} Installed into the first binary package listed in the **debian/control** file as **usr/share/doc/binarypackage/README.source**.

If running „**dpkg-source -x**“ on a source package doesn't produce the source of the package, ready for editing, and allow one to make changes and run **dpkg-buildpackage** to produce a modified package without taking any additional steps, creating this file is recommended.

See „[Debian policy manual section 4.14](#)“.

binarypackage.service ^{-x3} If this exists, it is installed into **lib/systemd/system/binarypackage.service** in **binarypackage**.

Siehe **dh_systemd_enable**(1), **dh_systemd_start**(1) und **dh_installinit**(1).

source/format ^{-x1} The Debian package format.

- Use „**3.0 (quilt)**“ to make this non-native package (popular)
- Use „**3.0 (native)**“ to make this native package

See „SOURCE PACKAGE FORMATS“ in **dpkg-source**(1).

source/lintian-overrides ^{-x2} This file is not installed, but is scanned by the **lintian** command to provide overrides for the source package.

Siehe **dh_lintian**(1) und **lintian**(1).

source/local-options and **source/local-patch-header** ^{-x4}

Anmerkung



These files are not compatible with the **dgkit** workflow. See „Abschnitt [11.14](#)“.

There is no reason to use these with the current version of **dpkg-source**(1).

source/options ^{-x2} The **dpkg-source** command uses this content as its options. This is typically used with „Abschnitt 11.13“ and options may be:

- **auto-commit**
- **single-debian-patch**

This is included in the generated source package.

See „FILE FORMATS“ in **dpkg-source**(1).

source/patch-header ^{-x2} Free form text that is put on top of the automatic patch generated.

This is included in the generated source package and is meant to be committed to the „Abschnitt 11.13“.

See „FILE FORMATS“ in **dpkg-source**(1).

binarypackage.symbols ^{-x1} The symbols files, if present, are passed to the **dpkg-gensymbols** command to be processed and installed.

Siehe **dh_makeshlibs**(1) und „Abschnitt 10.16“.

binarypackage.templates This is the **debconf templates** file used for asking any questions necessary to configure the package. See „Abschnitt 10.22“.

tests/control ^{-x1} This is the RFC822-style test meta data file defined in **DEP-8**. See **autopkg-test**(1) and „Abschnitt 10.4“.

TODO Installed into the first binary package listed in the **debian/control** file as **usr/share/doc/binarypackage/T**

Siehe **dh_installdocs**(1).

Binärpaket.tmpfile ^{-x3} If this exists, it is installed into **usr/lib/tmpfiles.d/binarypackage.conf** in **binarypackage**.

Siehe **dh_systemd_enable**(1), **dh_systemd_start**(1) und **dh_installinit**(1).

binarypackage.upstart ^{-x4} If this exists, it is installed into **etc/init/package.conf** in the package build directory. (deprecated)

Siehe **dh_installinit**(1).

upstream/metadata ^{-x1} Per-package machine-readable metadata about upstream (**DEP-12**). See „Upstream METadata GAttered with YAmI (UMEGAYA)“.

Kapitel 7

Quality of packaging

The quality of Debian packaging can be improved by using testing tools.

- **lintian**(1)
- **piuparts**(1)

If you follow „Kapitel 4“, these are automatically executed. You are expected to fix all warnings.

7.1 Reformat debian/* files with wrap-and-sort

It is good idea to reformat **debian/*** files consistently using the **wrap-and-sort**(1) command in **devscripts** package.

Reformat debian/* files

```
[debhello-0.0] $ wrap-and-sort -vast
```

7.2 Validate debian/* files with debputy

The new **debputy** tool [1](#) includes subcommands to validate (and fix) most files in **debian/***.

Check correctness of files in debian/*

```
[debhello-0.0] $ debputy lint --spellcheck
```

Format debian/control and debian/tests/control files

```
[debhello-0.0] $ debputy reformat --style black
```

Using the „**debputy reformat**“ command obsoletes using „**wrap-and-sort -vast**“.

The debputy tool also includes a language server. You can set up to get real-time feedback while editing **debian/*** files with any modern editor supporting the [Language Server Protocol](#).

¹The main purpose of the debputy tool is to offer a new Debian package build paradigm. This new paradigm is beyond the scope of this tutorial.

Kapitel 8

Sanitization of the source

There are a few cases that require sanitizing the source to prevent contamination of the generated Debian source package.

- Non-https://www.debian.org/social_contract.html#guidelines[DFSG] compliant content in the upstream source.
 - Debian takes software freedom seriously and adheres to the [DFSG](#).
- Extraneous auto-generated content in the upstream source.
 - Debian packages should rebuild these under the latest system.
- Extraneous VCS content in the upstream source.
 - The `-i` and `-I` options set in „Abschnitt 4.5“ for the **dpkg-source**(1) command should avoid these.
 - ✱ The `-i` option is intended for non-native Debian packages.
 - ✱ The `-I` option is intended for native Debian packages.

There are several methods to avoid including undesirable content.

8.1 Fix with Files-Excluded

This method is suitable for avoiding non-https://www.debian.org/social_contract.html#guidelines[DFSG] compliant content in the upstream source tarball.

- List the files to be removed in the **Files-Excluded** stanza of the **debian/copyright** file.
- List the URL to download the upstream tarball in the **debian/watch** file.
- Führen Sie den Befehl **uscan** aus, um einen neuen Tarball der Originalautoren herunterzuladen.
 - Alternatively, use the „**gbp import-orig --uscan --pristine-tar**“ command.
- **mk-origtargz** invoked from **uscan** removes excluded files from the upstream tarball and repack it as a clean tarball.
- Der resultierende Tarball hat die Versionsnummer mit einer zusätzlichen Endung **+dfsg**.

See „**COPYRIGHT FILE EXAMPLES**“ in **mk-origtargz**(1).

8.2 Fix with „debian/rules clean“

This method is suitable for avoiding auto-generated files by removing them in the **„debian/rules clean“** target.

Anmerkung



The **„debian/rules clean“** target is called before the **„dpkg-source --build“** command by the **dpkg-buildpackage** command. The **„dpkg-source --build“** command ignores removed files.

8.3 Fix with extend-diff-ignore

This is for the non-native Debian package.

The problem of extraneous diffs can be fixed by ignoring changes made to specific parts of the source tree. This is done by adding the **„extend-diff-ignore=...“** line in the **debian/source/options** file.

debian/source/options to exclude the config.sub, config.guess and Makefile files:

```
# Don't store changes on autogenerated files
extend-diff-ignore = "(^|/)(config\.sub|config\.guess|Makefile)$"
```

Anmerkung



This approach always works, even when you can't remove the file. It saves you from having to make a backup of the unmodified file just to restore it before the next build.

Tipp



If you use the **debian/source/local-options** file instead, you can hide this setting from the generated source package. This may be useful when local non-standard VCS files interfere with your packaging.

8.4 Fix with tar-ignore

This is for the native Debian package.

You can exclude certain files in the source tree from the generated tarball by adjusting the file glob. Add the **„tar-ignore=...“** lines in the **debian/source/options** or **debian/source/local-options** files.

Anmerkung



For example, if the source package of a native package needs files with the **.o** extension as part of the test data, the setting in „Abschnitt 4.5“ may be too aggressive. You can work around this by dropping the **-I** option for **DEB_BUILD_DPKG_BUILDPACKAGE_OPTS** in „Abschnitt 4.5“ and adding the **„tar-ignore=...“** lines in the **debian/source/local-options** file for each package.

8.5 Fix with „git clean -dfx“

The problem of extraneous content in the second build can be avoided by restoring the source tree. This is done by committing the source tree to the Git repository before the first build.

You can restore the source tree before the second package build. For example:

```
[debhello] $ git reset --hard
[debhello] $ git clean -dfx
```

This works because the **dpkg-source** command ignores the contents of typical VCS files in the source tree, as specified by the **DEBUILD_DPKG_BUILDPACKAGE_OPTS** setting in „Abschnitt 4.5“.

Tipp



If the source tree is not managed by a VCS, run "**git init; git add -A .; git commit**" before the first build.

Kapitel 9

More on packaging

Let's explore more fundamentals of Debian packaging.

9.1 Package customization

All customization data for the Debian source package resides in the **debian/** directory as presented in „Abschnitt 5.7“:

- The Debian package build system can be customized through the **debian/rules** file (see „Abschnitt 9.2“).
- The Debian package installation path etc. can be customized through the addition of configuration files such as *package.install* and *package.docs* in the **debian/** directory for the **dh_*** commands from the **debhelper** package (see „Abschnitt 6.14“).

When these are not sufficient to make a good Debian package, **-p1** patches of **debian/patches/*** files are deployed to modify the upstream source. These are applied in the sequence defined in the **debian/patches/series** file before building the package as presented in „Abschnitt 5.9“.

You should address the root cause of the Debian packaging problem in the least invasive way possible. This approach will make the generated package more robust for future upgrades.

Anmerkung



If the patch addressing the root cause is useful to the upstream project, send it to the upstream maintainer.

9.2 Customized debian/rules

Flexible customization of the Abschnitt 6.5 is achieved by adding appropriate **override_dh_*** targets and their rules.

When a special operation is required for a certain **dh_foo** command invoked by the **dh** command, its automatic execution can be overridden by adding the makefile target **override_dh_foo** in the **debian/rules** file.

The build process may be customized via the upstream provided interface such as arguments to the standard source build system commands, such as:

- **configure**,
- **Makefile**,
- „**python -m build**“, or
- **Build.PL**.

In this case, you should add the **override_dh_auto_build** target with „**dh_auto_build -- arguments**“. This ensures that *arguments* are passed to the build system after the default parameters that **dh_auto_build** usually passes.

Tipp



Avoid executing bare build system commands directly if they are supported by the **dh_auto_build** command.

Siehe:

- „Abschnitt 5.7“ for the basic example.
- „Abschnitt 10.3“ to be reminded of the challenge involving the underlying build system.
- „Abschnitt 10.10“ for multiarch customization.
- „Abschnitt 10.6“ for hardening customization.

9.3 Variables for debian/rules

Some variable definitions useful for customizing **debian/rules** can be found in files under **/usr/share/dpkg/**. Notably:

pkg-info.mk Set **DEB_SOURCE**, **DEB_VERSION**, **DEB_VERSION_EPOCH_UPSTREAM**, **DEB_VERSION_UPSTREAM**, and **DEB_DISTRIBUTION** variables obtained from **dpkg-parsechangelog(1)**. (useful for backport support etc..)

vendor.mk Set **DEB_VENDOR** and **DEB_PARENT_VENDOR** variables; and **dpkg_vendor_derives_from** macro obtained from **dpkg-vendor(1)**. (useful for vendor support (Debian, Ubuntu, ...).)

architecture.mk Set **DEB_HOST_*** and **DEB_BUILD_*** variables obtained from **dpkg-architecture(1)**.

buildflags.mk Set **CFLAGS**, **CPPFLAGS**, **CXXFLAGS**, **OBJCFLAGS**, **OBJCXXFLAGS**, **GCJFLAGS**, **FFLAGS**, **FCFLAGS**, and **LDFLAGS** build flags obtained from **dpkg-buildflags(1)**.

For example, you can add an extra option to **CONFIGURE_FLAGS** for **linux-any** target architectures by adding the following to **debian/rules**:

```
DEB_HOST_ARCH_OS ?= $(shell dpkg-architecture -qDEB_HOST_ARCH_OS)
...
ifeq ($(DEB_HOST_ARCH_OS), linux)
CONFIGURE_FLAGS += --enable-wayland
endif
```

Siehe „Abschnitt 10.10“, **dpkg-architecture(1)** und **dpkg-buildflags(1)**.

9.4 New upstream release

When a new upstream release tarball **debhello-newversion.tar.xz** is released, the Debian source package can be updated by invoking commands in the old source tree as:

```
[debhello-0.0] $ uscan
... debhello-newversion.tar.xz downloaded
[debhello-0.0] $ update -v newversion ../debhello-newversion.tar.xz
```

- The **debian/watch** file in the old source tree must be a valid one.
- This make symlink **../debhello_newversion.orig.tar.xz** pointing to **../debhello-newversion.tar.xz**.

- Files are extracted from `../debhello-newversion.tar.xz` to `../debhello-newversion/`
- Files are copied from `../debhello-oldversion/debian/` to `../debhello-newversion/debian/`.

After the above, you should refresh `debian/patches/*` files (see „Abschnitt 9.5“) and update `debian/changelog` with the `dch(1)` command.

When „`debian uupdate`“ is specified at the end of line in the `debian/watch` file, `uscan` automatically executes `uupdate(1)` after downloading the tarball.

9.5 Manage patch queue with dquilt

You can add, drop, and refresh `debian/patches/*` files with `dquilt` to manage patch queue.

- **Add** a new patch `debian/patches/bugname.patch` recording the upstream source modification on the file `buggy_file` as:

```
[debhello-0.0] $ dquilt push -a
[debhello-0.0] $ dquilt new bugname.patch
[debhello-0.0] $ dquilt add buggy_file
[debhello-0.0] $ vim buggy_file
...
[debhello-0.0] $ dquilt refresh
[debhello-0.0] $ dquilt header -e
[debhello-0.0] $ dquilt pop -a
```

- **Drop** (`==` disable) an existing patch
 - Comment out pertinent line in `debian/patches/series`
 - Erase the patch itself (optional)
- **Refresh** `debian/patches/*` files to make „`dpkg-source -b`“ work as expected after updating a Debian package to the new upstream release.

```
[debhello-0.0] $ uscan; uupdate # updating to the new upstream release
[debhello-0.0] $ while dquilt push; do dquilt refresh ; done
[debhello-0.0] $ dquilt pop -a
```

- If conflicts are encountered with „`dquilt push`“ in the above, resolve them and run „`dquilt refresh`“ manually for each of them.

9.6 Build commands

Here is a recap of popular low level package build commands. There are many ways to do the same thing.

- **dpkg-buildpackage** = core of package building tool
- **debuild** = `dpkg-buildpackage` + `lintian` (build under the sanitized environment variables)
- **schroot** = core of the Debian chroot environment tool
- **sbuild** = `dpkg-buildpackage` on custom `schroot` (build in the chroot)

9.7 Note on sbuild

The `sbuild(1)` command is a wrapper script of `dpkg-buildpackage` which builds Debian binary packages in a chroot environment managed by the `schroot(1)` command. For example, building for Debian **unstable** suite can be done as:

```
[debhello-0.0] $ sudo sbuild -d unstable
```

In **schroot**(1) terminology, this builds a Debian package in a clean ephemeral **chroot** „**chroot:unstable-amd64-sbuild**“ started as a copy of the clean minimal persistent **chroot** „**source:unstable-amd64-sbuild**“.

This build environment was set up as described in „Abschnitt 4.6“ with „**sbuild-debian-developer-setup -s unstable**“ which essentially did the following:

```
[~] $ sudo mkdir -p /srv/chroot/dist-amd64-sbuild
[~] $ sudo sbuild-createchroot unstable /srv/chroot/unstable-amd64-sbuild http:// ↔
    deb.debian.org/debian
[~] $ sudo usermod -a -G sbuild <your_user_name>
[~] $ sudo newgrp -
```

The **schroot**(1) configuration for **unstable-amd64-sbuild** was generated at **/etc/schroot/chroot.d/unstable-amd64-sbuild.\$Suffix** :

```
[unstable-amd64-sbuild]
description=Debian sid/amd64 autobuilder
groups=root,sbuild
root-groups=root,sbuild
profile=sbuild
type=directory
directory=/srv/chroot/unstable-amd64-sbuild
union-type=overlay
```

Hier:

- The profile defined in the **/etc/schroot/sbuild/** directory is used to setup the chroot environment.
- **/srv/chroot/unstable-amd64-sbuild** directory holds the chroot filesystem.
- **/etc/sbuild/unstable-amd64-sbuild** is symlinked to **/srv/chroot/unstable-amd64-sbuild** .

You can update this source chroot „**source:unstable-amd64-sbuild**“ by:

```
[~] $ sudo sbuild-update -udcar unstable
```

You can log into this source chroot „**source:unstable-amd64-sbuild**“ by:

```
[~] $ sudo sbuild-shell unstable
```

Tipp



If your source chroot filesystem is missing packages such as **libeatmydata1**, **ccache**, and **lintian** for your needs, you may want to install these by logging into it.

9.8 Special build cases

The **orig.tar.xz** file may need to be uploaded for a Debian revision other than **0** or **1** under some exceptional cases (e.g., for a security upload).

When an essential package becomes a non-essential one (e.g., **adduser**), you need to remove it manually from the existing chroot environment for its use by **piuparts**.

9.9 Upload orig.tar.xz

When you first upload the package to the archive, you need to include the original **orig.tar.xz** source, too.

If the Debian revision number of the package is either **1** or **0**, this is the default. Otherwise, you must provide the **dpkg-buildpackage** option **-sa** to the **dpkg-buildpackage** command.

- **dpkg-buildpackage -sa**
- **debuild -sa**
- **sbuild**
- For „**gbp buildpackage**“, edit the **~/l.gbp.conf** file.

Tipp



On the other hand, the **-sd** option will force the exclusion of the original **orig.tar.xz** source.

Tipp



Security uploads require including the **orig.tar.xz** file.

9.10 Skipped uploads

If you created multiple entries in the **debian/changelog** while skipping uploads, you must create a proper ***_changes** file which includes all changes since the last upload. This can be done by specifying the **dpkg-buildpackage** option **-v** with the last uploaded version, e.g., **1.2**.

- **dpkg-buildpackage -v1.2**
- **debuild -v1.2**
- **sbuild --debbuildopts -v1.2**
- For **gbp buildpackage**, edit the **~/l.gbp.conf** file.

9.11 Bug reports

The **reportbug(1)** command used for the bug report of *binarypackage* can be customized by the files in **usr/share/bug/binarypackage/**.

The **dh_bugfiles** command installs these files from the template files in the **debian/** directory.

- **debian/binarypackage.bug-control** → **usr/share/bug/binarypackage/control**
 - This file contains some directions such as redirecting the bug report to another package.
- **debian/binarypackage.bug-presubj** → **usr/share/bug/binarypackage/presubj**
 - This file is displayed to the user by the **reportbug** command.
- **debian/binarypackage.bug-script** → **usr/share/bug/binarypackage** or **usr/share/bug/binarypackage/script**
 - The **reportbug** command runs this script to generate a template file for the bug report.

See `dh_bugfiles(1)` and „[reportbug's Features for Developers \(README.developers\)](#)“

Tipp



If you always remind the bug reporter of something or ask them about their situation, use these files to automate it.

Kapitel 10

Advanced packaging

Let's describe advanced topics on Debian packaging.

10.1 Historical perspective

Let me oversimplify historical perspective of Debian packaging practices focused on the non-native packaging.

[Debian was started in 1990s](#) when upstream packages were available from public FTP sites such as [Sunsite](#). In those early days, Debian packaging used Debian source format currently known as the Debian source format „1.0“:

- The Debian source package ships a set of files for the Debian source package.
 - *package_version.orig.tar.xz* : symlink to or copy of the upstream released file.
 - *package_version-revision.diff.gz* : „**One big patch**“ for Debian modifications.
 - *package_version-revision.dsc* : package description.
- Several workaround approaches such as **dpatch**, **db**s, or **cdb**s were deployed to manage multiple topic patches.

The modern Debian source format „**3.0 (quilt)**“ was invented around 2008 (see „[ProjectsDebSrc3.0](#)“):

- The Debian source package ships a set of files for the Debian source package.
 - *package_version.orig.tar.gz* : symlink to or copy of the upstream released file.
 - *package_version-revision.debian.tar.gz* : tarball of **debian/** for Debian modifications.
 - ✱ The **debian/source/format** file contains „**3.0 (quilt)**“.
 - ✱ Optional multiple topic patches are stored in the **debian/patches/** directory.
 - *package_version-revision.dsc* : package description.
- The standardized approach to manage multiple topic patches using **quilt(1)** is deployed for the Debian source format „**3.0 (quilt)**“.

Most Debian packages adopted the Debian source formats „**3.0 (quilt)**“ and „**3.0 (native)**“.

Now, the **git(1)** is popular with upstream and Debian developers. The **git** and its associated tools are important part of the modern Debian packaging workflow. This modern workflow involving **git** will be mentioned later in „Kapitel 11“.

10.2 Current trends

Current Debian packaging practices and their trends are moving target. See:

- „[Debian Trends](#)“ — Hints for „De facto standard“ of Debian practices
 - Build systems: **dh**

- Debian source format: „**3.0 (quilt)**“
- VCS: **git**
- VCS Hosting: [salsa](#)
- Rules-Requires-Root: adopted, fakeroot
- Copyright format: [DEP-5](#)
- „**debhelper-compat-upgrade-checklist**(7) manpage“ — Upgrade checklist for **debhelper**
- „[DEP - Debian Enhancement Proposals](#)“ — Formal proposals to enhance Debian

You can also search entire Debian source code data by yourself, too.

- „[Debian Sources](#)“ — code search tool
 - „[Debian Code Search](#)“ — wiki page describing its usage
- „[Debian Code Search](#)“ — another code search tool

10.3 Note on build system

Auto-generated files of the build system may be found in the released upstream tarball. These should be regenerated when Debian package is build. E.g.:

- „**dh \$@ --with autoreconf**“ should be used in the **debian/rules** if Autotools (**autoconf** + **automake**) are used.

Some modern build system may be able to download required source codes and binary files from arbitrary remote hosts to satisfy build requirements. Don't use this download feature. The official Debian package is required to be build only with packages listed in **Build-Depends:** of the **debian/control** file.

10.4 Continuous integration

The **dh_auto_test**(1) command is a **debhelper** command that tries to automatically run the test suite provided by the upstream developer during the Debian package building process.

The **autopkgtest**(1) command can be used after the Debian package building process. It tests generated Debian binary packages in the virtual environment using the **debian/tests/control** RFC822-style metadata file as [continuous integration](#) (CI). See:

- Documents in the **/usr/share/doc/autopkgtest/** directory
- „[4. autopkgtest: Automatic testing for packages](#)“ of the „Ubuntu Packaging Guide“

There are several other CI tools on Debian for you to explore.

- The [Salsa](#) offers „Abschnitt 11.3“.
- The **debci** package: CI platform on top of the **autopkgtest** package
- The **jenkins** package: generic CI platform

10.5 Bootstrapping

Debian cares about supporting new ports or flavours. The new ports or flavours require [bootstrap-ping](#) operation for the cross-build of the initial minimal native-building system. In order to avoid build-dependency loops during bootstrapping, the build-dependency needs to be reduced using the **DEB_BUILD_PROFILE** environment variable.

See Debian wiki: „[BuildProfileSpec](#)“.

Tipp



If a core package **foo** build depends on a package **bar** with deep build dependency chains but **bar** is only used in the **test** target in **foo**, you can safely mark the **bar** with **<!nocheck>** in the **Build-depends** of **foo** to avoid build loops.

10.6 Compiler hardening

The compiler hardening support spreading for Debian **jessie** (8.0) demands that we pay extra attention to the packaging.

You should read the following references in detail.

- Debian wiki: „[Hardening](#)“
- Debian wiki: „[Hardening Walkthrough](#)“

The **debmake** command adds template comments to the **debian/rules** file as needed for **DEB_BUILD_MAINT_OPTIONS**, **DEB_CFLAGS_MAINT_APPEND**, and **DEB_LDFLAGS_MAINT_APPEND** (see „Kapitel 5“ and **dpkg-buildflags(1)**).

10.7 Reproduzierbares Bauen

Here are some recommendations to attain a reproducible build result.

- Betten Sie keine Zeitstempel, basierend auf der Systemzeit, ein.
- Don't embed the file path of the build environment.
- Use „**dh \$@**“ in the **debian/rules** to access the latest **debhelper** features.
- Export the build environment as „**LC_ALL=C.UTF-8**“ (see „Abschnitt 12.1“).
- Set the timestamp used in the upstream source from the value of the debhelper-provided environment variable **\$SOURCE_DATE_EPOCH**.
- Lesen Sie mehr unter „[Reproduzierbares Bauen](#)“.
 - „[Reproduzierbares Bauen - Wie geht es](#)“.
 - „[Reproduzierbares Bauen - Zeitstempelvorschlag](#)“.

Reproducible builds are important for security and quality assurance. They allow independent verification that no vulnerabilities or backdoors have been introduced during the build process.

Die durch **dpkg-genbuildinfo(1)** erstellte Steuerdatei **source-name_source-version_arch.buildinfo** zeichnet die Bauumgebung auf. Siehe **deb-buildinfo(5)**

10.8 Substvar

The **debian/control** file also defines the package dependency in which the „[variable substitutions mechanism](#)“ (substvar) may be used to free package maintainers from chores of tracking most of the simple package dependency cases. See **deb-substvars(5)**.

The **debmake** command supports the following substvars:

- **\${misc:Depends}** for all binary packages
- **\${misc:Pre-Depends}** for all multiarch packages

- `${shlibs:Depends}` for all binary executable and library packages
- `${python:Depends}` for all Python packages
- `${python3:Depends}` for all Python3 packages
- `${perl:Depends}` for all Perl packages
- `${ruby:Depends}` for all Ruby packages

For the shared library, required libraries found simply by „`objdump -p /path/to/program | grep NEEDED`“ are covered by the **shlib** substar.

For Python and other interpreters, required modules found simply looking for lines with „`import`“, „`use`“, „`require`“, etc., are covered by the corresponding substars.

For other programs which do not deploy their own substars, the **misc** substar covers their dependency.

For POSIX shell programs, there is no easy way to identify the dependency and no substar covers their dependency.

For libraries and modules required via the dynamic loading mechanism including the „[GObject introspection](#)“ mechanism, there is no easy way to identify the dependency and no substar covers their dependency.

10.9 Bibliothekspaket

Die Paketierung von Bibliothekssoftware verlangt von Ihnen deutlich mehr Arbeit als normal. Es folgen ein paar Erinnerungen zur Paketierung von Bibliothekssoftware:

- The library binary package must be named as in „Abschnitt [10.17](#)“.
- Debian ships shared libraries such as `/usr/lib/<triplet>/libfoo-0.1.so.1.0.0` (see „Abschnitt [10.10](#)“).
- Debian encourages using versioned symbols in the shared library (see „Abschnitt [10.16](#)“).
- Debian doesn't ship `*.la` libtool library archive files.
- Debian discourages using and shipping `*.a` static library files.

Before packaging shared library software, see:

- „[Chapter 8 - Shared libraries](#)“ of the „Debian Policy Manual“
- „[10.2 Libraries](#)“ of the „Debian Policy Manual“
- „[6.7.2. Libraries](#)“ of the „Debian Developer's Reference“

For the historic background study, see:

- „[Escaping the Dependency Hell](#)“ [1](#)
 - This encourages having versioned symbols in the shared library.
- „[Debian Library Packaging guide](#)“ [2](#)
 - Please read the discussion thread following [its announcement](#), too.

¹This document was written before the introduction of the **symbols** file.

²The strong preference is to use the SONAME versioned **-dev** package names over the single **-dev** package name in „[Chapter 6. Development \(-DEV\) packages](#)“, which does not seem to be shared by the former ftp-master (Steve Langasek). This document was written before the introduction of the **multiarch** system and the **symbols** file.

10.10 Multiarch

Multiarch support for cross-architecture installation of binary packages (particularly **i386** and **amd64**, but also other combinations) in the **dpkg** and **apt** packages introduced in Debian **wheezy** (7.0, May 2013), demands that we pay extra attention to packaging.

You should read the following references in detail.

- Ubuntu wiki (upstream)
 - „[MultiarchSpec](#)“
- Debian wiki (Debian situation)
 - „[Debian multiarch support](#)“
 - „[Multiarch/Implementation](#)“

The multiarch is enabled by using the **<triplet>** value such as **i386-linux-gnu** and **x86_64-linux-gnu** in the install path of shared libraries as **/usr/lib/<triplet>/**, etc..

- The **<triplet>** value required internally by **debhelper** scripts is implicitly set in themselves. The maintainer doesn't need to worry.
- The **<triplet>** value used in **override_dh_*** target scripts must be explicitly set in the **debian/rules** file by the maintainer. The **<triplet>** value is stored in the **\$(DEB_HOST_MULTIARCH)** variable in the following **debian/rules** snippet example:

```
DEB_HOST_MULTIARCH = $(shell dpkg-architecture -qDEB_HOST_MULTIARCH)
...
override_dh_install:
  mkdir -p package1/lib/$(DEB_HOST_MULTIARCH)
  cp -dR tmp/lib/. package1/lib/$(DEB_HOST_MULTIARCH)
```

Siehe:

- „Abschnitt [9.3](#)“
- „Abschnitt [16.2](#)“
- „Abschnitt [10.12](#)“
- „**dpkg-architecture(1)** manpage“

10.11 Aufteilung eines Debian-Binärpakets

For well behaving build systems, the split of a Debian binary package into small ones can be realized as follows.

- Create binary package entries for all binary packages in the **debian/control** file.
- List all file paths (relative to **debian/tmp**) in the corresponding **debian/binarypackage.install** files.

Bitte prüfen Sie die Beispiele in dieser Anleitung:

- „Abschnitt [14.11](#)“ (Autotools-basiert)
- „Abschnitt [14.12](#)“ (CMake-basiert)

An intuitive and flexible method to create the initial template **debian/control** file defining the split of the Debian binary packages is accommodated with the **-b** option. See „Abschnitt [16.2](#)“.

10.12 Pakettrennungsszenarien und -beispiele

Here are some typical multiarch package split scenarios for the following upstream source examples using the **debmake** command:

- a library source *libfoo-1.0.tar.xz*
- a tool source *bar-1.0.tar.xz* written in a compiled language
- a tool source *baz-1.0.tar.xz* written in an interpreted language

<i>Binärpaket</i>	<i>Typ</i>	<i>Architecture:</i>	<i>Multi-Arch:</i>	<i>Paketinhalt</i>
libfoo1	lib*	any	same	die Laufzeitbibliothek, koinstallierbar
libfoo-dev	dev*	any	same	the shared library header files etc., co-installable
libfoo-tools	bin*	any	foreign	the run-time support programs, not co-installable
libfoo-doc	doc*	all	foreign	the shared library documentation files
<i>bar</i>	bin*	any	foreign	the compiled program files, not co-installable
<i>bar-doc</i>	doc*	all	foreign	the documentation files for the program
<i>baz</i>	script	all	foreign	the interpreted program files

10.13 Multiarch library path

Debian policy requires to comply with the „[Filesystem Hierarchy Standard \(FHS\), version 3.0](#)“, with the exceptions noted in „[File System Structure](#)“.

The most notable exception is the use of */usr/lib/<triplet>/* instead of */usr/lib<qual>/* (e.g., */lib32/* and */lib64/*) to support a multiarch library.

Tabelle 10.2 The multiarch library path options

Classic path	i386 multiarch path	amd64 multiarch path
<i>/lib/</i>	<i>/lib/i386-linux-gnu/</i>	<i>/lib/x86_64-linux-gnu/</i>
<i>/usr/lib/</i>	<i>/usr/lib/i386-linux-gnu/</i>	<i>/usr/lib/x86_64-linux-gnu/</i>

For Autotools based packages under the **debhelper** package (compat>=9), this path setting is automatically taken care by the **dh_auto_configure** command.

For other packages with non-supported build systems, you need to manually adjust the install path as follows.

- If „*/configure*“ is used in the **override_dh_auto_configure** target in **debian/rules**, make sure to replace it with „**dh_auto_configure --**“ while re-targeting the install path from */usr/lib/* to */usr/lib/\$(DEB_HOST_MULTIARCH)/*.
- Replace all occurrences of */usr/lib/* with */usr/lib/*/* in **debian/foo.install** files.

All files installed simultaneously as the multiarch package to the same file path should have exactly the same file content. You must be careful with differences generated by the data byte order and by the compression algorithm.

The shared library files in the default path */usr/lib/* and */usr/lib/<triplet>/* are loaded automatically.

For shared library files in another path, the GCC option **-I** must be set by the **pkg-config** command to make them load properly.

10.14 Multiarch header file path

GCC includes both `/usr/include/` and `/usr/include/<triplet>/` by default on the multiarch Debian system.

If the header file is not in those paths, the GCC option `-I` must be set by the **pkg-config** command to make `"#include <foo.h>"` work properly.

Tabelle 10.3 The multiarch header file path options

Classic path	i386 multiarch path	amd64 multiarch path
<code>/usr/include/</code>	<code>/usr/include/i386-linux-gnu/</code>	<code>/usr/include/x86_64-linux-gnu/</code>
<code>/usr/include/package/</code>	<code>/usr/include/i386-linux-gnu/package/</code>	<code>/usr/include/x86_64-linux-gnu/package/</code>
	<code>/usr/lib/i386-linux-gnu/package/</code>	<code>/usr/lib/x86_64-linux-gnu/package/</code>

The use of the `/usr/lib/<triplet>/package/` path for the library files allows the upstream maintainer to use the same install script for the multiarch system with `/usr/lib/<triplet>` and the biarch system with `/usr/lib<qual>/`. [3](#)

The use of the file path containing *package* enables having more than 2 development libraries simultaneously installed on a system.

10.15 Multiarch *.pc file path

The **pkg-config** program is used to retrieve information about installed libraries in the system. It stores its configuration parameters in the `*.pc` file and is used for setting the `-I` and `-L` options for GCC.

Tabelle 10.4 The *.pc file path options

Classic path	i386 multiarch path	amd64 multiarch path
<code>/usr/lib/pkgconfig/</code>	<code>/usr/lib/i386-linux-gnu/pkgconfig/</code>	<code>/usr/lib/x86_64-linux-gnu/pkgconfig/</code>

10.16 Bibliothekssymbole

The symbols support in **dpkg** introduced in Debian **lenny** (5.0, May 2009) helps us to manage the backward ABI compatibility of the library package with the same package name. The **DEBIAN/symbols** file in the binary package provides the minimal version associated with each symbol.

An oversimplified method for the library packaging is as follows.

- Extract the old **DEBIAN/symbols** file of the immediate previous binary package with the „**dpkg-deb -e**“ command.
 - Alternatively, the **mc** command may be used to extract the **DEBIAN/symbols** file.
- Copy it to the **debian/binarypackage.symbols** file.
 - If this is the first package, use an empty content file instead.
- Build the binary package.
 - If the **dpkg-gensymbols** command warns about some new symbols:
 - ✱ Extract the updated **DEBIAN/symbols** file with the „**dpkg-deb -e**“ command.
 - ✱ Trim the Debian revision such as **-1** in it.
 - ✱ Copy it to the **debian/binarypackage.symbols** file.

³This path is compliant with the FHS. „[Filesystem Hierarchy Standard: /usr/lib : Libraries for programming and packages](#)“ states „Applications may use a single subdirectory under `/usr/lib`. If an application uses a subdirectory, all architecture-dependent data exclusively used by the application must be placed within that subdirectory.“

- ✱ Re-build the binary package.
- If the **dpkg-gensymbols** command does not warn about new symbols:
 - ✱ You are done with the library packaging.

For the details, you should read the following primary references.

- „8.6.3 The symbols system“ of the „Debian Policy Manual“
- „dh_makeshlibs(1) manpage“
- „dpkg-gensymbols(1) manpage“
- „dpkg-shlibdeps(1) manpage“
- „deb-symbols(5) manpage“

Sie sollten auch Folgendes prüfen:

- Debian wiki: „UsingSymbolsFiles“
- Debian wiki: „Projects/ImprovedDpkgShlibdeps“
- Debian kde team: „Working with symbols files“
- „Abschnitt 14.11“
- „Abschnitt 14.12“

Tipp



For C++ libraries and other cases where the tracking of symbols is problematic, follow „8.6.4 The shlibs system“ of the „Debian Policy Manual“, instead. Please make sure to erase the empty **debian/binarypackage.symbols** file generated by the **debmake** command. For this case, the **DEBIAN/shlibs** file is used.

10.17 Library package name

Let's consider that the upstream source tarball of the **libfoo** library is updated from **libfoo-7.0.tar.xz** to **libfoo-8.0.tar.xz** with a new SONAME major version which affects other packages.

The binary library package must be renamed from **libfoo7** to **libfoo8** to keep the **unstable** suite system working for all dependent packages after the upload of the package based on the **libfoo-8.0.tar.xz**.

Warnung



If the binary library package isn't renamed, many dependent packages in the **unstable** suite become broken just after the library upload even if a binNMU upload is requested. The binNMU may not happen immediately after the upload due to several reasons.

The **-dev** package must follow one of the following naming rules:

- Use the **unversioned -dev** package name: **libfoo-dev**
 - This is the typical one for leaf library packages.
 - Only one version of the library source package is allowed in the archive.
 - ✱ The associated library package needs to be renamed from **libfoo7** to **libfoo8** to prevent dependency breakage in the **unstable** suite during the library transition.

- This approach should be used if the simple binNMU resolves the library dependency quickly for all affected packages. (ABI change by dropping the deprecated API while keeping the active API unchanged.)
- This approach may still be a good idea if manual code updates, etc. can be coordinated and manageable within limited packages. (API change)
- Use the **versioned -dev** package names: **libfoo7-dev** and **libfoo8-dev**
 - This is typical for many major library packages.
 - Two versions of the library source packages are allowed simultaneously in the archive.
 - * Make all dependent packages depend on **libfoo-dev**.
 - * Make both **libfoo7-dev** and **libfoo8-dev** provide **libfoo-dev**.
 - * The source package needs to be renamed as **libfoo7-7.0.tar.xz** and **libfoo8-8.0.tar.xz** respectively from **libfoo-?.0.tar.xz**.
 - * The package specific install file path including **libfoo7** and **libfoo8** respectively for header files etc. needs to be chosen to make them co-installable.
 - Do not use this heavy handed approach, if possible.
 - This approach should be used if the update of multiple dependent packages require manual code updates, etc. (API change) Otherwise, the affected packages become RC buggy with FTBFS (Fails To Build From Source).

Tipp

If the data encoding scheme changes (e.g., latin1 to utf-8), the same care as the API change needs to be taken.

Siehe „Abschnitt 10.9“.

10.18 Bibliotheksübergänge

When you package a new library package version which affects other packages, you must file a transition bug report against the **release.debian.org** pseudo package using the **reportbug** command with the **ben** file and wait for the approval for its upload from the **Release Team**.

Release team has the „**transition tracker**“. See „**Transitions**“.

Achtung

Please make sure to rename binary packages as in „Abschnitt 10.17“.

10.19 binNMU-sicher

A „**binNMU**“ is a binary-only non-maintainer upload performed for library transitions etc. In a binNMU upload, only the „**Architecture: any**“ packages are rebuilt with a suffixed version number (e.g. version 2.3.4-3 will become 2.3.4-3+b1). The „**Architecture: all**“ packages are not built.

The dependency defined in the **debian/control** file among binary packages from the same source package should be safe for the binNMU. This needs attention if there are both „**Architecture: any**“ and „**Architecture: all**“ packages involved in it.

- „**Architecture: any**“ package: depends on „**Architecture: any**“ *foo* package

- **Depends:** *foo* (= `${binary:Version}`)
- „**Architecture: any**“ package: depends on „**Architecture: all**“ *bar* package
 - **Depends:** *bar* (= `${source:Version}`)
- „**Architecture: all**“ package: depends on „**Architecture: any**“ *baz* package
 - **Depends:** *baz* (`>= ${source:Version}`), *baz* (`<< ${source:Version}.0~`)

10.20 Fehlersuchinformationen

The Debian package is built with the debugging information but packaged into the binary package after stripping the debugging information as required by „[Chapter 10 - Files](#)“ of the „Debian Policy Manual“.

Siehe

- „[6.7.9. Best practices for debug packages](#)“ of the „Debian Developer's Reference“.
- „[18.2 Debugging Information in Separate Files](#)“ of the „Debugging with gdb“
- „**dh_strip**(1) manpage“
- „**strip**(1) manpage“
- „**readelf**(1) manpage“
- „**objcopy**(1) manpage“
- Debian wiki: „[DebugPackage](#)“
- Debian wiki: „[AutomaticDebugPackages](#)“
- Debian debian-devel post: „[Status on automatic debug packages](#)“ (2015-08-15)

10.21 -dbgsym package

The debugging information is automatically packaged separately as the debug package using the **dh_strip** command with its default behavior. The name of such a debug package normally has the **-dbgsym** suffix.

- The **debian/rules** file shouldn't explicitly contain **dh_strip**.
- Set the **Build-Depends** to **debhelper-compat (>=13)** while removing **Build-Depends** to **debhelper** in **debian/control**.

10.22 debconf

The **debconf** package enables us to configure packages during their installation in 2 main ways:

- non-interactively from the **debian-installer** pre-seeding.
- interactively from the menu interface (**dialog**, **gnome**, **kde**, ...)
- the package installation: invoked by the **dpkg** command
- the installed package: invoked by the **dpkg-reconfigure** command

All user interactions for the package installation must be handled by this **debconf** system using the following files.

- **debian/binarypackage.config**
 - This is the **debconf config** script used for asking any questions necessary to configure the package.

- **debian/binarypackage.template**

- This is the **debconf templates** file used for asking any questions necessary to configure the package.

These **debconf** files are called by package configuration scripts in the binary Debian package

- **DEBIAN/binarypackage.preinst**
- **DEBIAN/binarypackage.prerm**
- **DEBIAN/binarypackage.postinst**
- **DEBIAN/binarypackage.postrm**

See **dh_installdebconf(1)**, **debconf(7)**, **debconf-devel(7)** and „[3.9.1 Prompting in maintainer scripts](#)“ in the „Debian Policy Manual“.

Kapitel 11

Packaging with git

Up to „Kapitel 10“, we focused on packaging operations without using [Git](#) or any other [VCS](#). These traditional packaging operations were based on the tarball released by the upstream as mentioned in „Abschnitt 10.1“.

Currently, the **git(1)** command is the de-facto platform for the VCS tool and is the essential part of both upstream development and Debian packaging activities. (See Debian wiki „[Debian git packaging maintainer branch formats and workflows](#)“ for existing VCS workflows.)

Anmerkung



Since the non-native Debian source package uses „**diff -u**“ as its backend technology for the maintainer modification, it can't represent modification involving symlink, file permissions, nor binary data ([March 2022 discussion on debian-devel@l.d.o](#)). Please avoid making such maintainer modifications even though these can be recorded in the Git repository.

Since VCS workflows are complicated topic and there are many practice styles, I only touch on some key points with minimal information, here.

[Salsa](#) is the remote Git repository service with associated tools. It offers the collaboration platform for Debian packaging activities using a custom [GitLab](#) application instance. See:

- „Abschnitt [11.1](#)“
- „Abschnitt [11.2](#)“
- „Abschnitt [11.3](#)“

There are 2 styles of branch names for the Git repository used for the packaging. See „Abschnitt [11.4](#)“. There are 2 main usage styles for the Git repository for the packaging. See:

- „Abschnitt [11.5](#)“
- „Abschnitt [11.13](#)“

There are 2 notable Debian packaging tools for the Git repository for the packaging.

- **gbp(1)** and its subcommands:
 - This is a tool designed to work mainly with „Abschnitt [11.5](#)“.
 - See „Abschnitt [11.9](#)“.
- **dgit(1)** and its subcommands:
 - This is a tool designed to work mainly with „Abschnitt [11.13](#)“.
 - This contains a tool to upload Debian packages using the **dgit** server.
 - See „Abschnitt [11.14](#)“.

11.1 Salsa repository

It is highly desirable to host Debian source code package on [Salsa](#). Over 90% of all Debian source code packages are hosted on [Salsa](#). ¹

The exact VCS repository hosting an existing Debian source code package can be identified by a metadata field `Vcs - *` which can be viewed with the `apt - cache showsrc <package - name>` command.

11.2 Salsa account setup

After signing up for an account on [Salsa](#), make sure that the following pages have the same e-mail address and GPG keys you have configured to be used with Debian, as well as your SSH key:

- <https://salsa.debian.org/-/profile/emails>
- https://salsa.debian.org/-/user_settings/gpg_keys
- https://salsa.debian.org/-/user_settings/ssh_keys

11.3 Salsa CI service

[Salsa](#) runs [Salsa CI](#) service as an instance of [GitLab CI](#) for „Abschnitt 10.4“.

For every „**git push**“ instances, tests which mimic tests run on the official Debian package service can be run by setting [Salsa CI](#) configuration file „Abschnitt 6.13“ as:

```
---
include:
  - https://salsa.debian.org/salsa-ci-team/pipeline/raw/master/recipes/debian.yml

# Customizations here
```

11.4 Branch names

The Git repository for the Debian packaging should have at least 2 branches:

- **debian-branch** to hold the current Debian packaging head.
 - old style: **master** (or **debian**, **main**, ...)
 - [DEP-14](#) style: **debian/latest**
- **upstream-branch** to hold the upstream releases in the imported form.
 - old style: **upstream**
 - [DEP-14](#) style: **upstream/latest**

In this tutorial, old style branch names are used in examples for simplicity.

Anmerkung



This **upstream-branch** may need to be created using the tarball released by the upstream independent of the upstream Git repository since it tends to contain automatically generated files.

The upstream Git repository content can co-exist in the local Git repository used for the Debian packaging by adding its copy. E.g.:

```
[debhello] $ git remote add upstreamvcs <url-upstream-git-repo>
[debhello] $ git fetch upstreamvcs master:upstream-master
```

This allows easy cherry-picking from the upstream Git repository for bug fixes.

¹Use of `git.debian.org` or `alioth.debian.org` are deprecated now.

11.5 Patch unapplied Git repository

The patch unapplied Git repository can be summarized as:

- This seems to be the traditional practice as of 2024.
- The source tree matches extracted contents by „**dpkg-source -x --skip-patches**“ of the Debian source package.
 - The upstream source is recorded in the Git repository without changes.
 - The maintainer modified contents are confined within the **debian/*** directory.
 - Maintainer changes to the upstream source are recorded in **debian/patches/*** files for the Debian source format „**3.0 (quilt)**“.
- This repository style is useful for all variants of traditional workflows and **gbp** based workflow:
 - „Abschnitt 5.7“ (no patch)
 - „Abschnitt 5.10“
 - ✱ **debian/patches/*** files can also be generated using „**git format-patch**“, „**git diff**“, or „**gitk**“ from **git** commits in the through-away maintainer modification branch or from the upstream unreleased commits.
 - „Abschnitt 5.11“ including the last „**dquilt pop -a**“ step
 - „Abschnitt 11.6“
- Use helper scripts such as **dquilt(1)** and **gbp-pq(1)** to manage data in **debian/patches/*** files.
 - Add **.pc** line to the **~/.gitignore** file if **dquilt** is used.
- Use „**dpkg-source -b**“ to build the Debian source package.
- Use **dput(1)** to upload the Debian source package.

11.6 Patch by „gbp-pq“ approach

For „Abschnitt 11.5“, you can generate **debian/patches/*** files using the **gbp-pq(1)** command from **git** commits in the through-away **patch-queue** branch.

Unlike **dquilt** which offers similar functionality as seen „Abschnitt 5.11“ and „Abschnitt 9.5“, **gbp-pq** doesn't use **.pc/*** files to track patch state, but instead **gbp-pq** utilizes temporary branches in git.

11.7 Manage patch queue with gbp-pq

You can add, drop, and refresh **debian/patches/*** files with **gbp-pq** to manage patch queue.

If the package is managed in „Abschnitt 11.5“ using the **git-buildpackage** package, you can revise the upstream source to fix bug as the maintainer and release a new Debian revision using **gbp pq**.

- **Add** a new patch recording the upstream source modification on the file *buggy_file* as:

```
[debhello] $ git checkout master
[debhello] $ gbp pq import
gbp:info: ... imported on 'patch-queue/master'
[debhello] $ vim buggy_file
...
[debhello] $ git add buggy_file
[debhello] $ git commit
[debhello] $ gbp pq export
gbp:info: On 'patch-queue/master', switching to 'master'
gbp:info: Generating patches from git (master..patch-queue/master)
[debhello] $ git add debian/patches/*
[debhello] $ dch -i
[debhello] $ git commit -a -m "Closes: #<bug_number>"
[debhello] $ git tag debian/<version>-<rev>
```

- **Drop** (== disable) an existing patch
 - Comment out pertinent line in **debian/patches/series**
 - Erase the patch itself (optional)
- **Refresh** **debian/patches/*** files to make „**dpkg-source -b**“ work as expected after updating a Debian package to the new upstream release.

```
[debhello] $ git checkout master
[debhello] $ gbp pq --force import # ensure patch-queue/master branch
gbp:info: ... imported on 'patch-queue/master'
[debhello] $ git checkout master
[debhello] $ gbp import-orig --pristine-tar --uscan
...
gbp:info: Successfully imported version ?..? of ../packagename_?..?.orig. ↵
tar.xz
[debhello] $ gbp pq rebase
... resolve conflicts and commit to patch-queue/master branch
[debhello] $ gbp pq export
gbp:info: On 'patch-queue/master', switching to 'master'
gbp:info: Generating patches from git (master..patch-queue/master)
[debhello] $ git add debian/patches
[debhello] $ git commit -m "Update patches"
[debhello] $ dch -v <newversion>-1
[debhello] $ git commit -a -m "release <newversion>-1"
[debhello] $ git tag debian/<newversion>-1
```

11.8 gbp import-dscs --debsnap

For Debian source packages named „<source-package>“ recorded in the snapshot.debian.org archive, an initial git repository managed in „Abschnitt 11.5“ with all of the Debian version history can be generated as follows.

```
[debhello] $ gbp import-dscs --debsnap --pristine-tar <source-package>
```

11.9 Note on gbp

The **gbp** command is provided by the **git-buildpackage** package.

- This command is designed to manage contents of „Abschnitt 11.5“ efficiently.
- Use „**gbp import-orig**“ to import the new upstream tar to the git repository.
 - The „**--pristine-tar**“ option for the „**git import-orig**“ command enables storing the upstream tarball in the same git repository.
 - The „**--uscan**“ option as the last argument of the „**gbp import-orig**“ command enables downloading and committing the new upstream tarball into the git repository.
- Use „**gbp import-dsc**“ to import the previous Debian source package to the git repository.
- Use „**gbp dch**“ to generate the Debian changelog from the git commit messages.
- Use „**gbp buildpackage**“ to build the Debian binary package from the git repository.
 - The **sbuild** package can be used as its clean chroot build backend either by configuration or adding „**--git-builder=sbuild -A -s --source-only-changes -v -d unstable**“
- Use „**gbp pull**“ to update the **debian**, **upstream** and **pristine-tar** branches safely from the remote repository.
- Use „**gbp pq**“ to manage quilt patches without using **dquilt** command.

- Use „**gbp clone** *REPOSITORY_URL*“ to clone and set up tracking branches for **debian**, **upstream** and **pristine-tar**.

Package history management with the **git-buildpackage** package is becoming the standard practice for many Debian maintainers. See more at:

- „[Building Debian Packages with git-buildpackage](#)“
- „[4 tips to maintain a “3.0 \(quilt\)” Debian source package in a VCS](#)“
- The **systemd** packaging practice documentation on „[Building from source](#)“
- The workflow mentioned in **dggit-maint-gbp**(7) which enables to use this **gbp** with **dggit**

11.10 The Git repository browser

The **gitk** command in the **gitk** package displays changes in a repository or a selected set of commits. This includes visualizing the commit graph, showing information related to each commit, and the files in the trees of each revision.

This **gitk** command also provides very intuitive UI to many cumbersome operations of the „**git**“ command such as „**git checkout** ...“, „**git reset*** ...“, „**git diff** ...“, etc..

11.11 Git commit history organization

When your local Git commit history becomes intertwined, you need to organize it before pushing it out to the public.

The most simple organization process is to squash all changes to a single commit using „**git rebase -i**“ interactively.

But this may create a huge commit with files such as auto-generated files not intended to be committed. You can **drop** such files in the commit using „**git rm** *some_file*“ and „**git commit --amend**“. This may be quite cumbersome.

This cumbersome **drop** process can be eased by using the „**git-ime**“ command in the **imdiff** package. It automatically splits a single commit with many files into multiple commits involving only a single file changes. Now you can drop such files using „**git rebase -i**“ interactively.

Tipp



The „**git-ime**“ operating on a single file change commit splits it into multiple commits of line changes using **imdiff** interactively. Invoking this with the **--auto** option will automate this split commit operation. See **git-ime**(1) and **imdiff**(1).

11.12 Quasi-native Debian packaging

The **quasi-native** packaging scheme packages a source without the real upstream tarball using the **non-native** package format.

Tipp



Some people promote this **quasi-native** packaging scheme even for programs written only for Debian since it helps to ease communication with the downstream distros such as Ubuntu for bug fixes etc.

This **quasi-native** packaging scheme involves 2 preparation steps:

- Organize its source tree almost like **native** Debian package (see „Abschnitt 6.4“) with **debian/*** files with a few exceptions:
 - Make **debian/source/format** to contain „**3.0 (quilt)**“ instead of „**3.0 (native)**“ .
 - Make **debian/changelog** to contain *version-revision* instead of *version* .
- Generate missing upstream tarball preferably without **debian/*** files.
 - For Debian source format „**3.0 (quilt)**“, removal of files under **debian/** directory is an optional action.

The rest is the same as the **non-native** packaging workflow as written in „Abschnitt 6.1“.

Although this can be done in many ways, you can use the Git repository and „**git deborig**“ as:

```
[~] $ cd /path/to/debhello
[debhello] $ dch -r
... set its <version>-<revision>, e.g., 1.0-1
[debhello] $ git tag -s debian/1.0-1
[debhello] $ git rm -rf debian
[debhello] $ git tag -s upstream/1.0
[debhello] $ git commit -m upstream/1.0
[debhello] $ git reset --hard HEAD^
[debhello] $ git deborig
[debhello] $ sbuild
```

11.13 Patch applied Git repository

Anmerkung



The focus of this introductory tutorial „[Guide for Debian Maintainers](#)“ isn't the patch applied Git repository which is rather a new trend initiated by the proponent of the **dggit** command. So minimal explanation is given here.

The patch applied Git repository can be summarized as:

- The source tree matches extracted contents by „**dpkg-source -x**“ of the Debian source package.
 - The source tree is buildable and the same as what NMU maintainers see.
 - The source is recorded in the Git repository with maintainer changes including the **debian/** directory.
 - Maintainer changes to the upstream source are also recorded in **debian/patches/*** files for the Debian source format „**3.0 (quilt)**“.

11.14 Note on dggit

The **dggit** command is provided by the **dggit** package.

- This command enables to access the Debian package repository as if it were a **git** remote repository.
- This command offers tools to manage Debian packaging activities mainly using „Abschnitt 11.13“.
 - No more convoluted operations to manage patch files in the **debian/patches** directory.
- Use „**dggit build-source**“ or „**dggit sbuild**“ to build the Debian source-only or source+binary package.

- Use „**dggit push-source**“ or „**dggit push-build**“ for uploading the Debian source-only or source+binary package via the **dggit** server.
- Use **git-deborig**(1) to produce Debian *package.orig.tar.xz* from the upstream version in **debian/changelog**.

Tipp



The **dggit** server is browsable at <https://browse.dggit.debian.org/> site.

Anmerkung



In order to keep the working tree **dggit**-compatible, delete **debian/source/local-options** and **debian/source/local-patch-header** if they exist.

Hints for workflow styles:

- **dggit-maint-merge**(7) workflow.
 - Use this for the Debian non-native package without granular topic patches recorded in the Debian source package.
 - ✱ Good enough for packages only with trivial modifications to the upstream.
 - ✱ Only choice for packages with intertwined modification histories to the upstream.
 - Add **auto-commit** and **single-debian-patch** lines in the **debian/source/options** file
 - ✱ No granular topic patches recorded inside of the Debian source package.
 - Use „**git checkout upstream; git pull**“ to pull the new upstream commit and use „**git checkout master ; git merge <new-version-tag>**“ to merge it to the **master** branch.
 - See „Abschnitt 5.12“ for example.
- **dggit-maint-debrebase**(7) workflow.
 - Use this for the Debian non-native package with granular topic patches recorded in the Debian source package.
 - Use the **git-debrebase**(1) command to maintain series of Debian changes to upstream source.
- **dggit-maint-native**(7) workflow,
 - Use this for the Debian native package in the Debian Git repository. (No maintainer changes)
- **dggit-maint-gbp**(7) workflow
 - Use this for the Debian non-native package using source format „**3.0 (quilt)**“ with its Debian Git repository which had been using **gbp-buildpackage**(1) with „Abschnitt 11.5“.

This author likes this new **dggit** command and just started to use it with **dggit-maint-merge**(7) and **dggit-maint-native**(7) workflows. Thus, topics around **dggit** are beyond this tutorial document to cover in depth. Please start reading the latest relevant manpages and upstream resources:

- „[dggit: use the Debian archive as a git remote \(2015\)](#)“
- „[tag2upload \(2023\)](#)“

Kapitel 12

Tipps

Please also read insightful pages linked from „[Notes on Debian](#)“ by Russ Allbery (long time Debian developer) which have best practices for advanced packaging topics.

12.1 Build under UTF-8

The default locale of the build environment is **C**.

Some programs such as the **read** function of Python3 change their behavior depending on the locale.

Adding the following code to the **debian/rules** file ensures building the program under the **C.UTF-8** locale.

```
LC_ALL := C.UTF-8
export LC_ALL
```

12.2 UTF-8 conversion

If upstream documents are encoded in old encoding schemes, converting them to **UTF-8** is a good idea.

Use the **iconv** command in the **libc-bin** package to convert the encoding of plain text files.

```
[debhello] $ iconv -f latin1 -t utf8 foo_in.txt > foo_out.txt
```

Use **w3m(1)** to convert from HTML files to UTF-8 plain text files. When you do this, make sure to execute it under UTF-8 locale.

```
[debhello] $ LC_ALL=C.UTF-8 w3m -o display_charset=UTF-8 \
    -cols 70 -dump -no-graph -T text/html \
    < foo_in.html > foo_out.txt
```

Run these scripts in the **override_dh_*** target of the **debian/rules** file.

12.3 Hints for Debugging

When you face build problems or core dumps of generated binary programs, you need to resolve them yourself. That's **debug**.

This is too deep a topic to describe here. So, let me just list few pointers and hints for some typical debug tools.

- Wikipedia: „[core dump](#)“
 - „**man core**“
 - Update the „**/etc/security/limits.conf**“ file to include the following:

```
* soft core unlimited
```

- „**ulimit -c unlimited**“ in **~/.bashrc**
- „**ulimit -a**“ to check
- Press **Ctrl-** or „**kill -ABRT 'PID'**“ to make a core dump file
- **gdb** - The GNU Debugger
 - „**info gdb**“
 - „Debugging with GDB“ in **/usr/share/doc/gdb-doc/html/gdb/index.html**
- **strace** - Trace system calls and signals
 - Use **strace-graph** script found in **/usr/share/doc/strace/examples/** to make a nice tree view
 - „**man strace**“
- **ltrace** - Trace library calls
 - „**man ltrace**“
- „**sh -n script.sh**“ - Syntax check of a Shell script
- „**sh -x script.sh**“ - Trace a Shell script
- „**python3 -m py_compile script.py**“ - Syntax check of a Python script
- „**python3 -mtrace --trace script.py**“ - Trace a Python script
- „**perl -I ../libpath -c script.pl**“ - Syntax check of a Perl script
- „**perl -d:Trace script.pl**“ - Trace a Perl script
 - Install the **libterm-readline-gnu-perl** package or its equivalent to add input line editing capability with history support.
- **lsuf** - List open files by processes
 - „**man lsuf**“

Tipp



Der Befehl **script** zeichnet Konsolenausgaben auf.

Tipp



Die Befehle **screen** und **tmux** bieten Ihnen im Zusammenspiel mit **ssh** eine sichere und robuste Verbindung zu fernen Terminals.

Tipp



A Python- and Shell-like REPL (=READ + EVAL + PRINT + LOOP) environment for Perl is offered by the **reply** command from the **libreply-perl** (new) package and the **re.pl** command from the **libdevel-repl-perl** (old) package.

Tipp

The **rlwrap** and **rlfe** commands add input line editing capability with history support to any interactive commands. E.g. „**rlwrap dash -i**“.

Kapitel 13

Tool usages

Here are some notable tools around Debian packaging.

Anmerkung



The descriptions in this section are intentionally brief. Prospective maintainers are strongly encouraged to search for and read all relevant documentation associated with these commands.

Anmerkung



Examples here use the **gz**-compression. The **xz**-compression may be used instead.

13.1 debdiff

Sie können die Dateiinhalte in zwei Quellpaketen mit dem Befehl **debdiff** vergleichen.

```
[base_dir] $ debdiff old-package.dsc new-package.dsc
```

Sie können auch Dateilisten in zwei Gruppen von Debian-Binärpaketen mit dem Befehl **debdiff** vergleichen.

```
[base_dir] $ debdiff old-package.changes new-package.changes
```

Diese sind nützlich, um herauszufinden, was sich in Quellpaketen geändert hat und zu prüfen, ob unbeabsichtigte Änderungen beim Aktualisieren der Binärpakete erfolgten, wie beispielsweise falsch angeordnete oder entfernte Dateien.

Debian now enforces the source-only upload when developing packages. So there may be 2 different ***.changes** files:

- *package_version-revision_source.changes* for the normal source-only upload
- *package_version-revision_arch.changes* for the source+binary upload

13.2 dget

Mit dem Befehl **dget** können Sie eine Gruppe von Dateien für das Debian-Quellpaket herunterladen.

```
[base_dir] $ dget https://www.example.org/path/to/package_version-rev.dsc
```

13.3 mk-origtargz

You can make the upstream tarball `../foo-newversion.tar.[xg]z` accessible from the Debian source tree as `../foo_newversion.orig.tar.[xg]z`. This command is useful for renaming and symlinking the upstream tarball to the expected Debian naming convention.

13.4 origtargz

You can fetch the pre-existing orig tarball of a Debian package from various sources, and unpack it with **origtargz** command.

This is basically for **-2**, **-3**, ... revisions.

Anmerkung



When the upstream tarball is missing, **debmake** automatically produces a required tarball. This is a convenient feature and good enough for making a private Debian package. But when making a Debian package for the official Debian repository, you must use exactly the same upstream tarball as the **-1** revision. For such case, **origtargz** should be used.

13.5 git deborig

If the upstream project is hosted in a Git repository without an official tarball release, you can generate its orig tarball from the **git** repository for use by the Debian source package. Execute „git deborig“ from the root of the checked-out source tree.

This is basically for **-1** revisions.

13.6 dpkg-source -b

The „**dpkg-source -b**“ command packs the upstream source tree into the Debian source package.

It expects a series of patches in the **debian/patches/** directory and their application sequence in **debian/patches/series**.

It is compatible with **dquilt** (see „Abschnitt 4.4“) operations and understands the patch application status from the existence of **.pc/applied-patches**.

The **dpkg-buildpackage** command invokes „**dpkg-source -b**“.

13.7 dpkg-source -x

The „**dpkg-source -x**“ command extracts the source tree and applies the patches in the **debian/patches/** directory using the sequence specified in **debian/patches/series** to the upstream source tree. It also adds **.pc/applied-patches**. (See „Abschnitt 11.13“.)

The „**dpkg-source -x --skip-patches**“ command extracts source tree only. It doesn't add **.pc/applied-patches**. (See „Abschnitt 11.5“.)

Both extracted source trees are ready for building Debian binary packages with **dpkg-buildpackage**, **dbuild**, **sbuilt**, etc..

13.8 debc

Sie sollten erstellte Pakete mit dem Befehl **debc** lokal installieren, um sie zu testen.

```
[base_dir] $ debc package_version-rev_arch.changes
```

13.9 piuparts

You should install generated packages with the **piuparts** command to test it automatically.

```
[base_dir] $ sudo piuparts package_version-rev_arch.changes
```

Anmerkung



This is a very slow process with remote APT package repository access.

13.10 bts

After uploading the package, you will receive bug reports. It is an important duty of a package maintainer to manage these bugs properly, as described in „[5.8. Handling bugs](#)“ of the „Debian Developer’s Reference“.

The **bts** command is a handy tool to manage bugs on the „[Debian Bug Tracking System](#)“.

```
[~] $ bts severity 123123 wishlist , tags -1 pending
```

13.11 dpkg-depcheck

You can use **dpkg-depcheck(1)** to obtain a good first approximation to the **Build-Depends** line needed by a Debian package.

```
[foo-1.0] $ dpkg-depcheck -b debian/rules build
```

Kapitel 14

Weitere Beispiele

There is an old Latin saying: „**fabricando fit faber**“ („practice makes perfect“).

Es wird nachdrücklich empfohlen, mit einfachen Paketen zu üben und mit allen Schritten der Debian-Paketierung zu experimentieren. Dieses Kapitel stellt Ihnen viele Fälle von Originalautoren zur Übung bereit.

This should also serve as introductory examples for many programming topics.

- Programming in the POSIX shell, Python3, and C.
- Methode, um ein Desktop-GUI-Programmstarter mit Icon-Graphiken zu erstellen.
- Conversion of a command from [CLI](#) to [GUI](#).
- Conversion of a program to use **gettext** for [internationalization and localization](#): POSIX shell and C sources.
- Overview of many build systems: Makefile, Python, Autotools, and CMake.

Bitte beachten Sie, dass Debian ein paar Dinge sehr Ernst nimmt:

- Freie Software (auch als Libre Software bekannt)
- Stabilität und Sicherheit des Betriebssystems
- Universelles Betriebssystem mittels:
 - freier Wahl der Quellen der Originalautoren
 - freier Wahl der CPU-Architektur und
 - freier Wahl der Sprachen für Oberflächen.

Das in „Kapitel 5“ dargestellte Beispiel ist die Voraussetzung für dieses Kapitel.

Some details are intentionally left vague in the following sections. Please try to read the pertinent documentation and practice yourself to find them out.

Tipp



The best source of a packaging example is the current Debian archive itself. Please use the „[Debian Code Search](#)“ service to find pertinent examples.

14.1 Cherry-pick templates

Here is an example of creating a simple Debian package from a zero-content source in an empty directory.

This is a good way to obtain all the template files without cluttering the upstream source tree you are working on.

Let's assume this empty directory to be **debhello-0.1**.

```
[base_dir] $ mkdir debhello-0.1
[base_dir] $ tree
.
+-- debhello-0.1

2 directories, 0 files
```

Let's generate the maximum amount of template files.

Let's also use the „**-p debhello -t -x3 -u 0.1 -r 1**“ options to create the missing upstream tarball with optional **-x3**, and **-t** options.

```
[base_dir] $ cd debhello-0.1
[debhello-0.1] $ debmake -p debhello -x3 -t -T -u 0.1 -r 1
I: debmake (version: 5.1.2)
...
```

Lassen Sie uns die erstellten Vorlagendateien anschauen.

```
[debhello-0.1] $ cd ..
[base_dir] $ tree
.
+-- debhello-0.1
|   +-- debian
|       +-- README.Debian
|       +-- README.source
|       +-- bug-control.ex
|       +-- bug-presubj.ex
|       +-- bug-script.ex
|       +-- changelog
|       +-- clean
|       +-- conffiles.ex
|       +-- control
|       +-- copyright
|       +-- cron.d.ex
|       +-- cron.daily.ex
|       +-- cron.hourly.ex
|       +-- cron.monthly.ex
|       +-- cron.weekly.ex
|       +-- default.ex
|       +-- dirs
|       +-- doc-base.ex
|       +-- docs
|       +-- emacs-en-install.ex
|       +-- emacs-en-remove.ex
|       +-- emacs-en-startup.ex
|       +-- examples
|       +-- gbp.conf
|       +-- info.ex
|       +-- install
|       +-- links
|       +-- lintian-overrides.ex
|       +-- maintscript.ex
|       +-- manpage.1.ex
|       +-- manpage.asciidoc.ex
|       +-- manpage.md.ex
|       +-- manpage.sgml.ex
|       +-- manpage.xml.ex
|       +-- manpages
|       +-- patches
|       |   +-- series
|       +-- postinst.ex
|       +-- postrm.ex
|       +-- preinst.ex
|       +-- prerm.ex
```

```
|      +-- rules
|      +-- salsa-ci.yml
|      +-- service.ex
|      +-- source
|      |   +-- format
|      |   +-- lintian-overrides.ex
|      |   +-- options.ex
|      |   +-- patch-header.ex
|      +-- tests
|      |   +-- control
|      +-- tmpfile.ex
|      +-- upstream
|      |   +-- metadata
|      +-- watch
+-- debhello-0.1.tar.xz
+-- debhello_0.1.orig.tar.xz -> debhello-0.1.tar.xz

7 directories, 53 files
```

Now you can copy any of these generated template files in the *debhello-0.1/debian/* directory to your package as needed while renaming them as needed.

14.2 Kein Makefile (Shell, CLI)

Here is an example of creating a simple Debian package from a POSIX shell CLI program without its build system.

Let's assume this upstream tarball to be **debhello-0.2.tar.xz**.

This type of source has no automated means and files must be installed manually.

Zum Beispiel:

```
[base_dir] $ tar -xzmf debhello-0.2.tar.xz
[base_dir] $ cd debhello-0.2
[debhello-0.2] $ sudo cp scripts/hello /bin/hello
...
```

Let's get this source as tar file from a remote site and make it the Debian package.

Download debhello-0.2.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-0.2.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-0.2.tar.xz
[base_dir] $ tree
.
+-- debhello-0.2
|   +-- README.md
|   +-- data
|   |   +-- hello.desktop
|   |   +-- hello.png
|   +-- man
|   |   +-- hello.1
|   +-- scripts
|       +-- hello
+-- debhello-0.2.tar.xz

5 directories, 6 files
```

Here, the POSIX shell script **hello** is a very simple one.

hello (v=0.2)

```
[base_dir] $ cat debhello-0.2/scripts/hello
#!/bin/sh -e
echo "Hello from the shell!"
echo ""
```

```
echo -n "Type Enter to exit this program: "
read X
```

Here, **hello.desktop** supports the „[Desktop Entry Specification](#)“.
hello.desktop (v=0.2)

```
[base_dir] $ cat debhello-0.2/data/hello.desktop
[Desktop Entry]
Name=Hello
Name[fr]=Bonjour
Comment=Greetings
Comment[fr]=Salutations
Type=Application
Keywords=hello
Exec=hello
Terminal=true
Icon=hello.png
Categories=Utility;
```

Here, **hello.png** is the icon graphics file.

Let's package this with the **debmake** command. Here, the **-b':sh'** option is used to specify that the generated binary package is a shell script.

```
[base_dir] $ cd debhello-0.2
[debhello-0.2] $ debmake -b':sh' -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-0.2] $ cd ..
I: Non-native Debian package pkg="debhello", ver="0.2", rev="1" method="dir_d...
I: already in the package-version form: "debhello-0.2"
I: [base_dir] $ ln -sf debhello-0.2.tar.xz debhello_0.2.orig.tar.xz
I: [base_dir] $ cd debhello-0.2
I: parsing option -b ":sh"
I: binary package=debhello Type=script / Arch=all M-A=foreign
I: build_type = Unknown
I: ext_type = 1                      1 files
I: ext_type = desktop                1 files
I: ext_type = md                     1 files
I: creating debian/* files with "-x 1" option
I: [debhello-0.2] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
I: creating debian/rules from extra0_rules
I: creating debian/source/format from extra0source_format
...
```

Let's inspect notable template files generated.

The source tree after the basic debmake execution. (v=0.2)

```
[debhello-0.2] $ cd ..
[base_dir] $ tree
.
+-- debhello-0.2
|   +-- README.md
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- debian
|       |   +-- README.Debian
|       |   +-- README.source
|       |   +-- changelog
|       |   +-- clean
|       |   +-- control
```



```

| | +-- copyright
| | +-- dirs
| | +-- docs
| | +-- examples
| | +-- gbp.conf
| | +-- install
| | +-- links
| | +-- manpages
| | +-- patches
| | | +-- series
| | +-- rules
| | +-- salsa-ci.yml
| | +-- source
| | | +-- format
| | +-- tests
| | | +-- control
| | +-- upstream
| | | +-- metadata
| | +-- watch
| +-- man
| | +-- hello.1
| +-- scripts
| | +-- hello
+-- debhello-0.2.tar.xz
+-- debhello_0.2.orig.tar.xz -> debhello-0.2.tar.xz

10 directories, 27 files

```

debian/rules (Vorlagendatei, v=0.2):

```

[base_dir] $ cd debhello-0.2
[debhello-0.2] $ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
# See debhelper(7) (un-comment to enable)
# This is an autogenerated template for debian/rules.
#
# Output every command that modifies files on the build system.
#export DH_VERBOSE = 1
#
# Copy some variable definitions from pkg-info.mk and vendor.mk
# under /usr/share/dpkg/ to here if they are useful.
#
# These are rarely used code. (START)
#
# The following include for *.mk magically sets miscellaneous
# variables while honoring existing values of pertinent
# environment variables:
#
# Architecture-related variables such as DEB_TARGET_MULTIARCH:
#include /usr/share/dpkg/architecture.mk
# Vendor-related variables such as DEB_VENDOR:
#include /usr/share/dpkg/vendor.mk
# Package-related variables such as DEB_DISTRIBUTION
#include /usr/share/dpkg/pkg-info.mk
#
# You may alternatively set them using a simple script such as:
# DEB_VENDOR ?= $(shell dpkg-vendor --query Vendor)
#
# These are rarely used code. (END)
#

### main packaging script based on post dh7 syntax
%:
    dh $@

```

```
# debmake generated override targets
```

This is essentially the standard **debian/rules** file with the **dh** command. Since this is the script package, this template **debian/rules** file has no build flag related contents.

debian/control (Vorlagendatei, v=0.2):

```
[debhello-0.2] $ cat debian/control
Source: debhello
Section: unknown
Priority: optional
Maintainer: "Osamu Aoki" <osamu@debian.org>
Build-Depends:
  debhelper-compat (= 13),
Standards-Version: 4.7.3
Homepage: <insert the upstream URL, if relevant>
Rules-Requires-Root: no
#Vcs-Git: https://salsa.debian.org/debian/debhello.git
#Vcs-Browser: https://salsa.debian.org/debian/<project_site>

Package: debhello
Section: unknown
Architecture: all
Multi-Arch: foreign
Depends:
  ${misc:Depends},
Description: auto-generated package by debmake
  This Debian binary package was auto-generated by the
  debmake(1) command provided by the debmake package.
.
==== This comes from the unmodified template file ====
.
Please edit this template file (debian/control) and other package files
(debian/*) to make them meet all the requirements of the Debian Policy
before uploading this package to the Debian archive.
.
See
* https://www.debian.org/doc/manuals/developers-reference/best-pkging-pract...
* https://www.debian.org/doc/manuals/debmake-doc/ch05.en.html#control
.
The synopsis description at the top should be about 60 characters and
written as a phrase. No extra capital letters or a final period. No
articles b''-b'' "a", "an", or "the".
.
The package description for general-purpose applications should be
written for a less technical user. This means that we should avoid
jargon. GNOME or KDE is fine but GTK+ is probably not.
.
Use the canonical forms of words:
* Use X Window System, X11, or X; not X Windows, X-Windows, or X Window.
* Use GTK+, not GTK or gtk.
* Use GNOME, not Gnome.
* Use PostScript, not Postscript or postscript.
```

Since this is the shell script package, the **debmake** command sets „**Architecture: all**“ and „**Multi-Arch: foreign**“. Also, it sets required **substvar** parameters as „**Depends: \${misc:Depends}**“. These are explained in „Kapitel 6“.

Since this upstream source lacks the upstream **Makefile**, that functionality needs to be provided by the maintainer. This upstream source contains only a script file and data files and no C source files; the **build** process can be skipped but the **install** process needs to be implemented. For this case, this is achieved cleanly by adding the **debian/install** and **debian/manpages** files without complicating the **debian/rules** file.

Let's make this Debian package better as the maintainer.

debian/rules (Betreuerversion, v=0.2):

```
[base_dir] $ cd debhello-0.2
[debhello-0.2] $ vim debian/rules
... hack, hack, hack, ...
[debhello-0.2] $ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1

%:
    dh $@
```

debian/control (Betreuerversion, v=0.2):

```
[debhello-0.2] $ vim debian/control
... hack, hack, hack, ...
[debhello-0.2] $ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends:
    debhelper-compat (= 13),
Standards-Version: 4.7.3
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello
Architecture: all
Multi-Arch: foreign
Depends:
    ${misc:Depends},
Description: Simple packaging example for debmake
    This Debian binary package is an example package.
    (This is an example only)
```

Warnung

If you leave „**Section: unknown**“ in the template **debian/control** file unchanged, the **lintian** error may cause a build failure.

debian/install (Betreuerversion, v=0.2):

```
[debhello-0.2] $ vim debian/install
... hack, hack, hack, ...
[debhello-0.2] $ cat debian/install
data/hello.desktop usr/share/applications
data/hello.png usr/share/pixmaps
scripts/hello usr/bin
```

debian/manpages (Betreuerversion, v=0.2):

```
$ vim debian/manpages
... hack, hack, hack, ...
[debhello-0.2] $ cat debian/manpages
man/hello.1
```

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

Vorlagendateien unter debian/. (v=0.2):

```
[debhello-0.2] $ rm -f debian/clean debian/dirs debian/links
[debhello-0.2] $ rm -f debian/README.source debian/source/*.ex
```

```
[debhello-0.2] $ rm -rf debian/patches
[debhello-0.2] $ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- docs
+-- examples
+-- gbp.conf
+-- install
+-- manpages
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 15 files
```

You can create a non-native Debian package using the **debuild** command (or its equivalents) in this source tree. The command output is very verbose and explains what it does as follows.

```
[base_dir] $ cd debhello-0.2
[debhello-0.2] $ debuild
dpkg-buildpackage -us -uc -ui -i
dpkg-buildpackage: info: source package debhello
dpkg-buildpackage: info: source version 0.2-1
dpkg-buildpackage: info: source distribution unstable
dpkg-buildpackage: info: source changed by Osamu Aoki <osamu@debian.org>
dpkg-source -i --before-build .
dpkg-buildpackage: info: host architecture amd64
debian/rules clean
dh clean
dh_clean
rm -f debian/debhelper-build-stamp
...
debian/rules binary
dh binary
dh_update_autotools_config
dh_autoreconf
create-stamp debian/debhelper-build-stamp
dh_prep
rm -f -- debian/debhello.substvars
rm -fr -- debian/.debhelper/generated/debhello/ debian/debhello/ debi...
dh_auto_install --destdir=debian/debhello/
...
Finished running lintian.
```

Lassen Sie uns die Ergebnisse anschauen.

The generated files of debhello version 0.2 by the debuild command:

```
[debhello-0.2] $ cd ..
[base_dir] $ tree -FL 1
./
+-- debhello-0.2/
+-- debhello-0.2.tar.xz
+-- debhello_0.2-1.debian.tar.xz
+-- debhello_0.2-1.dsc
+-- debhello_0.2-1_all.deb
+-- debhello_0.2-1_amd64.build
```

```
+-- debhello_0.2-1_amd64.buildinfo
+-- debhello_0.2-1_amd64.changes
+-- debhello_0.2.orig.tar.xz -> debhello-0.2.tar.xz
```

2 directories, 8 files

You see all the generated files.

- The **debhello_0.2.orig.tar.xz** file is a symlink to the upstream tarball.
- The **debhello_0.2-1.debian.tar.xz** file contains the maintainer generated contents.
- The **debhello_0.2-1.dsc** file is the meta data file for the Debian source package.
- Die Datei **debhello_0.2-1_all.deb** ist das Debian-Binärpaket.
- The **debhello_0.2-1_amd64.build** file is the build log file.
- The **debhello_0.2-1_amd64.buildinfo** file is the meta data file generated by **dpkg-genbuildinfo(1)**.
- The **debhello_0.2-1_amd64.changes** file is the meta data file for the Debian binary package.

The **debhello_0.2-1.debian.tar.xz** file contains the Debian changes to the upstream source as follows.

The compressed archive contents of debhello_0.2-1.debian.tar.xz:

```
[base_dir] $ tar --xz -tf debhello-0.2.tar.xz
debhello-0.2/
debhello-0.2/data/
debhello-0.2/data/hello.desktop
debhello-0.2/data/hello.png
debhello-0.2/man/
debhello-0.2/man/hello.1
debhello-0.2/scripts/
debhello-0.2/scripts/hello
debhello-0.2/README.md
[base_dir] $ tar --xz -tf debhello_0.2-1.debian.tar.xz
debian/
debian/README.Debian
debian/changelog
debian/control
debian/copyright
debian/docs
debian/examples
debian/gbp.conf
debian/install
debian/manpages
debian/rules
debian/salsa-ci.yml
debian/source/
debian/source/format
debian/tests/
debian/tests/control
debian/upstream/
debian/upstream/metadata
debian/watch
```

The **debhello_0.2-1_amd64.deb** file contains the files to be installed as follows.

The binary package contents of debhello_0.2-1_all.deb:

```
[base_dir] $ dpkg -c debhello_0.2-1_all.deb
drwxr-xr-x root/root ... ./
drwxr-xr-x root/root ... ./usr/
drwxr-xr-x root/root ... ./usr/bin/
-rwxr-xr-x root/root ... ./usr/bin/hello
drwxr-xr-x root/root ... ./usr/share/
```

```
drwxr-xr-x root/root ... ./usr/share/applications/
-rw-r--r-- root/root ... ./usr/share/applications/hello.desktop
drwxr-xr-x root/root ... ./usr/share/doc/
drwxr-xr-x root/root ... ./usr/share/doc/debhello/
-rw-r--r-- root/root ... ./usr/share/doc/debhello/README.Debian
-rw-r--r-- root/root ... ./usr/share/doc/debhello/changelog.Debian.gz
-rw-r--r-- root/root ... ./usr/share/doc/debhello/copyright
drwxr-xr-x root/root ... ./usr/share/man/
drwxr-xr-x root/root ... ./usr/share/man/man1/
-rw-r--r-- root/root ... ./usr/share/man/man1/hello.1.gz
drwxr-xr-x root/root ... ./usr/share/pixmaps/
-rw-r--r-- root/root ... ./usr/share/pixmaps/hello.png
```

Dies ist die erstellte Abhängigkeitsliste von **debhello_0.2-1_all.deb**.

The generated dependency list of debhello_0.2-1_all.deb:

```
[debhello-0.2] $ dpkg -f debhello_0.2-1_all.deb pre-depends \
                depends recommends conflicts breaks
```

(No extra dependency packages required since this is a POSIX shell program.)

Anmerkung



If you wish to replace upstream provided PNG file **data/hello.png** with maintainer provided one **debian/hello.png**, editing **debian/install** isn't enough. When you add **debian/hello.png**, you need to add a line „include-binaries“ to **debian/source/options** since PNG is a binary file. See **dpkg-source(1)**.

/tep200.slog/ vim:set filetype=asciidoc:

14.3 Makefile (Shell, CLI)

Here is an example of creating a simple Debian package from a POSIX shell CLI program using the **Makefile** as its build system.

Let's assume its upstream tarball to be **debhello-1.0.tar.xz**.

Diese Art der Quellen soll als Nichtsystemdatei wie folgt installiert werden:

```
[base_dir] $ tar -xzmf debhello-1.0.tar.xz
[base_dir] $ cd debhello-1.0
[debhello-1.0] $ make install
```

Debian packaging requires changing this „**make install**“ process to install files to the target system image location instead of the normal location under **/usr/local**.

Let's get the source and make the Debian package.

Download debhello-1.0.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-1.0.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-1.0.tar.xz
[base_dir] $ tree
.
+-- debhello-1.0
|   +-- Makefile
|   +-- README.md
|   +-- data
|       | +-- hello.desktop
|       | +-- hello.png
|   +-- man
|       | +-- hello.1
|   +-- scripts
|       +-- hello
```

```
+-- debhello-1.0.tar.xz
5 directories, 7 files
```

Here, the **Makefile** uses **\$(DESTDIR)** and **\$(prefix)** properly. All other files are the same as in „Abschnitt 14.2“ and most of the packaging activities are the same.

Makefile (v=1.0)

```
[base_dir] $ cat debhello-1.0/Makefile
prefix = /usr/local

all:
    : # do nothing

install:
    install -D scripts/hello \
        $(DESTDIR)$(prefix)/bin/hello
    install -m 644 -D data/hello.desktop \
        $(DESTDIR)$(prefix)/share/applications/hello.desktop
    install -m 644 -D data/hello.png \
        $(DESTDIR)$(prefix)/share/pixmaps/hello.png
    install -m 644 -D man/hello.1 \
        $(DESTDIR)$(prefix)/share/man/man1/hello.1

clean:
    : # do nothing

distclean: clean

uninstall:
    -rm -f $(DESTDIR)$(prefix)/bin/hello
    -rm -f $(DESTDIR)$(prefix)/share/applications/hello.desktop
    -rm -f $(DESTDIR)$(prefix)/share/pixmaps/hello.png
    -rm -f $(DESTDIR)$(prefix)/share/man/man1/hello.1

.PHONY: all install clean distclean uninstall
```

Let's package this with the **debmake** command. Here, the **-b':sh'** option is used to specify that the generated binary package is a shell script.

```
[base_dir] $ cd debhello-1.0
[debhello-1.0] $ debmake -b':sh' -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-1.0] $ cd ..
I: Non-native Debian package pkg="debhello", ver="1.0", rev="1" method="dir_d...
I: already in the package-version form: "debhello-1.0"
I: [base_dir] $ ln -sf debhello-1.0.tar.xz debhello_1.0.orig.tar.xz
I: [base_dir] $ cd debhello-1.0
I: parsing option -b ":sh"
I: binary package=debhello Type=script / Arch=all M-A=foreign
I: build_type = make
I: ext_type = 1 1 files
I: ext_type = desktop 1 files
I: ext_type = md 1 files
I: creating debian/* files with "-x 1" option
I: [debhello-1.0] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
I: creating debian/rules from extra0_rules
I: creating debian/source/format from extra0source_format
...
```

Let's inspect the notable template files generated.

debian/rules (Vorlagendatei, v=1.0):

```
[base_dir] $ cd debhello-1.0
[debhello-1.0] $ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
# See debhelper(7) (un-comment to enable)
# This is an autogenerated template for debian/rules.
#
# Output every command that modifies files on the build system.
#export DH_VERBOSE = 1
#
# Copy some variable definitions from pkg-info.mk and vendor.mk
# under /usr/share/dpkg/ to here if they are useful.
#
# These are rarely used code. (START)
#
# The following include for *.mk magically sets miscellaneous
# variables while honoring existing values of pertinent
# environment variables:
#
# Architecture-related variables such as DEB_TARGET_MULTIARCH:
#include /usr/share/dpkg/architecture.mk
# Vendor-related variables such as DEB_VENDOR:
#include /usr/share/dpkg/vendor.mk
# Package-related variables such as DEB_DISTRIBUTION
#include /usr/share/dpkg/pkg-info.mk
#
# You may alternatively set them using a simple script such as:
# DEB_VENDOR ?= $(shell dpkg-vendor --query Vendor)
#
# These are rarely used code. (END)
#

### main packaging script based on post dh7 syntax
%:
    dh $@

# debmake generated override targets
# Use "make prefix=/usr" (override prefix=/usr/local in Makefile)
#override_dh_auto_install:
#    dh_auto_install -- prefix=/usr

# Do not install python .pyc .pyo if they exist
#override_dh_install:
#    dh_install --list-missing -X.pyc -X.pyo
```

Let's make this Debian package better as the maintainer.

debian/rules (Betreuerversion, v=1.0):

```
[base_dir] $ cd debhello-1.0
[debhello-1.0] $ vim debian/rules
... hack, hack, hack, ...
[debhello-1.0] $ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1

%:
    dh $@

override_dh_auto_install:
    dh_auto_install -- prefix=/usr
```


Since this upstream source has the proper upstream **Makefile**, there is no need to create **debian/install** and **debian/manpages** files.

The **debian/control** file is exactly the same as the one in „Abschnitt 14.2“.

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

Vorlagendateien unter debian/. (v=1.0):

```
[debhello-1.0] $ rm -f debian/clean debian/dirs debian/install debian/links
[debhello-1.0] $ rm -f debian/README.source debian/source/*.ex
[debhello-1.0] $ rm -rf debian/patches
[debhello-1.0] $ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- docs
+-- examples
+-- gbp.conf
+-- manpages
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 14 files
```

The rest of the packaging activities are practically the same as the ones in „Abschnitt 14.2“.

14.4 pyproject.toml (Python3, CLI)

Here is an example of creating a simple Debian package from a Python3 CLI program using **pyproject.toml**.

Let's get the source and make the Debian package.

Download debhello-1.1.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-1.1.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-1.1.tar.xz
[base_dir] $ tree
.
+-- debhello-1.1
|   +-- LICENSE
|   +-- MANIFEST.in
|   +-- README.md
|   +-- data
|   |   +-- hello.desktop
|   |   +-- hello.png
|   +-- manpages
|   |   +-- hello.1
|   +-- pyproject.toml
|   +-- src
|       +-- debhello
|           +-- __init__.py
|           +-- main.py
+-- debhello-1.1.tar.xz

6 directories, 10 files
```

Here, the content of this **debhello** source tree as follows.

pyproject.toml (v=1.1) — PEP 517 configuration

```
[base_dir] $ cat debhello-1.1/pyproject.toml
[build-system]
requires = ["setuptools >= 61.0"] # REQUIRED if [build-system] table is used...
build-backend = "setuptools.build_meta" # If not defined, then legacy behavi...

[project]
name = "debhello"
version = "1.1.0"
description = "Hello Python (CLI)"
readme = {file = "README.md", content-type = "text/markdown"}
requires-python = ">=3.12"
license = "MIT"
keywords = ["debhello"]
authors = [
    {name = "Osamu Aoki", email = "osamu@debian.org" },
]
maintainers = [
    {name = "Osamu Aoki", email = "osamu@debian.org" },
]
classifiers = [
    "Development Status :: 5 - Production/Stable",
    "Intended Audience :: Developers",
    "Topic :: System :: Archiving :: Packaging",
    "Programming Language :: Python :: 3",
    "Programming Language :: Python :: 3.12",
    "Programming Language :: Python :: 3 :: Only",
    # Others
    "Operating System :: POSIX :: Linux",
    "Natural Language :: English",
]
[project.urls]
"Homepage" = "https://salsa.debian.org/debian/debmake"
"Bug Reports" = "https://salsa.debian.org/debian/debmake/issues"
"Source" = "https://salsa.debian.org/debian/debmake"
[project.scripts]
hello = "debhello.main:main"
[tool.setuptools]
package-dir = {"" = "src"}
packages = ["debhello"]
include-package-data = true
```

MANIFEST.in (v=1.1) — for tar-ball.

```
[base_dir] $ cat debhello-1.1/MANIFEST.in
include data/*
include manpages/*
```

src/debhello/__init__.py (v=1.1)

```
[base_dir] $ cat debhello-1.1/src/debhello/__init__.py
"""
debhello program (CLI)
"""
```

src/debhello/main.py (v=1.1) — command entry point

```
[base_dir] $ cat debhello-1.1/src/debhello/main.py
"""
debhello program
"""

import sys
```

```
__version__ = '1.1.0'

def main(): # needed for console script
    print(' ===== Hello Python3 =====')
    print('argv = {}'.format(sys.argv))
    print('version = {}'.format(debhello.__version__))
    return

if __name__ == "__main__":
    sys.exit(main())
```

Let's package this with the **debmake** command. Here, the **-b:py3** option is used to specify the generated binary package containing Python3 script and module files.

```
[base_dir] $ cd debhello-1.1
[debhello-1.1] $ debmake -b:py3 -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-1.1] $ cd ..
I: Non-native Debian package pkg="debhello", ver="1.1", rev="1" method="dir_d...
I: already in the package-version form: "debhello-1.1"
I: [base_dir] $ ln -sf debhello-1.1.tar.xz debhello_1.1.orig.tar.xz
I: [base_dir] $ cd debhello-1.1
I: parsing option -b ":py3"
I: binary package=debhello Type=python3 / Arch=all M-A=foreign
W: setuptools build system.
I: build_type = Python (pyproject.toml: PEP-518, PEP-621, PEP-660)
I: ext_type = python3                2 files
I: ext_type = 1                      1 files
I: ext_type = desktop                1 files
I: creating debian/* files with "-x 1" option
I: [debhello-1.1] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
I: creating debian/rules from extra0_rules
...
```

Let's inspect the notable template files generated.

debian/rules (Vorlagendatei, v=1.1):

```
[base_dir] $ cd debhello-1.1
[debhello-1.1] $ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
# See debhelper(7) (un-comment to enable)
# This is an autogenerated template for debian/rules.
#
# Output every command that modifies files on the build system.
#export DH_VERBOSE = 1
#
# Copy some variable definitions from pkg-info.mk and vendor.mk
# under /usr/share/dpkg/ to here if they are useful.
#
# These are rarely used code. (START)
#
# The following include for *.mk magically sets miscellaneous
# variables while honoring existing values of pertinent
# environment variables:
#
# Architecture-related variables such as DEB_TARGET_MULTIARCH:
#include /usr/share/dpkg/architecture.mk
# Vendor-related variables such as DEB_VENDOR:
#include /usr/share/dpkg/vendor.mk
```

```
# Package-related variables such as DEB_DISTRIBUTION
#include /usr/share/dpkg/pkg-info.mk
#
# You may alternatively set them using a simple script such as:
# DEB_VENDOR ?= $(shell dpkg-vendor --query Vendor)
#
# These are rarely used code. (END)
#

### main packaging script based on post dh7 syntax
%:
    dh $@ --with python3 --buildsystem=pybuild

# debmake generated override targets
# Too complicated to provide examples here.
#
# Check situation of Python on Debian
#   https://wiki.debian.org/Python
#
#   https://wiki.debian.org/Python/TransitionToDHPython2
#   https://wiki.debian.org/Python/Pybuild
#   https://wiki.debian.org/Python/LibraryStyleGuide
#
# If a module package doesn't use distutils or setuptools but uses flit
# you need flit plugin. See pybuild(1).
#
# Pure PEP-517 based build with "python3 -m build ..." is supported.
#
# To update the upstream source to support python3, see
#   https://wiki.python.org/moin/Python2orPython3
#   https://wiki.python.org/moin/PortingToPy3k/BilingualQuickRef
```

This is essentially the standard **debian/rules** file with the **dh** command.

The use of the „**--with python3**“ option invokes **dh_python3** to calculate Python dependencies, add maintainer scripts to byte compiled files, etc. See **dh_python3(1)**.

The use of the „**--buildsystem=pybuild**“ option invokes various build systems for requested Python versions in order to build modules and extensions. See **pybuild(1)**.

debian/control (Vorlagendatei, v=1.1):

```
[debhelloworld-1.1] $ cat debian/control
Source: debhelloworld
Section: unknown
Priority: optional
Maintainer: "Osamu Aoki" <osamu@debian.org>
Build-Depends:
    debhelper-compat (= 13),
    dh-python,
    pybuild-plugin-pyproject,
    python3-all,
    python3-setuptools,
Standards-Version: 4.7.3
Homepage: <insert the upstream URL, if relevant>
Rules-Requires-Root: no
#Vcs-Git: https://salsa.debian.org/debian/debhelloworld.git
#Vcs-Browser: https://salsa.debian.org/debian/<project_site>

Package: debhelloworld
Section: unknown
Architecture: all
Multi-Arch: foreign
Depends:
    ${misc:Depends},
    ${python3:Depends},
Description: auto-generated package by debmake
```

```

This Debian binary package was auto-generated by the
debmake(1) command provided by the debmake package.
.
===== This comes from the unmodified template file =====
.
Please edit this template file (debian/control) and other package files
(debian/*) to make them meet all the requirements of the Debian Policy
before uploading this package to the Debian archive.
.
See
* https://www.debian.org/doc/manuals/developers-reference/best-pkging-pract...
* https://www.debian.org/doc/manuals/debmake-doc/ch05.en.html#control
.
The synopsis description at the top should be about 60 characters and
written as a phrase. No extra capital letters or a final period. No
articles b'"b'" "a", "an", or "the".
.
The package description for general-purpose applications should be
written for a less technical user. This means that we should avoid
jargon. GNOME or KDE is fine but GTK+ is probably not.
.
Use the canonical forms of words:
* Use X Window System, X11, or X; not X Windows, X-Windows, or X Window.
* Use GTK+, not GTK or gtk.
* Use GNOME, not Gnome.
* Use PostScript, not Postscript or postscript.

```

Since this is the Python3 package, the **debmake** command sets „**Architecture: all**“ and „**Multi-Arch: foreign**“. Also, it sets required **substvar** parameters as „**Depends: \${python3:Depends}, \${misc:Depends}**“. These are explained in „Kapitel 6“.

Let's make this Debian package better as the maintainer.

debian/rules (Betreuerversion, v=1.1):

```

[base_dir] $ cd debhello-1.1
[debhello-1.1] $ vim debian/rules
... hack, hack, hack, ...
[debhello-1.1] $ cat debian/rules
#!/usr/bin/make -f
export PYBUILD_NAME=debhello
export PYBUILD_VERBOSE=1
export DH_VERBOSE=1

%:
    dh $@ --with python3 --buildsystem=pybuild

```

debian/control (Betreuerversion, v=1.1):

```

[debhello-1.1] $ vim debian/control
... hack, hack, hack, ...
[debhello-1.1] $ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends:
    debhelper-compat (= 13),
    pybuild-plugin-pyproject,
    python3-all,
Standards-Version: 4.7.3
Rules-Requires-Root: no
Vcs-Browser: https://salsa.debian.org/debian/debmake-doc
Vcs-Git: https://salsa.debian.org/debian/debmake-doc.git
Homepage: https://salsa.debian.org/debian/debmake-doc

Package: debhello

```

```

Architecture: all
Depends:
    ${misc:Depends},
    ${python3:Depends},
Description: Simple packaging example for debmake
    This is an example package to demonstrate Debian packaging using
    the debmake command.
.
The generated Debian package uses the dh command offered by the
debhelper package and the dpkg source format `3.0 (quilt)'.

```

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

This **debhello** command comes with the upstream-provided manpage and desktop file but the upstream **pyproject.toml** doesn't install them. So you need to update **debian/install** and **debian/manpages** as follows:

debian/install (Betreuerversion, v=1.1):

```

[debhello-1.1] $ vim debian/copyright
... hack, hack, hack, ...
[debhello-1.1] $ cat debian/copyright
Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: debhello
Upstream-Contact: Osamu Aoki <osamu@debian.org>
Source: https://salsa.debian.org/debian/debmake-doc

Files:
*
Copyright: 2015-2024 Osamu Aoki <osamu@debian.org>
License: Expat
Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:
.
The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.
.
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

```

debian/manpages (Betreuerversion, v=1.1):

```

[debhello-1.1] $ vim debian/install
... hack, hack, hack, ...
[debhello-1.1] $ cat debian/install
data/hello.desktop usr/share/applications
data/hello.png usr/share/pixmaps

```

The rest of the packaging activities are practically the same as the ones in „Abschnitt 14.3“.

Vorlagendateien unter debian/. (v=1.1):

```

[debhello-1.1] $ rm -f debian/clean debian/dirs debian/links
[debhello-1.1] $ rm -f debian/README.source debian/source/*.ex
[debhello-1.1] $ rm -rf debian/patches
[debhello-1.1] $ tree -F debian
debian/
+-- README.Debian
+-- changelog

```

```
+-- control
+-- copyright
+-- docs
+-- examples
+-- gbp.conf
+-- install
+-- manpages
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 15 files
```

Hier ist die erstellte Abhängigkeitsliste von **debhello_1.1-1_all.deb**.

The generated dependency list of debhello_1.1-1_all.deb:

```
[debhello-1.1] $ dpkg -f debhello_1.1-1_all.deb pre-depends \
                depends recommends conflicts breaks
Depends: python3:any
```

14.5 Makefile (Shell, GUI)

Here is an example of creating a simple Debian package from a POSIX shell GUI program using the **Makefile** as its build system.

This upstream is based on „Abschnitt 14.3“ with enhanced GUI support.

Let's assume its upstream tarball to be **debhello-1.2.tar.xz**.

Let's get the source and make the Debian package.

Download debhello-1.2.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-1.2.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-1.2.tar.xz
[base_dir] $ tree
.
+-- debhello-1.2
|   +-- Makefile
|   +-- README.md
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- man
|       |   +-- hello.1
|   +-- scripts
|       +-- hello
+-- debhello-1.2.tar.xz

5 directories, 7 files
```

Here, the **hello** has been re-written to use the **zenity** command to make this a GTK+ GUI program.
hello (v=1.2)

```
[base_dir] $ cat debhello-1.2/scripts/hello
#!/bin/sh -e
zenity --info --title "hello" --text "Hello from the shell!"
```

Here, the desktop file is updated to be **Terminal=false** as a GUI program.
hello.desktop (v=1.2)

```
[base_dir] $ cat debhello-1.2/data/hello.desktop
[Desktop Entry]
Name=Hello
Name[fr]=Bonjour
Comment=Greetings
Comment[fr]=Salutations
Type=Application
Keywords=hello
Exec=hello
Terminal=false
Icon=hello.png
Categories=Utility;
```

Alle anderen Dateien sind identisch zu „Abschnitt 14.3“.

Let's package this with the **debmake** command. Here, the „-b':sh'“ option is used to specify that the generated binary package is a shell script.

```
[base_dir] $ cd debhello-1.2
[debhello-1.2] $ debmake -b':sh' -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-1.2] $ cd ..
I: Non-native Debian package pkg="debhello", ver="1.2", rev="1" method="dir_d...
I: already in the package-version form: "debhello-1.2"
I: [base_dir] $ ln -sf debhello-1.2.tar.xz debhello_1.2.orig.tar.xz
I: [base_dir] $ cd debhello-1.2
I: parsing option -b ":sh"
I: binary package=debhello Type=script / Arch=all M-A=foreign
I: build_type = make
I: ext_type = 1                      1 files
I: ext_type = desktop                1 files
I: ext_type = md                     1 files
I: creating debian/* files with "-x 1" option
I: [debhello-1.2] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
I: creating debian/rules from extra0_rules
I: creating debian/source/format from extra0source_format
...
```

Let's inspect the notable template files generated.

debian/control (Vorlagendatei, v=1.2):

```
[debhello-1.2] $ cat debian/control
Source: debhello
Section: unknown
Priority: optional
Maintainer: "Osamu Aoki" <osamu@debian.org>
Build-Depends:
  debhelper-compat (= 13),
Standards-Version: 4.7.3
Homepage: <insert the upstream URL, if relevant>
Rules-Requires-Root: no
#Vcs-Git: https://salsa.debian.org/debian/debhello.git
#Vcs-Browser: https://salsa.debian.org/debian/<project_site>

Package: debhello
Section: unknown
Architecture: all
Multi-Arch: foreign
Depends:
  ${misc:Depends},
```



```

Description: auto-generated package by debmake
This Debian binary package was auto-generated by the
debmake(1) command provided by the debmake package.
.
===== This comes from the unmodified template file =====
.
Please edit this template file (debian/control) and other package files
(debian/*) to make them meet all the requirements of the Debian Policy
before uploading this package to the Debian archive.
.
See
* https://www.debian.org/doc/manuals/developers-reference/best-pkging-pract...
* https://www.debian.org/doc/manuals/debmake-doc/ch05.en.html#control
.
The synopsis description at the top should be about 60 characters and
written as a phrase. No extra capital letters or a final period. No
articles b''-b'' "a", "an", or "the".
.
The package description for general-purpose applications should be
written for a less technical user. This means that we should avoid
jargon. GNOME or KDE is fine but GTK+ is probably not.
.
Use the canonical forms of words:
* Use X Window System, X11, or X; not X Windows, X-Windows, or X Window.
* Use GTK+, not GTK or gtk.
* Use GNOME, not Gnome.
* Use PostScript, not Postscript or postscript.

```

Let's make this Debian package better as the maintainer.

debian/control (Betreuerversion, v=1.2):

```

[debhello-1.2] $ vim debian/control
... hack, hack, hack, ...
[debhello-1.2] $ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends:
  debhelper-compat (= 13),
Standards-Version: 4.7.3
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello
Architecture: all
Multi-Arch: foreign
Depends:
  zenity,
  ${misc:Depends},
Description: Simple packaging example for debmake
This Debian binary package is an example package.
(This is an example only)

```

Please note the manually added **zenity** dependency.

The **debian/rules** file is exactly the same as the one in „Abschnitt 14.3“.

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

Template files under debian/. (v=1.2):

```

[debhello-1.2] $ rm -f debian/clean debian/dirs debian/install debian/links
[debhello-1.2] $ rm -f debian/README.source debian/source/*.ex
[debhello-1.2] $ rm -rf debian/patches
[debhello-1.2] $ tree -F debian
debian/

```

```
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- docs
+-- examples
+-- gbp.conf
+-- manpages
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 14 files
```

Die restlichen Paketieraktivitäten sind praktisch die gleichen wie in „Abschnitt 14.3“. Hier ist die erstellte Abhängigkeitsliste von **debhello_1.2-1_all.deb**.

The generated dependency list of debhello_1.2-1_all.deb:

```
[debhello-1.2] $ dpkg -f debhello_1.2-1_all.deb pre-depends \
                depends recommends conflicts breaks
Depends: zenity
```

14.6 pyproject.toml (Python3, GUI)

Here is an example of creating a simple Debian package from a Python3 GUI program using **pyproject.toml**.

Let's assume this upstream tarball to be **debhello-1.3.tar.xz**.

Let's get the source and make the Debian package.

Download debhello-1.3.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-1.3.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-1.3.tar.xz
[base_dir] $ tree
.
+-- debhello-1.3
|   +-- LICENSE
|   +-- MANIFEST.in
|   +-- README.md
|   +-- data
|   |   +-- hello.desktop
|   |   +-- hello.png
|   +-- manpages
|   |   +-- hello.1
|   +-- pyproject.toml
|   +-- src
|       +-- debhello
|           +-- __init__.py
|           +-- main.py
+-- debhello-1.3.tar.xz

6 directories, 10 files
```

Here, the content of this **debhello** source tree as follows.

pyproject.toml (v=1.3) — PEP 517 configuration

```
[base_dir] $ cat debhello-1.3/pyproject.toml
[build-system]
requires = ["setuptools >= 61.0"] # REQUIRED if [build-system] table is used...
build-backend = "setuptools.build_meta" # If not defined, then legacy behavi...

[project]
name = "debhello"
version = "1.3.0"
description = "Hello Python (GUI)"
readme = {file = "README.md", content-type = "text/markdown"}
requires-python = ">=3.12"
license = "MIT"
keywords = ["debhello"]
authors = [
    {name = "Osamu Aoki", email = "osamu@debian.org" },
]
maintainers = [
    {name = "Osamu Aoki", email = "osamu@debian.org" },
]
classifiers = [
    "Development Status :: 5 - Production/Stable",
    "Intended Audience :: Developers",
    "Topic :: System :: Archiving :: Packaging",
    "Programming Language :: Python :: 3",
    "Programming Language :: Python :: 3.12",
    "Programming Language :: Python :: 3 :: Only",
    # Others
    "Operating System :: POSIX :: Linux",
    "Natural Language :: English",
]
[project.urls]
"Homepage" = "https://salsa.debian.org/debian/debmake"
"Bug Reports" = "https://salsa.debian.org/debian/debmake/issues"
"Source" = "https://salsa.debian.org/debian/debmake"
[project.scripts]
hello = "debhello.main:main"
[tool.setuptools]
package-dir = {"" = "src"}
packages = ["debhello"]
include-package-data = true
```

MANIFEST.in (v=1.3) — for tar-ball.

```
[base_dir] $ cat debhello-1.3/MANIFEST.in
include data/*
include manpages/*
```

src/debhello/__init__.py (v=1.3)

```
[base_dir] $ cat debhello-1.3/src/debhello/__init__.py
"""
debhello program (GUI)
"""
```

src/debhello/main.py (v=1.3) — command entry point

```
[base_dir] $ cat debhello-1.3/src/debhello/main.py
#!/usr/bin/python3
from gi.repository import Gtk

__version__ = '1.3.0'

class TopWindow(Gtk.Window):

    def __init__(self):
```

```

    Gtk.Window.__init__(self)
    self.title = "Hello World!"
    self.counter = 0
    self.border_width = 10
    self.set_default_size(400, 100)
    self.set_position(Gtk.WindowPosition.CENTER)
    self.button = Gtk.Button(label="Click me!")
    self.button.connect("clicked", self.on_button_clicked)
    self.add(self.button)
    self.connect("delete-event", self.on_window_destroy)

    def on_window_destroy(self, *args):
        Gtk.main_quit(*args)

    def on_button_clicked(self, widget):
        self.counter += 1
        widget.set_label("Hello, World!\nClick count = %i" % self.counter)

def main():
    window = TopWindow()
    window.show_all()
    Gtk.main()

if __name__ == '__main__':
    main()

```

Let's package this with the **debmake** command. Here, the **-b':py3'** option is used to specify that the generated binary package contains Python3 script and module files.

```

[base_dir] $ cd debhello-1.3
[debhello-1.3] $ debmake -b':py3' -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-1.3] $ cd ..
I: Non-native Debian package pkg="debhello", ver="1.3", rev="1" method="dir_d...
I: already in the package-version form: "debhello-1.3"
I: [base_dir] $ ln -sf debhello-1.3.tar.xz debhello_1.3.orig.tar.xz
I: [base_dir] $ cd debhello-1.3
I: parsing option -b ":py3"
I: binary package=debhello Type=python3 / Arch=all M-A=foreign
W: setuptools build system.
I: build_type = Python (pyproject.toml: PEP-518, PEP-621, PEP-660)
I: ext_type = python3                2 files
I: ext_type = 1                      1 files
I: ext_type = desktop                1 files
I: creating debian/* files with "-x 1" option
I: [debhello-1.3] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
I: creating debian/rules from extra0_rules
...

```

The result is practically the same as in „Abschnitt 14.4“.

Let's make this Debian package better as the maintainer.

debian/rules (Betreuerversion, v=1.3):

```

[base_dir] $ cd debhello-1.3
[debhello-1.3] $ vim debian/rules
... hack, hack, hack, ...
[debhello-1.3] $ cat debian/rules
#!/usr/bin/make -f
export PYBUILD_NAME=debhello
export PYBUILD_VERBOSE=1

```

```
export DH_VERBOSE=1
```

```
%:
```

```
dh $@ --with python3 --buildsystem=pybuild
```

debian/control (Betreuerversion, v=1.3):

```
[debhello-1.3] $ vim debian/control
... hack, hack, hack, ...
[debhello-1.3] $ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends:
    debhelper-compat (= 13),
    pybuild-plugin-pyproject,
    python3-all,
Standards-Version: 4.7.3
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello
Architecture: all
Multi-Arch: foreign
Depends:
    gir1.2-gtk-3.0,
    python3-gi,
    ${misc:Depends},
    ${python3:Depends},
Description: Simple packaging example for debmake
    This Debian binary package is an example package.
    (This is an example only)
```

Please note the manually added **python3-gi** and **gir1.2-gtk-3.0** dependencies.

The rest of the packaging activities are practically the same as in <pyproject>.

Hier ist die erstellte Abhängigkeitsliste von **debhello_1.3-1_all.deb**.

The generated dependency list of debhello_1.3-1_all.deb:

```
[debhello-1.3] $ dpkg -f debhello_1.3-1_all.deb pre-depends \
    depends recommends conflicts breaks
Depends: gir1.2-gtk-3.0, python3-gi, python3:any
```

14.7 Makefile (Paket mit einem Programm)

Here is an example of creating a simple Debian package from a simple C source program using the **Makefile** as its build system.

This is an enhanced upstream source example for „Kapitel 5“. This comes with the manpage, the desktop file, and the desktop icon. This also links to an external library **libm** to be a more practical example.

Let's assume this upstream tarball to be **debhello-1.4.tar.xz**.

Diese Art der Quellen soll als Nichtsystemdatei wie folgt installiert werden:

```
[base_dir] $ tar -xzmf debhello-1.4.tar.xz
[base_dir] $ cd debhello-1.4
[debhello-1.4] $ make
[debhello-1.4] $ make install
```

Debian packaging requires changing this „**make install**“ process to install files into the target system image location instead of the normal location under **/usr/local**.

Let's get the source and make the Debian package.

Download debhello-1.4.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-1.4.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-1.4.tar.xz
[base_dir] $ tree
.
+-- debhello-1.4
|   +-- LICENSE
|   +-- Makefile
|   +-- README.md
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- man
|       |   +-- hello.1
|   +-- src
|       +-- config.h
|       +-- hello.c
+-- debhello-1.4.tar.xz

5 directories, 9 files
```

Here, the contents of this source are as follows.

src/hello.c (v=1.4):

```
[base_dir] $ cat debhello-1.4/src/hello.c
#include "config.h"
#include <math.h>
#include <stdio.h>
int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\\n");
    printf("4.0 * atan(1.0) = %10f8\\n", 4.0*atan(1.0));
    return 0;
}
```

src/config.h (v=1.4):

```
[base_dir] $ cat debhello-1.4/Makefile
prefix = /usr/local

all: src/hello

src/hello: src/hello.c
    $(CC) $(CPPFLAGS) $(CFLAGS) $(LDFLAGS) -o $@ $^ -lm

install: src/hello
    install -D src/hello \
        $(DESTDIR)$(prefix)/bin/hello
    install -m 644 -D data/hello.desktop \
        $(DESTDIR)$(prefix)/share/applications/hello.desktop
    install -m 644 -D data/hello.png \
        $(DESTDIR)$(prefix)/share/pixmaps/hello.png
    install -m 644 -D man/hello.1 \
        $(DESTDIR)$(prefix)/share/man/man1/hello.1

clean:
    -rm -f src/hello

distclean: clean

uninstall:
    -rm -f $(DESTDIR)$(prefix)/bin/hello
    -rm -f $(DESTDIR)$(prefix)/share/applications/hello.desktop
```

```
-rm -f $(DESTDIR)$(prefix)/share/pixmaps/hello.png
-rm -f $(DESTDIR)$(prefix)/share/man/man1/hello.1
```

```
.PHONY: all install clean distclean uninstall
```

Makefile (v=1.4):

```
[base_dir] $ cat debhello-1.4/src/config.h
#define PACKAGE_AUTHOR "Osamu Aoki"
```

Please note that this **Makefile** has the proper **install** target for the manpage, the desktop file, and the desktop icon.

Let's package this with the **debmake** command.

```
[base_dir] $ cd debhello-1.4
[debhello-1.4] $ debmake -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-1.4] $ cd ..
I: Non-native Debian package pkg="debhello", ver="1.4", rev="1" method="dir_d...
I: already in the package-version form: "debhello-1.4"
I: [base_dir] $ ln -sf debhello-1.4.tar.xz debhello_1.4.orig.tar.xz
I: [base_dir] $ cd debhello-1.4
I: parsing option -b ""
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: build_type = make
I: ext_type = c                2 files
I: ext_type = 1                1 files
I: ext_type = desktop          1 files
I: creating debian/* files with "-x 1" option
I: [debhello-1.4] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
I: creating debian/rules from extra0_rules
I: creating debian/source/format from extra0source_format
...
```

The result is practically the same as in „Abschnitt 5.6“.

Let's make this Debian package, which is practically the same as in „Abschnitt 5.7“, better as the maintainer.

If the **DEB_BUILD_MAINT_OPTIONS** environment variable is not exported in **debian/rules**, lintian warns „W: debhello: hardening-no-relro usr/bin/hello“ for the linking of **libm**.

The **debian/control** file makes it exactly the same as the one in „Abschnitt 5.7“, since the **libm** library is always available as a part of **libc6** (Priority: required).

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

Vorlagendateien unter debian/. (v=1.4):

```
[debhello-1.4] $ rm -f debian/clean debian/dirs debian/links
[debhello-1.4] $ rm -f debian/README.source debian/source/*.ex
[debhello-1.4] $ rm -rf debian/patches
[debhello-1.4] $ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- docs
+-- examples
+-- gbp.conf
+-- install
+-- manpages
+-- rules*
```

```
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 15 files
```

The rest of the packaging activities are practically the same as the one in „Abschnitt 5.8“. Here is the generated dependency list of all binary packages.

Die erstellte Abhängigkeitsliste aller Binärpakete (v=1.4):

```
[debhello-1.4] $ dpkg -f debhello-dbgsym_1.4-1_amd64.deb pre-depends \
                depends recommends conflicts breaks
Depends: debhello (= 1.4-1)
[debhello-1.4] $ dpkg -f debhello_1.4-1_amd64.deb pre-depends \
                depends recommends conflicts breaks
Depends: libc6 (>= 2.34)
```

14.8 Makefile.in + configure (Paket mit einem Programm)

Here is an example of creating a simple Debian package from a simple C source program using **Makefile.in** and **configure** as its build system.

This is an enhanced upstream source example for „Abschnitt 14.7“. This also links to an external library, **libm**, and this source is configurable using arguments to the **configure** script, which generates the **Makefile** and **src/config.h** files.

Let's assume this upstream tarball to be **debhello-1.5.tar.xz**.

This type of source is meant to be installed as a non-system file, for example, as:

```
[base_dir] $ tar -xzmf debhello-1.5.tar.xz
[base_dir] $ cd debhello-1.5
[debhello-1.5] $ ./configure --with-math
[debhello-1.5] $ make
[debhello-1.5] $ make install
```

Let's get the source and make the Debian package.

Download debhello-1.5.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-1.5.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-1.5.tar.xz
[base_dir] $ tree
.
+-- debhello-1.5
|   +-- LICENSE
|   +-- Makefile.in
|   +-- README.md
|   +-- configure
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- man
|       |   +-- hello.1
|   +-- src
|       +-- hello.c
+-- debhello-1.5.tar.xz

5 directories, 9 files
```


Here, the contents of this source are as follows.

src/hello.c (v=1.5):

```
[base_dir] $ cat debhello-1.5/src/hello.c
#include "config.h"
#ifdef WITH_MATH
# include <math.h>
#endif
#include <stdio.h>
int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\n");
#ifdef WITH_MATH
    printf("4.0 * atan(1.0) = %10f8\n", 4.0*atan(1.0));
#else
    printf("I can't do MATH!\n");
#endif
    return 0;
}
```

Makefile.in (v=1.5):

```
[base_dir] $ cat debhello-1.5/Makefile.in
prefix = @prefix@

all: src/hello

src/hello: src/hello.c
    $(CC) @VERBOSE@ \
        $(CPPFLAGS) \
        $(CFLAGS) \
        $(LDFLAGS) \
        -o $@ $^ \
        @LINKLIB@

install: src/hello
    install -D src/hello \
        $(DESTDIR)$(prefix)/bin/hello
    install -m 644 -D data/hello.desktop \
        $(DESTDIR)$(prefix)/share/applications/hello.desktop
    install -m 644 -D data/hello.png \
        $(DESTDIR)$(prefix)/share/pixmaps/hello.png
    install -m 644 -D man/hello.1 \
        $(DESTDIR)$(prefix)/share/man/man1/hello.1

clean:
    -rm -f src/hello

distclean: clean

uninstall:
    -rm -f $(DESTDIR)$(prefix)/bin/hello
    -rm -f $(DESTDIR)$(prefix)/share/applications/hello.desktop
    -rm -f $(DESTDIR)$(prefix)/share/pixmaps/hello.png
    -rm -f $(DESTDIR)$(prefix)/share/man/man1/hello.1

.PHONY: all install clean distclean uninstall
```

configure (v=1.5):

```
[base_dir] $ cat debhello-1.5/configure
#!/bin/sh -e
# default values
PREFIX="/usr/local"
VERBOSE=""
```

```

WITH_MATH="0"
LINKLIB=""
PACKAGE_AUTHOR="John Doe"

# parse arguments
while [ "${1}" != "" ]; do
    VAR="${1%=*}" # Drop suffix =*
    VAL="${1#*=}" # Drop prefix *=
    case "${VAR}" in
        --prefix)
            PREFIX="${VAL}"
            ;;
        --verbose|-v)
            VERBOSE="-v"
            ;;
        --with-math)
            WITH_MATH="1"
            LINKLIB="-lm"
            ;;
        --author)
            PACKAGE_AUTHOR="${VAL}"
            ;;
        *)
            echo "W: Unknown argument: ${1}"
            esac
            shift
    done

# setup configured Makefile and src/config.h
sed -e "s,@prefix@,${PREFIX}," \
    -e "s,@VERBOSE@,${VERBOSE}," \
    -e "s,@LINKLIB@,${LINKLIB}," \
    <Makefile.in >Makefile
if [ "${WITH_MATH}" = 1 ]; then
    echo "#define WITH_MATH" >src/config.h
else
    echo "/* not defined: WITH_MATH */" >src/config.h
fi
echo "#define PACKAGE_AUTHOR \"${PACKAGE_AUTHOR}\"" >>src/config.h

```

Please note that the **configure** command replaces strings with @...@ in **Makefile.in** to produce **Makefile** and creates **src/config.h**.

Let's package this with the **debmake** command.

```

[base_dir] $ cd debhello-1.5
[debhello-1.5] $ debmake -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-1.5] $ cd ..
I: Non-native Debian package pkg="debhello", ver="1.5", rev="1" method="dir_d...
I: already in the package-version form: "debhello-1.5"
I: [base_dir] $ ln -sf debhello-1.5.tar.xz debhello_1.5.orig.tar.xz
I: [base_dir] $ cd debhello-1.5
I: parsing option -b ""
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: build_type = configure
I: ext_type = c                1 files
I: ext_type = 1                1 files
I: ext_type = desktop          1 files
I: creating debian/* files with "-x 1" option
I: [debhello-1.5] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py

```

```
I: creating debian/changelog from extra0_changelog
I: creating debian/rules from extra0_rules
I: creating debian/source/format from extra0source_format
...
```

Das Ergebnis ist ähnlich zu „Abschnitt 5.6“, aber nicht exakt identisch.
Let's inspect the notable template files generated.

debian/rules (Vorlagendatei, v=1.5):

```
[base_dir] $ cd debhello-1.5
[debhello-1.5] $ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
# See debhelper(7) (un-comment to enable)
# This is an autogenerated template for debian/rules.
#
# Output every command that modifies files on the build system.
#export DH_VERBOSE = 1
#
# Copy some variable definitions from pkg-info.mk and vendor.mk
# under /usr/share/dpkg/ to here if they are useful.
#
# See FEATURE AREAS/ENVIRONMENT in dpkg-buildflags(1)
# Apply all hardening options
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
# Package maintainers to append CFLAGS
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
# Package maintainers to append LDFLAGS
#export DEB_LDFLAGS_MAINT_APPEND = -Wl, -O1
#
# With debhelper version 9 or newer, the dh command exports
# all buildflags. So there is no need to include the
# /usr/share/dpkg/buildflags.mk file here if compat is 9 or newer.
#
# These are rarely used code. (START)
#
# The following include for *.mk magically sets miscellaneous
# variables while honoring existing values of pertinent
# environment variables:
#
# Architecture-related variables such as DEB_TARGET_MULTIARCH:
#include /usr/share/dpkg/architecture.mk
# Vendor-related variables such as DEB_VENDOR:
#include /usr/share/dpkg/vendor.mk
# Package-related variables such as DEB_DISTRIBUTION
#include /usr/share/dpkg/pkg-info.mk
#
# You may alternatively set them using a simple script such as:
# DEB_VENDOR ?= $(shell dpkg-vendor --query Vendor)
#
# These are rarely used code. (END)
#

### main packaging script based on post dh7 syntax
%:
    dh $@

# debmake generated override targets
# Multiarch package requires library files to be installed to
# /usr/lib/<triplet>/ . If the build system does not support
# $(DEB_HOST_MULTIARCH), you may need to override some targets such as
# dh_auto_configure or dh_auto_install to use $(DEB_HOST_MULTIARCH) .
```

Let's make this Debian package better as the maintainer.

debian/rules (Betreuerversion, v=1.5):

```
[base_dir] $ cd debhello-1.5
[debhello-1.5] $ vim debian/rules
... hack, hack, hack, ...
[debhello-1.5] $ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@

override_dh_auto_configure:
    dh_auto_configure -- \
        --with-math \
        --author="Osamu Aoki"
```

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

The rest of the packaging activities are practically the same as the one in „Abschnitt 5.8“.

14.9 Autotools (Paket mit einem Programm)

Here is an example of creating a simple Debian package from a simple C source program using Autotools = Autoconf and Automake (**Makefile.am** and **configure.ac**) as its build system.

This source usually comes with the upstream auto-generated **Makefile.in** and **configure** files, too. This source can be packaged using these files as in „Abschnitt 14.8“ with the help of the **autotools-dev** package.

The better alternative is to regenerate these files using the latest Autoconf and Automake packages if the upstream provided **Makefile.am** and **configure.ac** are compatible with the latest version. This is advantageous for porting to new CPU architectures, etc. This can be automated by using the „**--with autoreconf**“ option for the **dh** command.

Let's assume this upstream tarball to be **debhello-1.6.tar.xz**.

This type of source is meant to be installed as a non-system file, for example, as:

```
[base_dir] $ tar -xzmf debhello-1.6.tar.xz
[base_dir] $ cd debhello-1.6
[debhello-1.6] $ autoreconf -ivf # optional
[debhello-1.6] $ ./configure --with-math
[debhello-1.6] $ make
[debhello-1.6] $ make install
```

Let's get the source and make the Debian package.

Download debhello-1.6.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-1.6.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-1.6.tar.xz
[base_dir] $ tree
.
+-- debhello-1.6
|   +-- LICENSE
|   +-- Makefile.am
|   +-- README.md
|   +-- configure.ac
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- man
|       |   +-- Makefile.am
|       |   +-- hello.1
```

```
|   +-- src
|       +-- Makefile.am
|       +-- hello.c
+-- debhello-1.6.tar.xz
```

5 directories, 11 files

Here, the contents of this source are as follows.

src/hello.c (v=1.6):

```
[base_dir] $ cat debhello-1.6/src/hello.c
#include "config.h"
#ifdef WITH_MATH
# include <math.h>
#endif
#include <stdio.h>
int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\n");
#ifdef WITH_MATH
    printf("4.0 * atan(1.0) = %10f8\n", 4.0*atan(1.0));
#else
    printf("I can't do MATH!\n");
#endif
    return 0;
}
```

Makefile.am (v=1.6):

```
[base_dir] $ cat debhello-1.6/Makefile.am
SUBDIRS = src man
[base_dir] $ cat debhello-1.6/man/Makefile.am
dist_man_MANS = hello.1
[base_dir] $ cat debhello-1.6/src/Makefile.am
bin_PROGRAMS = hello
hello_SOURCES = hello.c
```

configure.ac (v=1.6):

```
[base_dir] $ cat debhello-1.6/configure.ac
#                                     -*- Autoconf -*-
# Process this file with autoconf to produce a configure script.
AC_PREREQ([2.69])
AC_INIT([debhello],[2.1],[foo@example.org])
AC_CONFIG_SRCDIR([src/hello.c])
AC_CONFIG_HEADERS([config.h])
echo "Standard customization chores"
AC_CONFIG_AUX_DIR([build-aux])
AM_INIT_AUTOMAKE([foreign])
# Add #define PACKAGE_AUTHOR ... in config.h with a comment
AC_DEFINE(PACKAGE_AUTHOR, ["Osamu Aoki"], [Define PACKAGE_AUTHOR])
echo "Add --with-math option functionality to ./configure"
AC_ARG_WITH([math],
    [AS_HELP_STRING([--with-math],
        [compile with math library @<:@default=yes@:>@])],
    [],
    [with_math="yes"])
echo "==== withval    := \"\$withval\""
echo "==== with_math := \"\$with_math\""
# m4sh if-else construct
AS_IF([test "x$with_math" != "xno"],[
    echo "==== Check include: math.h"
    AC_CHECK_HEADER(math.h,[],[
        AC_MSG_ERROR([Couldn't find math.h.] )
```

```

])
echo "==== Check library: libm"
AC_SEARCH_LIBS(atan, [m])
#AC_CHECK_LIB(m, atan)
echo "==== Build with LIBS := \"$LIBS\""
AC_DEFINE(WITH_MATH, [1], [Build with the math library])
],[
echo "==== Skip building with math.h."
AH_TEMPLATE(WITH_MATH, [Build without the math library])
])
# Checks for programs.
AC_PROG_CC
AC_CONFIG_FILES([Makefile
                  man/Makefile
                  src/Makefile])
AC_OUTPUT

```

Tipp



Without „**foreign**“ strictness level specified in **AM_INIT_AUTOMAKE()** as above, **automake** defaults to „**gnu**“ strictness level requiring several files in the top-level directory. See „3.2 Strictness“ in the **automake** document.

Let's package this with the **debmake** command.

```

[base_dir] $ cd debhello-1.6
[debhello-1.6] $ debmake -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-1.6] $ cd ..
I: Non-native Debian package pkg="debhello", ver="1.6", rev="1" method="dir_d...
I: already in the package-version form: "debhello-1.6"
I: [base_dir] $ ln -sf debhello-1.6.tar.xz debhello_1.6.orig.tar.xz
I: [base_dir] $ cd debhello-1.6
I: parsing option -b ""
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: build_type = Autotools with autoreconf
I: ext_type = am                      3 files
I: ext_type = c                      1 files
I: ext_type = 1                      1 files
I: creating debian/* files with "-x 1" option
I: [debhello-1.6] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
I: creating debian/rules from extra0_rules
I: creating debian/source/format from extra0source_format
...

```

The result is similar to „Abschnitt 14.8“ but not exactly the same.

Let's inspect the notable template files generated.

debian/rules (Vorlagendatei, v=1.6):

```

[base_dir] $ cd debhello-1.6
[debhello-1.6] $ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
# See debhelper(7) (un-comment to enable)
# This is an autogenerated template for debian/rules.
#

```

```

# Output every command that modifies files on the build system.
#export DH_VERBOSE = 1
#
# Copy some variable definitions from pkg-info.mk and vendor.mk
# under /usr/share/dpkg/ to here if they are useful.
#
# See FEATURE AREAS/ENVIRONMENT in dpkg-buildflags(1)
# Apply all hardening options
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
# Package maintainers to append CFLAGS
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
# Package maintainers to append LDFLAGS
#export DEB_LDFLAGS_MAINT_APPEND = -Wl,-O1
#
# With debhelper version 9 or newer, the dh command exports
# all buildflags. So there is no need to include the
# /usr/share/dpkg/buildflags.mk file here if compat is 9 or newer.
#
# These are rarely used code. (START)
#
# The following include for *.mk magically sets miscellaneous
# variables while honoring existing values of pertinent
# environment variables:
#
# Architecture-related variables such as DEB_TARGET_MULTIARCH:
#include /usr/share/dpkg/architecture.mk
# Vendor-related variables such as DEB_VENDOR:
#include /usr/share/dpkg/vendor.mk
# Package-related variables such as DEB_DISTRIBUTION
#include /usr/share/dpkg/pkg-info.mk
#
# You may alternatively set them using a simple script such as:
# DEB_VENDOR ?= $(shell dpkg-vendor --query Vendor)
#
# These are rarely used code. (END)
#

### main packaging script based on post dh7 syntax
%:
    dh $@ --with autoreconf

# debmake generated override targets
# Set options for ./configure
#CONFIGURE_FLAGS = <options for ./configure>
#override_dh_configure:
#    dh_configure -- $(CONFIGURE_FLAGS)
#
# Do not install libtool archive, python .pyc .pyo
#override_dh_install:
#    dh_install --list-missing -X.la -X.pyc -X.pyo

```

Let's make this Debian package better as the maintainer.

debian/rules (Betreuerversion, v=1.6):

```

[base_dir] $ cd debhello-1.6
[debhello-1.6] $ vim debian/rules
... hack, hack, hack, ...
[debhello-1.6] $ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:

```

```
dh $@ --with autoreconf

override_dh_auto_configure:
    dh_auto_configure -- \
        --with-math
```

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

The rest of the packaging activities are practically the same as the one in „Abschnitt 5.8“.

14.10 CMake (Paket mit einem Programm)

Here is an example of creating a simple Debian package from a simple C source program using CMake (**CMakeLists.txt** and some files such as **config.h.in**) as its build system.

The **cmake** command generates the **Makefile** file based on the **CMakeLists.txt** file and its **-D** option. It also configures the file as specified in its **configure_file(...)** by replacing strings with **@...@** and changing the **#cmakedefine ...** line.

Let's assume this upstream tarball to be **debhello-1.7.tar.xz**.

This type of source is meant to be installed as a non-system file, for example, as:

```
[base_dir] $ tar -xzmf debhello-1.7.tar.xz
[base_dir] $ cd debhello-1.7
[debhello-1.7] $ mkdir obj-x86_64-linux-gnu # for out-of-tree build
[debhello-1.7] $ cd obj-x86_64-linux-gnu
[debhello-1.7] $ cmake ..
[debhello-1.7] $ make
[debhello-1.7] $ make install
```

Let's get the source and make the Debian package.

Download debhello-1.7.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-1.7.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-1.7.tar.xz
[base_dir] $ tree
.
+-- debhello-1.7
|   +-- CMakeLists.txt
|   +-- LICENSE
|   +-- README.md
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- man
|       |   +-- CMakeLists.txt
|       |   +-- hello.1
|   +-- src
|       +-- CMakeLists.txt
|       +-- config.h.in
|       +-- hello.c
+-- debhello-1.7.tar.xz

5 directories, 11 files
```

Here, the contents of this source are as follows.

src/hello.c (v=1.7):

```
[base_dir] $ cat debhello-1.7/src/hello.c
#include "config.h"
#ifdef WITH_MATH
# include <math.h>
#endif
#include <stdio.h>
```



```

int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\n");
#ifdef WITH_MATH
    printf("4.0 * atan(1.0) = %10f8\n", 4.0*atan(1.0));
#else
    printf("I can't do MATH!\n");
#endif
    return 0;
}

```

src/config.h.in (v=1.7):

```

[base_dir] $ cat debhello-1.7/src/config.h.in
/* name of the package author */
#define PACKAGE_AUTHOR "@PACKAGE_AUTHOR@"
/* math library support */
#cmakedefine WITH_MATH

```

CMakeLists.txt (v=1.7):

```

[base_dir] $ cat debhello-1.7/CMakeLists.txt
cmake_minimum_required(VERSION 3.31)
project(debhello)
set(PACKAGE_AUTHOR "Osamu Aoki")
add_subdirectory(src)
add_subdirectory(man)
[base_dir] $ cat debhello-1.7/man/CMakeLists.txt
install(
    FILES ${CMAKE_CURRENT_SOURCE_DIR}/hello.1
    DESTINATION share/man/man1
)
[base_dir] $ cat debhello-1.7/src/CMakeLists.txt
# Always define HAVE_CONFIG_H
add_definitions(-DHAVE_CONFIG_H)
# Interactively define WITH_MATH
option(WITH_MATH "Build with math support" OFF)
#variable_watch(WITH_MATH)
# Generate config.h from config.h.in
configure_file(
    "${CMAKE_CURRENT_SOURCE_DIR}/config.h.in"
    "${CMAKE_CURRENT_BINARY_DIR}/config.h"
)
include_directories("${CMAKE_CURRENT_BINARY_DIR}")
add_executable(hello hello.c)
install(TARGETS hello
    RUNTIME DESTINATION bin
)

```

Let's package this with the **debmake** command.

```

[base_dir] $ cd debhello-1.7
[debhello-1.7] $ debmake -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-1.7] $ cd ..
I: Non-native Debian package pkg="debhello", ver="1.7", rev="1" method="dir_d...
I: already in the package-version form: "debhello-1.7"
I: [base_dir] $ ln -sf debhello-1.7.tar.xz debhello_1.7.orig.tar.xz
I: [base_dir] $ cd debhello-1.7
I: parsing option -b ""
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: build_type = Cmake
I: ext_type = c                2 files
I: ext_type = 1                1 files

```

```

I: ext_type = desktop          1 files
I: creating debian/* files with "-x 1" option
I: [debhello-1.7] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
I: creating debian/rules from extra0_rules
I: creating debian/source/format from extra0source_format
...

```

The result is similar to „Abschnitt 14.8“ but not exactly the same.

Let's inspect the notable template files generated.

debian/rules (Vorlagendatei, v=1.7):

```

[base_dir] $ cd debhello-1.7
[debhello-1.7] $ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
# See debhelper(7) (un-comment to enable)
# This is an autogenerated template for debian/rules.
#
# Output every command that modifies files on the build system.
#export DH_VERBOSE = 1
#
# Copy some variable definitions from pkg-info.mk and vendor.mk
# under /usr/share/dpkg/ to here if they are useful.
#
# See FEATURE AREAS/ENVIRONMENT in dpkg-buildflags(1)
# Apply all hardening options
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
# Package maintainers to append CFLAGS
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
# Package maintainers to append LDFLAGS
#export DEB_LDFLAGS_MAINT_APPEND = -Wl,-O1
#
# With debhelper version 9 or newer, the dh command exports
# all buildflags. So there is no need to include the
# /usr/share/dpkg/buildflags.mk file here if compat is 9 or newer.
#
# These are rarely used code. (START)
#
# The following include for *.mk magically sets miscellaneous
# variables while honoring existing values of pertinent
# environment variables:
#
# Architecture-related variables such as DEB_TARGET_MULTIARCH:
#include /usr/share/dpkg/architecture.mk
# Vendor-related variables such as DEB_VENDOR:
#include /usr/share/dpkg/vendor.mk
# Package-related variables such as DEB_DISTRIBUTION
#include /usr/share/dpkg/pkg-info.mk
#
# You may alternatively set them using a simple script such as:
# DEB_VENDOR ?= $(shell dpkg-vendor --query Vendor)
#
# These are rarely used code. (END)
#

### main packaging script based on post dh7 syntax
%:
    dh $@

# debmake generated override targets

```

```
#override_dh_auto_configure:
#     dh_auto_configure -- \
#         -DCMAKE_LIBRARY_ARCHITECTURE="$(DEB_TARGET_MULTIARCH)"
#
# You may need to patch CMakeLists.txt to set the library install path to be:...
#-install(TARGETS <sharedlibname> LIBRARY DESTINATION lib)
#+install(TARGETS <sharedlibname> LIBRARY DESTINATION lib/${CMAKE_LIBRARY_ARC...

# Multiarch package requires library files to be installed to
# /usr/lib/<triplet>/ . If the build system does not support
# $(DEB_HOST_MULTIARCH), you may need to override some targets such as
# dh_auto_configure or dh_auto_install to use $(DEB_HOST_MULTIARCH) .
```

debian/control (template file, v=1.7):

```
[debhello-1.7] $ cat debian/control
Source: debhello
Section: unknown
Priority: optional
Maintainer: "Osamu Aoki" <osamu@debian.org>
Build-Depends:
    debhelper-compat (= 13),
    cmake,
Standards-Version: 4.7.3
Homepage: <insert the upstream URL, if relevant>
Rules-Requires-Root: no
#Vcs-Git: https://salsa.debian.org/debian/debhello.git
#Vcs-Browser: https://salsa.debian.org/debian/<project_site>

Package: debhello
Section: unknown
Architecture: any
Multi-Arch: foreign
Depends:
    ${misc:Depends},
    ${shlibs:Depends},
Description: auto-generated package by debmake
    This Debian binary package was auto-generated by the
    debmake(1) command provided by the debmake package.
.
==== This comes from the unmodified template file ====
.
Please edit this template file (debian/control) and other package files
(debian/*) to make them meet all the requirements of the Debian Policy
before uploading this package to the Debian archive.
.
See
* https://www.debian.org/doc/manuals/developers-reference/best-pkging-pract...
* https://www.debian.org/doc/manuals/debmake-doc/ch05.en.html#control
.
The synopsis description at the top should be about 60 characters and
written as a phrase. No extra capital letters or a final period. No
articles b''-b'' "a", "an", or "the".
.
The package description for general-purpose applications should be
written for a less technical user. This means that we should avoid
jargon. GNOME or KDE is fine but GTK+ is probably not.
.
Use the canonical forms of words:
* Use X Window System, X11, or X; not X Windows, X-Windows, or X Window.
* Use GTK+, not GTK or gtk.
* Use GNOME, not Gnome.
* Use PostScript, not Postscript or postscript.
```

Let's make this Debian package better as the maintainer.

debian/rules (Betreuerversion, v=1.7):

```
[base_dir] $ cd debhello-1.7
[debhello-1.7] $ vim debian/rules
... hack, hack, hack, ...
[debhello-1.7] $ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@

override_dh_auto_configure:
    dh_auto_configure -- -DWITH-MATH=1
```

debian/control (Betreuerversion, v=1.7):

```
[debhello-1.7] $ vim debian/control
... hack, hack, hack, ...
[debhello-1.7] $ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends:
    debhelper-compat (= 13),
    cmake,
Standards-Version: 4.7.3
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello
Architecture: any
Multi-Arch: foreign
Depends:
    ${misc:Depends},
    ${shlibs:Depends},
Description: Simple packaging example for debmake
    This Debian binary package is an example package.
    (This is an example only)
```

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

The rest of the packaging activities are practically the same as the one in „Abschnitt 14.8“.

14.11 Autotools (Paket mit mehreren Programmen)

Here is an example of creating a set of Debian binary packages including the executable package, the shared library package, the development file package, and the debug symbol package from a simple C source program using Autotools (Autoconf and Automake, which use **Makefile.am** and **configure.ac** as their input files) as its build system.

Let's package this in a similar way to „Abschnitt 14.9“.

Let's assume this upstream tarball to be **debhello-2.0.tar.xz**.

This type of source is meant to be installed as a non-system file, for example, as:

```
[base_dir] $ tar -xzmf debhello-2.0.tar.xz
[base_dir] $ cd debhello-2.0
[debhello-2.0] $ autoreconf -ivf # optional
[debhello-2.0] $ ./configure --with-math
[debhello-2.0] $ make
```

```
[debhello-2.0] $ make install
```

Let's get the source and make the Debian package.

Download debhello-2.0.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-2.0.tar.xz
```

```
...
```

```
[base_dir] $ tar --xz -xmf debhello-2.0.tar.xz
```

```
[base_dir] $ tree
```

```
.
+-- debhello-2.0
|   +-- LICENSE
|   +-- Makefile.am
|   +-- README.md
|   +-- configure.ac
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- lib
|       |   +-- Makefile.am
|       |   +-- sharedlib.c
|       |   +-- sharedlib.h
|   +-- man
|       |   +-- Makefile.am
|       |   +-- hello.1
|   +-- src
|       +-- Makefile.am
|       +-- hello.c
+-- debhello-2.0.tar.xz
```

```
6 directories, 14 files
```

Here, the contents of this source are as follows.

src/hello.c (v=2.0):

```
[base_dir] $ cat debhello-2.0/src/hello.c
#include "config.h"
#include <stdio.h>
#include <sharedlib.h>
int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\n");
    sharedlib();
    return 0;
}
```

lib/sharedlib.h und lib/sharedlib.c (v=1.6):

```
[base_dir] $ cat debhello-2.0/lib/sharedlib.h
int sharedlib();
[base_dir] $ cat debhello-2.0/lib/sharedlib.c
#include <stdio.h>
int
sharedlib()
{
    printf("This is a shared library!\n");
    return 0;
}
```

Makefile.am (v=2.0):

```
[base_dir] $ cat debhello-2.0/Makefile.am
# recursively process `Makefile.am` in SUBDIRS
SUBDIRS = lib src man
[base_dir] $ cat debhello-2.0/man/Makefile.am
```

```
# manpages (distributed in the source package)
dist_man_MANS = hello.1
[base_dir] $ cat debhello-2.0/lib/Makefile.am
# libtool libraries to be produced
lib_LTLIBRARIES = libsharedlib.la

# source files used for lib_LTLIBRARIES
libsharedlib_la_SOURCES = sharedlib.c

# C pre-processor flags used for lib_LTLIBRARIES
#libsharedlib_la_CPPFLAGS =

# Headers files to be installed in <prefix>/include
include_HEADERS = sharedlib.h

# Versioning Libtool Libraries with version triplets
libsharedlib_la_LDFLAGS = -version-info 1:0:0
[base_dir] $ cat debhello-2.0/src/Makefile.am
# program executables to be produced
bin_PROGRAMS = hello

# source files used for bin_PROGRAMS
hello_SOURCES = hello.c

# C pre-processor flags used for bin_PROGRAMS
AM_CPPFLAGS = -I$(srcdir) -I$(top_srcdir)/lib

# Extra options for the linker for hello
# hello_LDFLAGS =

# Libraries the `hello` binary to be linked
hello_LDADD = $(top_srcdir)/lib/libsharedlib.la
```

configure.ac (v=2.0):

```
[base_dir] $ cat debhello-2.0/configure.ac
#                                     -*- Autoconf -*-
# Process this file with autoconf to produce a configure script.
AC_PREREQ([2.69])
AC_INIT([debhello],[2.2],[foo@example.org])
AC_CONFIG_SRCDIR([src/hello.c])
AC_CONFIG_HEADERS([config.h])
echo "Standard customization chores"
AC_CONFIG_AUX_DIR([build-aux])

AM_INIT_AUTOMAKE([foreign])

# Set default to --enable-shared --disable-static
LT_INIT([shared disable-static])

# find the libltdl sources in the libltdl sub-directory
LT_CONFIG_LTDL_DIR([libltdl])

# choose one
LTDL_INIT([recursive])
#LTDL_INIT([subproject])
#LTDL_INIT([nonrecursive])

# Add #define PACKAGE_AUTHOR ... in config.h with a comment
AC_DEFINE(PACKAGE_AUTHOR, ["Osamu Aoki"], [Define PACKAGE_AUTHOR])
# Checks for programs.
AC_PROG_CC

# only for the recursive case
AC_CONFIG_FILES([Makefile
```

```
lib/Makefile
man/Makefile
src/Makefile])
AC_OUTPUT
```

Let's use the **debmake** command to package this into multiple packages:

- **debhello**: type = **bin**
- **libsharedlib1**: type = **lib**
- **libsharedlib-dev**: type = **dev**

Here, we use the **-b'libsharedlib1,libsharedlib-dev'** option to specify the additional binary packages to be generated.

```
[base_dir] $ cd debhello-2.0
[debhello-2.0] $ debmake -b',libsharedlib1,libsharedlib-dev' -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-2.0] $ cd ..
I: Non-native Debian package pkg="debhello", ver="2.0", rev="1" method="dir_d...
I: already in the package-version form: "debhello-2.0"
I: [base_dir] $ ln -sf debhello-2.0.tar.xz debhello_2.0.orig.tar.xz
I: [base_dir] $ cd debhello-2.0
I: parsing option -b ",libsharedlib1,libsharedlib-dev"
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: binary package=libsharedlib1 Type=lib / Arch=any M-A=same
I: binary package=libsharedlib-dev Type=dev / Arch=any M-A=same
I: build_type = Autotools with autoreconf
I: ext_type = am                      4 files
I: ext_type = c                      3 files
I: ext_type = 1                      1 files
I: creating debian/* files with "-x 1" option
I: [debhello-2.0] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
...
```

The result is similar to „Abschnitt 14.8“ but with more template files.

Let's inspect the notable template files generated.

debian/rules (Vorlagendatei, v=2.0):

```
[base_dir] $ cd debhello-2.0
[debhello-2.0] $ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
# See debhelper(7) (un-comment to enable)
# This is an autogenerated template for debian/rules.
#
# Output every command that modifies files on the build system.
#export DH_VERBOSE = 1
#
# Copy some variable definitions from pkg-info.mk and vendor.mk
# under /usr/share/dpkg/ to here if they are useful.
#
# See FEATURE AREAS/ENVIRONMENT in dpkg-buildflags(1)
# Apply all hardening options
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
# Package maintainers to append CFLAGS
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
# Package maintainers to append LDFLAGS
#export DEB_LDFLAGS_MAINT_APPEND = -Wl,-O1
#
```

```
# With debhelper version 9 or newer, the dh command exports
# all buildflags. So there is no need to include the
# /usr/share/dpkg/buildflags.mk file here if compat is 9 or newer.
#
# These are rarely used code. (START)
#
# The following include for *.mk magically sets miscellaneous
# variables while honoring existing values of pertinent
# environment variables:
#
# Architecture-related variables such as DEB_TARGET_MULTIARCH:
#include /usr/share/dpkg/architecture.mk
# Vendor-related variables such as DEB_VENDOR:
#include /usr/share/dpkg/vendor.mk
# Package-related variables such as DEB_DISTRIBUTION
#include /usr/share/dpkg/pkg-info.mk
#
# You may alternatively set them using a simple script such as:
# DEB_VENDOR ?= $(shell dpkg-vendor --query Vendor)
#
# These are rarely used code. (END)
#

### main packaging script based on post dh7 syntax
%:
    dh $@ --with autoreconf

# debmake generated override targets
# Set options for ./configure
#CONFIGURE_FLAGS = <options for ./configure>
#override_dh_configure:
#    dh_configure -- $(CONFIGURE_FLAGS)
#
# Do not install libtool archive, python .pyc .pyo
#override_dh_install:
#    dh_install --list-missing -X.la -X.pyc -X.pyo
```

Let's make this Debian package better as the maintainer.

debian/rules (Betreuerversion, v=2.0):

```
[base_dir] $ cd debhello-2.0
[debhello-2.0] $ vim debian/rules
... hack, hack, hack, ...
[debhello-2.0] $ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed

%:
    dh $@ --with autoreconf

override_dh_missing:
    dh_missing -X.la
```

debian/control (Betreuerversion, v=2.0):

```
[debhello-2.0] $ vim debian/control
... hack, hack, hack, ...
[debhello-2.0] $ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
```



```
Build-Depends:
  debhelper-compat (= 13),
  dh-autoreconf,
Standards-Version: 4.7.3
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no
```

```
Package: debhello
Architecture: any
Multi-Arch: foreign
Depends:
  libsharedlib1 (= ${binary:Version}),
  ${misc:Depends},
  ${shlibs:Depends},
Description: Simple packaging example for debmake
  This package contains the compiled binary executable.
.
  This Debian binary package is an example package.
  (This is an example only)
```

```
Package: libsharedlib1
Section: libs
Architecture: any
Multi-Arch: same
Pre-Depends:
  ${misc:Pre-Depends},
Depends:
  ${misc:Depends},
  ${shlibs:Depends},
Description: Simple packaging example for debmake
  This package contains the shared library.
```

```
Package: libsharedlib-dev
Section: libdevel
Architecture: any
Multi-Arch: same
Depends:
  libsharedlib1 (= ${binary:Version}),
  ${misc:Depends},
Description: Simple packaging example for debmake
  This package contains the development files.
```

debian/*.install (Betreuerversion, v=2.0):

```
[debhello-2.0] $ vim debian/copyright
... hack, hack, hack, ...
[debhello-2.0] $ cat debian/copyright
Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: debhello
Upstream-Contact: Osamu Aoki <osamu@debian.org>
Source: https://salsa.debian.org/debian/debmake-doc

Files:      *
Copyright: 2015-2021 Osamu Aoki <osamu@debian.org>
License:    Expat
Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:
.
The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.
.
```

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Since this upstream source creates the proper auto-generated **Makefile**, there is no need to create **debian/install** and **debian/manpages** files.

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

Vorlagendateien unter debian/. (v=2.0):

```
[debhello-2.0] $ rm -f debian/clean debian/dirs debian/install debian/links
[debhello-2.0] $ rm -f debian/README.source debian/source/*.ex
[debhello-2.0] $ rm -rf debian/patches
[debhello-2.0] $ tree -F debian
debian/
+-- README.Debian
+-- changelog
+-- control
+-- copyright
+-- debhello.install
+-- docs
+-- examples
+-- gbp.conf
+-- libsharedlib-dev.install
+-- libsharedlib1.install
+-- libsharedlib1.symbols
+-- manpages
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

4 directories, 18 files
```

The rest of the packaging activities are practically the same as the one in „Abschnitt 14.8“.

Here are the generated dependency list of all binary packages.

The generated dependency list of all binary packages (v=2.0):

```
[debhello-2.0] $ dpkg -f debhello-dbgsym_2.0-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: debhello (= 2.0-1)
[debhello-2.0] $ dpkg -f debhello_2.0-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.0-1), libc6 (>= 2.34)
[debhello-2.0] $ dpkg -f libsharedlib-dev_2.0-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.0-1)
[debhello-2.0] $ dpkg -f libsharedlib1-dbgsym_2.0-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.0-1)
[debhello-2.0] $ dpkg -f libsharedlib1_2.0-1_amd64.deb pre-depends \
    depends recommends conflicts breaks
Depends: libc6 (>= 2.2.5)
```

14.12 CMake (multi-binary package)

This example demonstrates creating a set of Debian binary packages including the executable package, the shared library package, the development file package, and the debug symbol package from a simple C source program using CMake (**CMakeLists.txt** and files such as **config.h.in**) as its build system.

Let's assume this upstream tarball to be **debhello-2.1.tar.xz**.

This type of source is meant to be installed as a non-system file, for example, as:

```
[base_dir] $ tar -xzmf debhello-2.1.tar.xz
[base_dir] $ cd debhello-2.1
[debhello-2.1] $ mkdir obj-x86_64-linux-gnu
[debhello-2.1] $ cd obj-x86_64-linux-gnu
[debhello-2.1] $ cmake ..
[debhello-2.1] $ make
[debhello-2.1] $ make install
```

Let's get the source and make the Debian package.

Download debhello-2.1.tar.xz

```
[base_dir] $ wget http://www.example.org/download/debhello-2.1.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-2.1.tar.xz
[base_dir] $ tree
.
+-- debhello-2.1
|   +-- CMakeLists.txt
|   +-- LICENSE
|   +-- README.md
|   +-- data
|       |   +-- hello.desktop
|       |   +-- hello.png
|   +-- lib
|       |   +-- CMakeLists.txt
|       |   +-- sharedlib.c
|       |   +-- sharedlib.h
|   +-- man
|       |   +-- CMakeLists.txt
|       |   +-- hello.1
|   +-- src
|       +-- CMakeLists.txt
|       +-- config.h.in
|       +-- hello.c
+-- debhello-2.1.tar.xz

6 directories, 14 files
```

Here, the contents of this source are as follows.

src/hello.c (v=2.1):

```
[base_dir] $ cat debhello-2.1/src/hello.c
#include "config.h"
#include <stdio.h>
#include <sharedlib.h>
int
main()
{
    printf("Hello, I am " PACKAGE_AUTHOR "!\n");
    sharedlib();
    return 0;
}
```

src/config.h.in (v=2.1):

```
[base_dir] $ cat debhello-2.1/src/config.h.in
/* name of the package author */
#define PACKAGE_AUTHOR "@PACKAGE_AUTHOR@"
```

lib/sharedlib.c und lib/sharedlib.h (v=2.1):

```
[base_dir] $ cat debhello-2.1/lib/sharedlib.h
int sharedlib();
[base_dir] $ cat debhello-2.1/lib/sharedlib.c
#include <stdio.h>
int
sharedlib()
{
    printf("This is a shared library!\n");
    return 0;
}
```

CMakeLists.txt (v=2.1):

```
[base_dir] $ cat debhello-2.1/CMakeLists.txt
cmake_minimum_required(VERSION 3.31)
project(debhello)
set(PACKAGE_AUTHOR "Osamu Aoki")
add_subdirectory(lib)
add_subdirectory(src)
add_subdirectory(man)
[base_dir] $ cat debhello-2.1/man/CMakeLists.txt
install(
    FILES ${CMAKE_CURRENT_SOURCE_DIR}/hello.1
    DESTINATION share/man/man1
)
[base_dir] $ cat debhello-2.1/src/CMakeLists.txt
# Always define HAVE_CONFIG_H
add_definitions(-DHAVE_CONFIG_H)
# Generate config.h from config.h.in
configure_file(
    "${CMAKE_CURRENT_SOURCE_DIR}/config.h.in"
    "${CMAKE_CURRENT_BINARY_DIR}/config.h"
)
include_directories("${CMAKE_CURRENT_BINARY_DIR}")
include_directories("${CMAKE_SOURCE_DIR}/lib")

add_executable(hello hello.c)
target_link_libraries(hello sharedlib)
install(TARGETS hello
    RUNTIME DESTINATION bin
)
```

Let's package this with the **debmake** command.

```
[base_dir] $ cd debhello-2.1
[debhello-2.1] $ debmake -b',libsharedlib1,libsharedlib-dev' -x1
I: debmake (version: 5.1.2)
I: Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>
I: [debhello-2.1] $ cd ..
I: Non-native Debian package pkg="debhello", ver="2.1", rev="1" method="dir_d...
I: already in the package-version form: "debhello-2.1"
I: [base_dir] $ ln -sf debhello-2.1.tar.xz debhello_2.1.orig.tar.xz
I: [base_dir] $ cd debhello-2.1
I: parsing option -b ',libsharedlib1,libsharedlib-dev'
I: binary package=debhello Type=bin / Arch=any M-A=foreign
I: binary package=libsharedlib1 Type=lib / Arch=any M-A=same
I: binary package=libsharedlib-dev Type=dev / Arch=any M-A=same
I: build_type = Cmake
I: ext_type = c                                4 files
I: ext_type = 1                                1 files
I: ext_type = desktop                           1 files
I: creating debian/* files with "-x 1" option
I: [debhello-2.1] $ licensecheck --recursive --copyright --deb-machine . > d...
I: creating debian/copyright by licensecheck.
```

```
I: creating debian/control from control.py
I: creating debian/control by control.py
I: creating debian/changelog from extra0_changelog
...
```

The result is similar to „Abschnitt 14.8“ but not exactly the same.

Let's inspect the notable template files generated.

debian/rules (Vorlagendatei, v=2.1):

```
[base_dir] $ cd debhello-2.1
[debhello-2.1] $ cat debian/rules
#!/usr/bin/make -f
# You must remove unused comment lines for the released package.
# See debhelper(7) (un-comment to enable)
# This is an autogenerated template for debian/rules.
#
# Output every command that modifies files on the build system.
#export DH_VERBOSE = 1
#
# Copy some variable definitions from pkg-info.mk and vendor.mk
# under /usr/share/dpkg/ to here if they are useful.
#
# See FEATURE AREAS/ENVIRONMENT in dpkg-buildflags(1)
# Apply all hardening options
#export DEB_BUILD_MAINT_OPTIONS = hardening=+all
# Package maintainers to append CFLAGS
#export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
# Package maintainers to append LDFLAGS
#export DEB_LDFLAGS_MAINT_APPEND = -Wl,-O1
#
# With debhelper version 9 or newer, the dh command exports
# all buildflags. So there is no need to include the
# /usr/share/dpkg/buildflags.mk file here if compat is 9 or newer.
#
# These are rarely used code. (START)
#
# The following include for *.mk magically sets miscellaneous
# variables while honoring existing values of pertinent
# environment variables:
#
# Architecture-related variables such as DEB_TARGET_MULTIARCH:
#include /usr/share/dpkg/architecture.mk
# Vendor-related variables such as DEB_VENDOR:
#include /usr/share/dpkg/vendor.mk
# Package-related variables such as DEB_DISTRIBUTION
#include /usr/share/dpkg/pkg-info.mk
#
# You may alternatively set them using a simple script such as:
# DEB_VENDOR ?= $(shell dpkg-vendor --query Vendor)
#
# These are rarely used code. (END)
#

### main packaging script based on post dh7 syntax
%:
    dh $@

# debmake generated override targets
#override_dh_auto_configure:
#    dh_auto_configure -- \
#        -DCMAKE_LIBRARY_ARCHITECTURE="$(DEB_TARGET_MULTIARCH)"
#
# You may need to patch CMakeLists.txt to set the library install path to be:...
#-install(TARGETS <sharedlibname> LIBRARY DESTINATION lib)
```

```

#+install(TARGETS <sharedlibname> LIBRARY DESTINATION lib/${CMAKE_LIBRARY_ARC...

# Multiarch package requires library files to be installed to
# /usr/lib/<triplet>/ . If the build system does not support
# $(DEB_HOST_MULTIARCH), you may need to override some targets such as
# dh_auto_configure or dh_auto_install to use $(DEB_HOST_MULTIARCH) .

```

Let's make this Debian package better as the maintainer.

debian/rules (Betreuerversion, v=2.1):

```

[base_dir] $ cd debhello-2.1
[debhello-2.1] $ vim debian/rules
... hack, hack, hack, ...
[debhello-2.1] $ cat debian/rules
#!/usr/bin/make -f
export DH_VERBOSE = 1
export DEB_BUILD_MAINT_OPTIONS = hardening=+all
export DEB_CFLAGS_MAINT_APPEND = -Wall -pedantic
export DEB_LDFLAGS_MAINT_APPEND = -Wl,--as-needed
DEB_HOST_MULTIARCH ?= $(shell dpkg-architecture -qDEB_HOST_MULTIARCH)

%:
    dh $@

override_dh_auto_configure:
    dh_auto_configure -- \
        -DCMAKE_LIBRARY_ARCHITECTURE="$(DEB_HOST_MULTIARCH)"

```

debian/control (Betreuerversion, v=2.1):

```

[debhello-2.1] $ vim debian/control
... hack, hack, hack, ...
[debhello-2.1] $ cat debian/control
Source: debhello
Section: devel
Priority: optional
Maintainer: Osamu Aoki <osamu@debian.org>
Build-Depends:
    debhelper-compat (= 13),
    cmake,
Standards-Version: 4.7.3
Homepage: https://salsa.debian.org/debian/debmake-doc
Rules-Requires-Root: no

Package: debhello
Architecture: any
Multi-Arch: foreign
Depends:
    libsharedlib1 (= ${binary:Version}),
    ${misc:Depends},
    ${shlibs:Depends},
Description: Simple packaging example for debmake
    This package contains the compiled binary executable.
.
    This Debian binary package is an example package.
    (This is an example only)

Package: libsharedlib1
Section: libs
Architecture: any
Multi-Arch: same
Pre-Depends:
    ${misc:Pre-Depends},
Depends:
    ${misc:Depends},

```

```

${shlibs:Depends},
Description: Simple packaging example for debmake
    This package contains the shared library.

Package: libsharedlib-dev
Section: libdevel
Architecture: any
Multi-Arch: same
Depends:
    libsharedlib1 (= ${binary:Version}),
    ${misc:Depends},
Description: Simple packaging example for debmake
    This package contains the development files.

```

debian/*.install (Betreuerversion, v=2.1):

```

[debhhello-2.1] $ vim debian/copyright
... hack, hack, hack, ...
[debhhello-2.1] $ cat debian/copyright
Format: https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: debhhello
Upstream-Contact: Osamu Aoki <osamu@debian.org>
Source: https://salsa.debian.org/debian/debmake-doc

Files:      *
Copyright:  2015-2021 Osamu Aoki <osamu@debian.org>
License:     Expat
Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:
.
The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.
.
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

```

The upstream CMakeLists.txt file needs to be patched to handle the multiarch path correctly.

debian/patches/* (Betreuerversion, v=2.1):

```

... hack, hack, hack, ...
[debhhello-2.1] $ cat debian/libsharedlib1.symbols
libsharedlib.so.1 libsharedlib1 #MINVER#
sharedlib@Base 2.1

```

Since this upstream source creates the proper auto-generated **Makefile**, there is no need to create **debian/install** and **debian/manpages** files.

Es gibt eine Reihe von weiteren Vorlagendateien unter dem Verzeichnis **debian/**. Diese müssen auch aktualisiert werden.

Vorlagendateien unter debian/. (v=2.1):

```

[debhhello-2.1] $ rm -f debian/clean debian/dirs debian/install debian/links
[debhhello-2.1] $ rm -f debian/README.source debian/source/*.ex
[debhhello-2.1] $ tree -F debian
debian/
+-- README.Debian
+-- changelog

```

```

+-- control
+-- copyright
+-- debhello.install
+-- docs
+-- examples
+-- gbp.conf
+-- libsharedlib-dev.install
+-- libsharedlib1.install
+-- libsharedlib1.symbols
+-- manpages
+-- patches/
|   +-- 000-cmake-multiarch.patch
|   +-- series
+-- rules*
+-- salsa-ci.yml
+-- source/
|   +-- format
+-- tests/
|   +-- control
+-- upstream/
|   +-- metadata
+-- watch

```

5 directories, 20 files

The rest of the packaging activities are practically the same as the one in „Abschnitt 14.8“.

Here are the generated dependency list of all binary packages.

The generated dependency list of all binary packages (v=2.1):

```

[debhello-2.1] $ dpkg -f debhello-dbgsym_2.1-1_amd64.deb pre-depends \
                depends recommends conflicts breaks
Depends: debhello (= 2.1-1)
[debhello-2.1] $ dpkg -f debhello_2.1-1_amd64.deb pre-depends \
                depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.1-1), libc6 (>= 2.34)
[debhello-2.1] $ dpkg -f libsharedlib-dev_2.1-1_amd64.deb pre-depends \
                depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.1-1)
[debhello-2.1] $ dpkg -f libsharedlib1-dbgsym_2.1-1_amd64.deb pre-depends \
                depends recommends conflicts breaks
Depends: libsharedlib1 (= 2.1-1)
[debhello-2.1] $ dpkg -f libsharedlib1_2.1-1_amd64.deb pre-depends \
                depends recommends conflicts breaks
Depends: libc6 (>= 2.2.5)

```

14.13 Internationalization

Here is an example of updating the simple upstream C source **debhello-2.0.tar.xz** presented in „Abschnitt 14.11“ for internationalization (i18n) and creating the updated upstream C source **debhello-2.0.tar.xz**.

In the real situation, the package should already be internationalized. So this example is educational for you to understand how this internationalization is implemented.

Tipp



The routine maintainer activity for the i18n is simply to add translation po files reported to you via the Bug Tracking System (BTS) to the **po/** directory and to update the language list in the **po/LINGUAS** file.

Let's get the source and make the Debian package.

Download debhello-2.0.tar.xz (i18n)

```
[base_dir] $ wget http://www.example.org/download/debhello-2.0.tar.xz
...
[base_dir] $ tar --xz -xmf debhello-2.0.tar.xz
[base_dir] $ tree
.
+-- debhello-2.0
|   +-- LICENSE
|   +-- Makefile.am
|   +-- README.md
|   +-- configure.ac
|   +-- data
|       | +-- hello.desktop
|       | +-- hello.png
|   +-- lib
|       | +-- Makefile.am
|       | +-- sharedlib.c
|       | +-- sharedlib.h
|   +-- man
|       | +-- Makefile.am
|       | +-- hello.1
|   +-- src
|       +-- Makefile.am
|       +-- hello.c
+-- debhello-2.0.tar.xz

6 directories, 14 files
```

Internationalize this source tree with the **gettextize** command and remove files auto-generated by Autotools.

run gettextize (i18n):

```
[base_dir] $ cd debhello-2.0
$ gettextize
Creating po/ subdirectory
Creating build-aux/ subdirectory
Copying file ABOUT-NLS
Copying file build-aux/config.rpath
Not copying intl/ directory.
Copying file po/Makefile.in.in
Copying file po/Makevars.template
Copying file po/Rules-quot
Copying file po/boldquot.sed
Copying file po/en@boldquot.header
Copying file po/en@quot.header
Copying file po/insert-header.sin
Copying file po/quot.sed
Copying file po/remove-potcdate.sin
Creating initial po/POTFILES.in
Creating po/ChangeLog
Creating directory m4
Copying file m4/gettext.m4
Copying file m4/iconv.m4
Copying file m4/lib-ld.m4
Copying file m4/lib-link.m4
Copying file m4/lib-prefix.m4
Copying file m4/nls.m4
Copying file m4/po.m4
Copying file m4/progtest.m4
Creating m4/ChangeLog
Updating Makefile.am (backup is in Makefile.am~)
Updating configure.ac (backup is in configure.ac~)
Creating ChangeLog
```

Please use `AM_GNU_GETTEXT([external])` in order to cause autoconfiguration to look for an external `libintl`.

Please create `po/Makevars` from the template in `po/Makevars.template`. You can then remove `po/Makevars.template`.

Please fill `po/POTFILES.in` as described in the documentation.

Please run `'aclocal'` to regenerate the `aclocal.m4` file. You need `aclocal` from GNU automake 1.9 (or newer) to do this. Then run `'autoconf'` to regenerate the `configure` file.

You will also need `config.guess` and `config.sub`, which you can get from the CV... of the `'config'` project at <http://savannah.gnu.org/>. The commands to fetch th... are

```
$ wget 'http://savannah.gnu.org/cgi-bin/viewcvs/*checkout*/config/config/conf...'
$ wget 'http://savannah.gnu.org/cgi-bin/viewcvs/*checkout*/config/config/conf...'
```

You might also want to copy the convenience header file `gettext.h` from the `/usr/share/gettext` directory into your package. It is a wrapper around `<libintl.h>` that implements the `configure --disable-nl...` option.

Press Return to acknowledge the previous 6 paragraphs.
[debhhello-2.0] \$ rm -rf m4 build-aux *~

Let's check generated files under the **po/** directory.

Dateien in po (i18n):

```
[debhhello-2.0] $ ls -l po
total 60
-rw-rw-r-- 1 osamu osamu 494 Feb 3 08:57 ChangeLog
-rw-rw-r-- 1 osamu osamu 17577 Feb 3 08:57 Makefile.in.in
-rw-rw-r-- 1 osamu osamu 3376 Feb 3 08:57 Makevars.template
-rw-rw-r-- 1 osamu osamu 59 Feb 3 08:57 POTFILES.in
-rw-rw-r-- 1 osamu osamu 2203 Feb 3 08:57 Rules-quot
-rw-rw-r-- 1 osamu osamu 217 Feb 3 08:57 boldquot.sed
-rw-rw-r-- 1 osamu osamu 1337 Feb 3 08:57 en@boldquot.header
-rw-rw-r-- 1 osamu osamu 1203 Feb 3 08:57 en@quot.header
-rw-rw-r-- 1 osamu osamu 672 Feb 3 08:57 insert-header.sin
-rw-rw-r-- 1 osamu osamu 153 Feb 3 08:57 quot.sed
-rw-rw-r-- 1 osamu osamu 432 Feb 3 08:57 remove-potcdate.sin
```

Let's update the **configure.ac** by adding `„AM_GNU_GETTEXT([external])“`, etc..

configure.ac (i18n):

```
[debhhello-2.0] $ vim configure.ac
... hack, hack, hack, ...
[debhhello-2.0] $ cat configure.ac
#                                     -*- Autoconf -*-
# Process this file with autoconf to produce a configure script.
AC_PREREQ([2.69])
AC_INIT([debhhello],[2.2],[foo@example.org])
AC_CONFIG_SRCDIR([src/hello.c])
AC_CONFIG_HEADERS([config.h])
echo "Standard customization chores"
AC_CONFIG_AUX_DIR([build-aux])

AM_INIT_AUTOMAKE([foreign])

# Set default to --enable-shared --disable-static
LT_INIT([shared disable-static])

# find the libltdl sources in the libltdl sub-directory
LT_CONFIG_LTDL_DIR([libltdl])
```

```
# choose one
LTDL_INIT([recursive])
#LTDL_INIT([subproject])
#LTDL_INIT([nonrecursive])

# Add #define PACKAGE_AUTHOR ... in config.h with a comment
AC_DEFINE(PACKAGE_AUTHOR, ["Osamu Aoki"], [Define PACKAGE_AUTHOR])
# Checks for programs.
AC_PROG_CC

# desktop file support required
AM_GNU_GETTEXT_VERSION([0.19.3])
AM_GNU_GETTEXT([external])

# only for the recursive case
AC_CONFIG_FILES([Makefile
                  po/Makefile.in
                  lib/Makefile
                  man/Makefile
                  src/Makefile])

AC_OUTPUT
```

Let's create the **po/Makevars** file from the **po/Makevars.template** file.

po/Makevars (i18n):

```
... hack, hack, hack, ...
[dehello-2.0] $ diff -u po/Makevars.template po/Makevars
--- po/Makevars.template      2026-02-03 08:57:47.107232138 +0000
+++ po/Makevars 2026-02-03 08:57:47.188342050 +0000
@@ -18,14 +18,14 @@
 # or entity, or to disclaim their copyright. The empty string stands for
 # the public domain; in this case the translators are expected to disclaim
 # their copyright.
-COPYRIGHT HOLDER = Free Software Foundation, Inc.
+COPYRIGHT HOLDER = Osamu Aoki <osamu@debian.org>

# This tells whether or not to prepend "GNU " prefix to the package
# name that gets inserted into the header of the $(DOMAIN).pot file.
# Possible values are "yes", "no", or empty. If it is empty, try to
# detect it automatically by scanning the files in $(top_srcdir) for
# "GNU packagename" string.
-PACKAGE_GNU =
+PACKAGE_GNU = no

# This is the email address or URL to which the translators shall report
# bugs in the untranslated strings:
[dehello-2.0] $ rm po/Makevars.template
```

Let's update C sources for the i18n version by wrapping strings with **_(...)**.

src/hello.c (i18n):

```
... hack, hack, hack, ...
[dehello-2.0] $ cat src/hello.c
#include "config.h"
#include <stdio.h>
#include <sharedlib.h>
#include <libintl.h>
#define _(string) gettext (string)
int
main()
{
    printf(_("Hello, I am " PACKAGE_AUTHOR "!\n"));
    sharedlib();
    return 0;
}
```

```
}
```

lib/sharedlib.c (I18n):

```
... hack, hack, hack, ...
[debhhello-2.0] $ cat lib/sharedlib.c
#include <stdio.h>
#include <libintl.h>
#define _(string) gettext (string)
int
sharedlib()
{
    printf(_("This is a shared library!\n"));
    return 0;
}
```

The new **gettext** (v=0.19) can handle the i18n version of the desktop file directly.

data/hello.desktop.in (I18n):

```
[debhhello-2.0] $ fgrep -v '[ja]=' data/hello.desktop > data/hello.desktop.in
[debhhello-2.0] $ rm data/hello.desktop
[debhhello-2.0] $ cat data/hello.desktop.in
[Desktop Entry]
Name=Hello
Comment=Greetings
Type=Application
Keywords=hello
Exec=hello
Terminal=true
Icon=hello.png
Categories=Utility;
```

Let's list the input files to extract translatable strings in **po/POTFILES.in**.

po/POTFILES.in (I18n):

```
... hack, hack, hack, ...
[debhhello-2.0] $ cat po/POTFILES.in
src/hello.c
lib/sharedlib.c
data/hello.desktop.in
```

Here is the updated root **Makefile.am** with **po** added to the **SUBDIRS** environment variable.

Makefile.am (I18n):

```
[debhhello-2.0] $ cat Makefile.am
# recursively process `Makefile.am` in SUBDIRS
SUBDIRS = po lib src man

ACLOCAL_AMFLAGS = -I m4

EXTRA_DIST = build-aux/config.rpath m4/ChangeLog
```

Let's make a translation template file, **debhhello.pot**.

po/debhhello.pot (I18n):

```
[debhhello-2.0] $ xgettext -f po/POTFILES.in -d debhhello -o po/debhhello.pot -k...
[debhhello-2.0] $ cat po/debhhello.pot
# SOME DESCRIPTIVE TITLE.
# Copyright (C) YEAR THE PACKAGE'S COPYRIGHT HOLDER
# This file is distributed under the same license as the PACKAGE package.
# FIRST AUTHOR <EMAIL@ADDRESS>, YEAR.
#
#, fuzzy
msgid ""
msgstr ""
"Project-Id-Version: PACKAGE VERSION\n"
```

```
"Report-Msgid-Bugs-To: \n"
"POT-Creation-Date: 2026-02-03 08:57+0000\n"
"PO-Revision-Date: YEAR-MO-DA HO:MI+ZONE\n"
"Last-Translator: FULL NAME <EMAIL@ADDRESS>\n"
"Language-Team: LANGUAGE <LL@li.org>\n"
"Language: \n"
"MIME-Version: 1.0\n"
"Content-Type: text/plain; charset=CHARSET\n"
"Content-Transfer-Encoding: 8bit\n"
```

```
#: src/hello.c:9
#, c-format
msgid "Hello, I am "
msgstr ""
```

```
#: lib/sharedlib.c:7
#, c-format
msgid "This is a shared library!\n"
msgstr ""
```

```
#: data/hello.desktop.in:2
msgid "Hello"
msgstr ""
```

```
#: data/hello.desktop.in:3
msgid "Greetings"
msgstr ""
```

```
#: data/hello.desktop.in:5
msgid "hello"
msgstr ""
```

Lassen Sie uns eine französische Übersetzung hinzufügen.

po/LINGUAS und po/fr.po (l18n):

```
[dehello-2.0] $ echo 'fr' > po/LINGUAS
[dehello-2.0] $ cp po/dehello.pot po/fr.po
[dehello-2.0] $ vim po/fr.po
... hack, hack, hack, ...
[dehello-2.0] $ cat po/fr.po
# SOME DESCRIPTIVE TITLE.
# This file is put in the public domain.
# FIRST AUTHOR <EMAIL@ADDRESS>, YEAR.
#
msgid ""
msgstr ""
"Project-Id-Version: dehello 2.2\n"
"Report-Msgid-Bugs-To: foo@example.org\n"
"POT-Creation-Date: 2015-03-01 20:22+0900\n"
"PO-Revision-Date: 2015-02-21 23:18+0900\n"
"Last-Translator: Osamu Aoki <osamu@debian.org>\n"
"Language-Team: French <LL@li.org>\n"
"Language: ja\n"
"MIME-Version: 1.0\n"
"Content-Type: text/plain; charset=UTF-8\n"
"Content-Transfer-Encoding: 8bit\n"

#: src/hello.c:34
#, c-format
msgid "Hello, my name is %s!\n"
msgstr "Bonjour, je m'appelle %s!\n"

#: lib/sharedlib.c:29
#, c-format
msgid "This is a shared library!\n"
```

```
msgstr "Ceci est une bibliothèque partagée!\n"

#: data/hello.desktop.in:3
msgid "Hello"
msgstr ""

#: data/hello.desktop.in:4
msgid "Greetings"
msgstr "Salutations"

#: data/hello.desktop.in:6
msgid "hello"
msgstr ""

#: data/hello.desktop.in:9
msgid "hello.png"
msgstr ""
```

The packaging activities are practically the same as the one in „Abschnitt [14.11](#)“. You can find more i18n examples by following „Abschnitt [14.14](#)“.

14.14 Details

You can obtain detailed information about the examples presented and their variants as follows:

Wie Sie die Details erhalten

```
[base_dir] $ apt-get source debmake-doc
[base_dir] $ cd debmake-doc*
[debmake-doc-*] $ view examples/README.md
```

Follow the exact instruction in **examples/README.md**.

```
[debmake-doc-*] $ cd examples
[examples] $ make
```

Now, each directory named as **examples/debhello-??_build-?** contains the Debian packaging example.

- emulated console command line activity log: the **.log** file
- emulated console command line activity log (short): the **.slog** file
- snapshot source tree image after the **debmake** command: the **debmake** directory
- snapshot source tree image after proper packaging: the **package** directory
- snapshot source tree image after the **debuild** command: the **test** directory

Notable examples include:

- POSIX shell script with Makefile and i18n support (v=3.0)
- C source with Makefile.in + configure and i18n support (v=3.2)
- C source with Autotools and i18n support (v=3.3)
- C source with CMake and i18n support (v=3.4)

Kapitel 15

debmake(1)-Handbuchseite

15.1 BEZEICHNUNG

debmake - Programm zur Erstellung eines Debian-Quellpakets

15.2 ÜBERSICHT

debmake [-h] [-n] [-p *package*] [-u *version*] [-r *revision*] [-z *extension*] [-b "*binarypackage[:type], ...*"] [-e *foo@example.org*] [-f "*firstname lastname*"] [-i [**debuild**|**sbuild**|**dgkit** **sbuild**|**gbp** **buildpackage**|**dpkg-buildpackage**| ...]] [-m] [-q] [-v] [-V] [-w "*addon, ...*"] [-x [01234]] [-y] [-B] [*URL*]

15.3 BESCHREIBUNG

debmake helps to build the Debian package from the upstream source.

Normally, this is done as follows:

- The upstream source is obtained as a tarball from a remote web site or a cloned work tree using „**git clone**“.
 - For a tarball, it is expanded to many files in the source directory.
 - For a cloned work tree, it is used as the source directory.
- **debmake** is typically invoked in the source directory without any argument.
 - The source directory is copied to `../package-version/` directory.
 - If `../package_version.orig.tar.xz` is missing, it is generated.
 - The current directory is moved to `../package-version/`.
 - Template files are generated in the `../package-version/debian/` directory
- Files in the `../package-version/debian/` directory should be manually adjusted.
- **dpkg-buildpackage** (usually from its wrapper **debuild**, **sbuild**, ...) is invoked in the `../package-version/` directory to make Debian source and binary packages.

Also, **debmake** can be invoked with an argument. This argument can be *URL* for a tarball hosted on a remote web site or for a source code accessed by „**git clone**“; or local *PATH* to the tarball or the source code.

Arguments to **-b**, **-f**, and **-w** options need to be quoted to protect them from the shell.

Other tools also offer ways to obtain the upstream tarball and creating required symlink to build a Debian package depending on your workflow. For example, **origtargz**, **mk-origtargz**, **git-deborig**, and **pristine-tar**.

15.4 Positional arguments

URL aquire the source tree from the tarball, the git repository or the source tree at this *URL* (or *PATH*) (if missing, the source tree uses the current directory)

15.5 Options

-h, --help show this help message and exit

-n, --native make a native source package without **.orig.tar.xz**

-p, --package package set the Debian package name

-u, --upstreamversion version set the upstream package version

-r, --revision revision set the Debian package revision

-z, --tarz extension set the tarball compression type, *extension*=(**tar.xz**|**tar.gz**|**tar.bz2**) (alias: **z**, **b**, **x**)

-b, --binaryspec "binarypackage[:type], ..." set the binary package specs by a comma separated list of *binarypackage:type* pairs. Here, *binarypackage* is the binary package name, and the optional *type* is chosen from the following *type* values:

- **bin**: C/C++ compiled ELF binary code package (any, foreign) (default, alias: "", i.e., **null-string**)
- **data**: Data (fonts, graphics, ...) package (all, foreign) (alias: **da**)
- **dev**: Library development package (any, same) (alias: **de**)
- **doc**: Documentation package (all, foreign) (alias: **do**)
- **lib**: Library package (any, same) (alias: **l**)
- **perl**: Perl script package (all, foreign) (alias: **pl**)
- **python3**: Python (version 3) script package (all, foreign) (alias: **py3**, **python**, **py**)
- **ruby**: Ruby script package (all, foreign) (alias: **rb**)
- **nodejs**: Node.js based JavaScript package (all, foreign) (alias: **js**)
- **script**: Shell and other interpreted language script package (all, foreign) (alias: **sh**)

The pair values in the parentheses, such as (any, foreign), are the **Architecture** and **Multi-Arch** stanza values set in the **debian/control** file. In many cases, the **debmake** command makes good guesses for *type* from *binarypackage*. If *type* is not obvious, *type* is set to **bin**.

Here are examples for typical binary package split scenarios where the upstream Debian source package name is **foo**:

- Generating an executable binary package **foo**:
 - „**-b'foo:bin**“, or its short form „**-b'-**“, or no **-b** option
- Generating an executable (python3) binary package **python3-foo**:
 - „**-b'python3-foo:py**“, or its short form „**-b'python3-foo**“
- Generating a data package **foo**:
 - „**-b'foo:data**“, or its short form „**-b'-:data**“
- Generating a executable binary package **foo** and a documentation one **foo-doc**:
 - „**-b'foo:bin,foo-doc:doc**“, or its short form „**-b'-:-doc**“
- Generating a executable binary package **foo**, a library package **libfoo1**, and a library development package **libfoo-dev**:
 - „**-b'foo:bin,libfoo1:lib,libfoo-dev:dev**“ or its short form „**-b'-,libfoo1,libfoo-dev**“

If the source tree contents do not match settings for *type*, the **debmake** command warns you.

-e, --email *foo@example.org* set e-mail address

The default is taken from the value of the environment variable **\$DEBEMAIL**.

-f, --fullname "*firstname lastname*" set the fullname

The default is taken from the value of the environment variable **\$DEBFULLNAME**.

-i, --invoke [*debuild*|*sbuild*|*dgkit sbuild*|*gbp buildpackage*|*dpkg-buildpackage*] ...] invoke package build tool

-m, --monoarch force packages to be non-multiarch

-q, --quitearly quit early before creating files in the debian directory

-v, --version show version information

-V, --verbose use --verbose for shell commands if available

-w, --with "*addon ...*" set additional „**dh --with**“ option arguments in **debian/rules**

For Autotools based packages, if they install Python (version 3) programs, setting **python3** as *addon* to the **debmake** command argument is needed since this is non-obvious. But for **pyproject.toml** based Python packages, setting **python3** as *addon* to the **debmake** command argument is not needed since this is obvious and the **debmake** command automatically set it to the **dh(1)** command.

-x, --extra [*01234*] generate extra configuration files as templates (default: 2)

Please note **debian/changelog**, **debian/control**, **debian/copyright**, **debian/rules**, and **debian/source/format** are required configuration files to build a modern Debian binary package.

The number determines which configuration templates are generated.

- **-x0**: all 5 required configuration template files. (selected option if any of these required files already exist)
- **-x1**: all **-x0** files + desirable configuration template files with binary package type supports.
- **-x2**: all **-x1** files + normal configuration template files with maintainer script supports. (default)
- **-x3**: all **-x2** files + optional configuration template files.
- **-x4**: all **-x3** files + deprecated configuration template files.

Some configuration template files are generated with the extra **.ex** suffix to ease their removal. To activate these, rename their file names to the ones without the **.ex** suffix and edit their contents. Existing configuration files are never overwritten. If you wish to update some of the existing configuration files, please rename them before running the **debmake** command and manually merge the generated configuration files with the old renamed ones.

-y, --yes use once to „force yes“ for all prompts, twice to „force no“

-B, --backup keep the user edited ones without **.ex** suffix and create template files with **.ex** suffix

15.6 BEISPIELE

For a well behaving source, you can build a good-for-local-use installable single Debian binary package easily with one command. Test install of such a package generated in this way offers a good alternative to the traditional „**make install**“ command installing into the **/usr/local** directory since the Debian package can be removed cleanly by the „**dpkg -P '...'**“ command. Here are some examples of how to build such test packages.

For a typical C program source tree packaged with **autoconf/automake**:

- **debmake -i sbuild**

Für einen typischen Python-(Version 3-)Modulquellbaum:

- **debmake -b":python3" -i sbuild**

For a typical Python (version 3) module in the *package-version.tar.xz* archive:

- **debmake** *package-version.tar.xz* -b":python3" -i sbuild

For a typical Perl module in the *package-version.tar.xz* archive:

- **debmake** *package-version.tar.xz* -b":perl" -i sbuild

15.7 HELFERPAKETE

Die Paketierung könnte die Installation einiger zusätzlicher, spezialisierter Helferpakete benötigen.

- Python (version 3) programs may require the **pybuild-plugin-pyproject** package.
- The Autotools (**autoconf** + **automake**) build system may require **autotools-dev** or **dh-autoreconf** package.
- Ruby-Programme könnten das Paket **gem2deb** benötigen.
- Node.js based JavaScript programs may require the **pkg-js-tools** package.
- Java-Programme könnten das Paket **javahelper** benötigen.
- Gnome-Programme könnten das Paket **gobject-introspection** benötigen.
- usw.

15.8 CAVEAT

Although **debmake** is meant to provide template files for the package maintainer to work on, actual packaging activities are often performed without using **debmake** while referencing only existing similar packages and „[Debian Policy Manual](#)“. All template files generated by **debmake** are required to be modified manually.

There are some points for **debmake**:

- **debmake** helps to write terse packaging tutorial „[Guide for Debian Maintainers](#)“ (**debmake-doc** package).
- **debmake** provides short extracted license texts as **debian/copyright** in decent accuracy to help license review.
- „[Guide for Debian Maintainers](#)“ also serves as a tutorial with examples for the usage of **debmake**.
- **debmake** internally calls **licensecheck** from the **licensecheck** package to create **debian/copyright** if it doesn't exist.
- **debmake** internally calls **lrc** from the **licenserecon** package to verify **debian/copyright** if it already exists.

There are some limitations for what characters may be used as a part of the Debian package. The most notable limitation is the prohibition of uppercase letters in the package name. Here is a summary as a set of regular expressions:

- Upstream package name (-p): `[-+ . a - z 0 - 9] { 2 , }`
- Binary package name (-b): `[-+ . a - z 0 - 9] { 2 , }`
- Upstream version (-u): `[0 - 9] [-+ . : ~ a - z 0 - 9 A - Z] *`
- Debian revision (-r): `[0 - 9] [+ . ~ a - z 0 - 9 A - Z] *`

See the exact definition in „[Chapter 5 - Control files and their fields](#)“ in the „[Debian Policy Manual](#)“.

debmake assumes relatively simple packaging cases. So all programs related to the interpreter are assumed to be „**Architecture: all**“. This is not always true.

15.9 **DEBUG**

Bitte berichten Sie Fehler (auf Englisch) mittels des Befehls **reportbug** gegen das Paket **debmake**.
The character set in the environment variable **\$DEBUG** determines the logging output level.

- **s**: program progress logging
- **p**: key para[.] value logging
- **P**: all para[.] value logging
- **d**: para["debs"] value logging

Use this feature as:

```
[base_dir] $ export DEBUG=spd; debmake ...
```

See **README.md** in the source for more.

15.10 **AUTOR**

Copyright © 2014-2026 Osamu Aoki <osamu@debian.org>

15.11 **LIZENZ**

Expat-Lizenz

15.12 **SIEHE AUCH**

The **debmake-doc** package provides the „[Guide for Debian Maintainers](#)“ in plain text, HTML and PDF formats under the **/usr/share/doc/debmake-doc/** directory.

See also **licensecheck(1)**, **lrc(1)**, **dpkg-source(1)**, **deb-control(5)**, **debhelper(7)**, **dh(1)**, **dpkg-buildpackage(1)**, **debuild(1)**, **quilt(1)**, **dpkg-depcheck(1)**, **sbuid(1)**, **gbp-buildpackage(1)**, and **gbp-pq(1)** manpages.

Kapitel 16

debmake options

Here are some additional explanations for **debmake** options.

16.1 Shortcut option (-i)

The **debmake** command offers a shortcut option.

- **-i**: Ausführen der Skripte zum Bau des Binärpakets

Das Beispiel in obigem „Kapitel 5“ kann so einfach wie folgt sein.

```
[base_dir] $ debmake package-1.0.tar.xz -i debuild
```

Tipp



A URL such as „<https://www.example.org/DL/package-1.0.tar.xz>“ for a tarball, „<https://github.com/username/package.git>“ for a git repository, or „[/path/to/source_dir](#)“ for a local source tree may be used as an argument.

16.2 debmake -b

The **debmake** command with the **-b** option provides an intuitive and flexible method to create the initial template **debian/control** file. This file defines the split of the Debian binary packages with the following stanzas:

- **Package:**
- **Architecture:** (e.g. **amd64**)
- **Multi-Arch:** (see „Abschnitt 10.10“)
- **Depends:**
- **Pre-Depends:**

The **debmake** command also sets an appropriate set of substvars (substitution variables) used in each pertinent dependency stanza.

Let's quote the pertinent part from the **debmake** manpage here.

-b, --binaryspec "*binarypackage*[:*type*], ..." set the binary package specs by a comma separated list of *binarypackage*:*type* pairs. Here, *binarypackage* is the binary package name, and the optional *type* is chosen from the following *type* values:

- **bin**: C/C++ compiled ELF binary code package (any, foreign) (default, alias: `""`, i.e., **null-string**)
- **data**: Data (fonts, graphics, ...) package (all, foreign) (alias: **da**)
- **dev**: Library development package (any, same) (alias: **de**)
- **doc**: Documentation package (all, foreign) (alias: **do**)
- **lib**: Library package (any, same) (alias: **l**)
- **perl**: Perl script package (all, foreign) (alias: **pl**)
- **python3**: Python (version 3) script package (all, foreign) (alias: **py3**, **python**, **py**)
- **ruby**: Ruby script package (all, foreign) (alias: **rb**)
- **nodejs**: Node.js based JavaScript package (all, foreign) (alias: **js**)
- **script**: Shell and other interpreted language script package (all, foreign) (alias: **sh**)

The pair values in the parentheses, such as (any, foreign), are the **Architecture** and **Multi-Arch** stanza values set in the **debian/control** file. In many cases, the **debmake** command makes good guesses for *type* from *binarypackage*. If *type* is not obvious, *type* is set to **bin**.

Here are examples for typical binary package split scenarios where the upstream Debian source package name is **foo**:

- Generating an executable binary package **foo**:
 - „**-b'foo:bin'**“, or its short form „**-b'-**“, or no **-b** option
- Generating an executable (python3) binary package **python3-foo**:
 - „**-b'python3-foo:py'**“, or its short form „**-b'python3-foo'**“
- Generating a data package **foo**:
 - „**-b'foo:data'**“, or its short form „**-b'-:data'**“
- Generating a executable binary package **foo** and a documentation one **foo-doc**:
 - „**-b'foo:bin,foo-doc:doc'**“, or its short form „**-b'-:-doc'**“
- Generating a executable binary package **foo**, a library package **libfoo1**, and a library development package **libfoo-dev**:
 - „**-b'foo:bin,libfoo1:lib,libfoo-dev:dev'**“ or its short form „**-b'-,libfoo1,libfoo-dev'**“

If the source tree contents do not match settings for *type*, the **debmake** command warns you.

16.3 debmake -B

The **debmake** command invoked with the **-B** option can generate template files with **.ex** suffix. This is handy if you want to see auto-generated template files to the existing ones.

16.4 debmake -x

The amount of template files generated by the **debmake** command depends on the **-x[01234]** option.

- See „Abschnitt 14.1“ for cherry-picking of the template files.

Anmerkung



None of the existing configuration files are modified by the **debmake** command.